



Transformers

MARS SERIES **503**

COMPONENT

50321
50327
50341
50375



MARS Control Transformers NEMA Class II Manual Reset Style


MARS control transformers are available with various outputs and voltages for special applications.

Application:

Provide power source for control circuit for air conditioning, heating, or refrigeration systems.

Features:

- UL class 2 recognized
- Low heat rise
- Color coded leads or quick connect terminals
- Foot-mount



50380

MARS Power Transformers

Application:

Provide 120V power source for air conditioning, heating, or refrigeration systems. MARS power transformers provide dual purpose options — **120V** or **24V secondary** with 208V/240V/480V primary connections. Three VA selections offer a true powerhouse!

Features:

- Color coded leads
- Compact size
- Low heat rise

Foot-Mount End Bell Type with Manual Reset

MARS NO.	FORMER MARS JARD NO.	JARD NO.	VA RATING	HZ	PRIMARY		SECONDARY	
					VOLTAGE	CONNECTIONS	VOLTAGE	CONNECTIONS
50327	44511	5041C	50	60	120/208/240/480	Color coded leads	24	Color coded leads
50321	44513	7541C	75	50/60	120/208/240/480	Color coded leads	24	Color coded leads
50375	-	-	75	50/60	120/208/240/575	Color coded leads	24	Color coded leads
50341*	44515	10041C	100	50/60	120/208/240/480	Color coded leads	24	Color coded leads
50312	44512	6041C	60	50/60	120/208/240/480	Color coded leads	24	Color coded leads
50370	44514	7541STC	75	50/60	120/277/380/575	Color coded leads	24	Color coded leads
50371	44516	10041STC	100	50/60	120/208/277/575	Color coded leads	24	Color coded leads

Power Transformers Foot-Mount Open Construction

MARS NO.	FORMER MARS JARD NO.	JARD NO.	VA RATING	HZ	PRIMARY		SECONDARY	
					VOLTAGE	CONNECTIONS	VOLTAGE	CONNECTIONS
50380 ⁽¹⁾	44536	5024P	50	60	208/240/480	Color coded leads	120/24	Color coded leads
50381 ⁽²⁾	-	-	100	60	208/240/480	Color coded leads	120/24	Color coded leads

* 100VA and higher does not qualify for NEMA Class II

(1) Not UL listed

(2) UL 506