SPECIFICATIONS

FLOW SWITCH

Red tamper proof switch housing with flow paddle. Adjustable pneumatic retard setting from 0 to 70 seconds. Two single pole, double throw microswitches to operate separate circuits, 120 Volt A.C. UL Listed for schedule 10 and 40 steel water pipe. Type and size as selected by model number.

MODEL SELECTION

FLOW SWITCHES ☐ 6201 2" For Steel Tube

- ☐ 6202 2-1/2" For Steel Tube
- ☐ 6203 3" For Steel Tube
- ☐ 6204 3-1/2" For Steel Tube
- ☐ 6205 4" For Steel Tube
- ☐ 6206 5" For Steel Tube
- ☐ 6207 6" For Steel Tube
- ☐ 6208 8" For Steel Tube
- ☐ **6211** 2" For Copper Tube
- ☐ **6212** 2-1/2" For Copper Tube
- ☐ 6216 Tee Type with Retard
- ☐ 6217 Tee Type without Retard

SUPERVISORY SWITCHES

- ☐ 6220 For OS&Y Gate valves
- ☐ 6222 For Sprinkler System Valves
- ☐ 6223 For Post Indicator Type Valves & Regulating Valves

ACCESSORIES

☐ 6230 Bell

☐ 12 Volts ☐ 24 Volts

☐ 6235 Bell Guard

☐ 6240 Pressure Gauge (UL Listed)

PRODUCT OPTIONS

"NO AVAILABLE OPTIONS"



MODELS





SUPERVISORY SWITCH

MODEL 6222

SUPERVISORY SWITCH **MODEL 6220**

Contact Ratings: 10A @ 125/250 VAC .5A @ 24 VDC



SUPERVISORY SWITCH **MODEL 6223**

MODEL 6230



BELL GUARD MODEL 6235



PRESSURE GAUGE **MODEL 6240**

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer- Fire Pro, Member of Morris Group International ™ Please visit potterroemer.com for most current specifications.

6201-6240 SERIES Date: 09/20/18









POTTER ROEMER/FIRE PRO

Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890

Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473

www.potterroemer.com