


**Reducer Bushing
 Flush Style**

Spigot x Socket



(Continued)

Part Number	Size	L	N	Approx. Wt. (Lbs.)
837-490F*	5X4	3	3/4	1.25
837-524 ¹	6X3/4	3-3/4	2-3/4	3.09
837-525 ¹	6X1	3-13/16	2-11/16	3.11
837-526 ¹	6X1-1/4	3-3/4	2-1/2	3.06
837-527 ¹	6X1-1/2	3- 3/4	2-11/32	3.01
837-528	6X2	3-1/2	2	2.87
837-529	6X2-1/2	3-7/8	2-1/8	3.37
837-530	6X3	3-1/2	1-5/8	2.83
837-532	6X4	3-1/2	1- 1/4	2.67
837-533F*	6X5	3	7/16	1.54
837-534	6X5	3-17/32	7/8	1.94
837-577 ¹	8X1-1/2	5-1/8	3-3/4	6.35
837-578 ¹	8X2	4-15/16	3- 3/8	6.21
837-580 ¹	8X3	4-13/16	2-15/16	6.02
837-582 ¹	8X4	4- 1/2	2- 1/4	5.20
837-583 ¹	8X5	4-29/32		7.06
837-583F*	8X5	4-7/16	1-3/4	6.66
837-585	8X6	4- 3/8	1- 3/8	5.12
837-621 ¹	10X2	5-13/16	4-5/16	13.18
837-622 ¹	10X2-1/2	6-5/32	4-3/8	13.51
837-623 ¹	10X3			13.14
837-624 ¹	10X4	5-27/32	3-9/16	12.98
837-625F*	10X5	5-5/16	2-11/16	11.85
837-626	10X6	5- 5/16	2-5/16	10.30
837-628	10X8	5-5/16	1-5/16	10.70
837-628F*	10X8	5-1/4	1-1/4	8.12
837-663 ¹	12X3	7-5/32	5-9/32	21.09
837-664 ¹	12X4	6-13/16	4-9/16	20.28
837-666 ¹	12X6	6-23/32	3-23/32	20.19
837-666F ^{1*}	12X6	6-3/8	3-5/16	21.34
837-668	12X8	6-5/16	2-5/16	15.07
837-668F ^{1*}	12X8	6-3/8	2-5/16	21.74
837-670	12X10	6-5/16	1-5/16	14.16
837-670F*	12X10	6	1	11.03
837-694F*	14X4	7-13/16	5-13/16	29.64
837-696F*	14X6	7- 3/4	4-11/16	29.55
837-698F*	14X8	7-5/16	3-5/16	24.43
837-700F*	14X10	7-5/16	2-5/16	22.30
837-702F*	14X12	7	1	9.36
837-754F*	16X4	8-13/16	6-13/16	51.58