

# 120 VOLT WATER HEATER ELEMENTS

**Fig. 1**

**Fig. 2**

**Fig. 3**


## HIGH WATT DENSITY ELEMENTS

PROSELECT PN	OLD PROSELECT PN	VOLTAGE	WATTS @ 120	WATTS @ 110	"A" DIA.	THREAD NPSM	NUT SIZE	MINIMUM TANK DIA.	WATT DENSITY	PIC FOR FIGURE	ADDITIONAL FEATURES
PSW12305	PF9000129PK	120	1440	1210	8"	1"	1-1/2"	9"	High	Fig. 1	High watt density screw in element for point of use and small tank design electric water heaters
PSW12313	PF9000177PK	120	1500	1260	8"	Flange	N/A	9"	High	Fig. 1	High watt density universal flange element for point of use and small tank design electric water heaters
PSW12306	PF9000130PK	120	2000	1681	12"	1"	1-1/2"	13"	High	Fig. 1	High watt density screw in element for point of use and small tank design electric water heaters

A dimension is measured from flange to end of element

## LOW WATT DENSITY ELEMENTS

PROSELECT PN	OLD PROSELECT PN	VOLTAGE	WATTS @ 120	WATTS @ 110	"A" DIA.	THREAD NPSM	NUT SIZE	MINIMUM TANK DIA.	WATT DENSITY	PIC FOR FIGURE	ADDITIONAL FEATURES
PSW12320	PF9000253PK	120	1650	1386	15"	1"	1-1/2"	16"	Low	Fig. 2	Low watt density screw in element for point of use and small tank design electric water heaters

A dimension is measured from flange to end of element

## ADAPTORS

PROSELECT PN	OLD PROSELECT PN	FEATURES	PIC FOR FIGURE	ADDITIONAL FEATURES
PSW12317	PF9000030PK	Adapter kit for installing screw-in flanged elements to four bolt flanged element openings.	Fig. 3	Includes gaskets, hardware, bracket, & install instructions

A dimension is measured from flange to end of element

## Warranty and Codes

These PROSELECT products carry a 1-year limited warranty.