

## SPLINE ONE-PIECE CORE BITS

### OVERVIEW

MILWAUKEE's One-Piece Carbide Tipped Core Bits are ideal for drilling large holes where the depth is relatively shallow. The core bit cuts a kerf only. The inside core must be removed by the operator before deeper drilling can be accomplished. Centering Bit 48-20-5495 is included. Use Drift Key 48-20-5497 (not included) to remove centering bit from the one-piece core bit. The one-piece core bits are available in SDS Max or Spline shanks. They come in a variety of diameters ranging from 1-1/2" to 6" with overall lengths of 11-3/8" or 22" and a drilling depth of 3". The asymmetric tooth pitch with alternating tooth geometries creates faster material pulverization. The one-piece design maximizes energy transfer and the thick wall core body is durable even in large hammers. The fluted core exterior minimizes friction loss and removes debris faster.

### FEATURES

- Asymmetrical and Alternating Teeth for faster material pulverization
- Thick Wall Core Body for durability even in large hammers
- Includes Centering Bit to reduce bit walking and create exact spot drilling

#### SPLINE ONE-PIECE CORE BITS

| Diameter | Length  | Part No.   |
|----------|---------|------------|
| 1-1/2"   | 11-3/8" | 48-20-5450 |
| 1-1/2"   | 22"     | 48-20-5452 |
| 1-3/4"   | 11-3/8" | 48-20-5454 |
| 1-3/4"   | 22"     | 48-20-5456 |
| 2"       | 11-3/8" | 48-20-5458 |
| 2"       | 22"     | 48-20-5460 |

| Diameter | Length  | Part No.   |
|----------|---------|------------|
| 2-5/8"   | 11-3/8" | 48-20-5462 |
| 2-5/8"   | 22"     | 48-20-5464 |
| 3-1/8"   | 11-3/8" | 48-20-5470 |
| 3-1/8"   | 22"     | 48-20-5472 |
| 3-9/16"  | 11-3/8" | 48-20-5478 |
| 3-9/16"  | 22"     | 48-20-5480 |

| Diameter | Length  | Part No.   |
|----------|---------|------------|
| 4"       | 11-3/8" | 48-20-5482 |
| 4"       | 22"     | 48-20-5484 |
| 5"       | 11-3/8" | 48-20-5486 |
| 5"       | 22"     | 48-20-5488 |
| 6"       | 22"     | 48-20-5490 |

#### SPLINE ONE-PIECE CORE BITS ACCESSORIES

| Description                           | Part No.   |
|---------------------------------------|------------|
| Centering Bit for One-Piece Core Bits | 48-20-5495 |
| Drift Key for One-Piece Core Bits     | 48-20-5497 |

## SPLINE OR ROUND/HEX DEMOLITION STEEL



#### SPLINE OR ROUND/HEX DEMOLITION STEEL

| Style      | Size | 1 Pack     | 15 Pack (Bulk) | 25 Pack (Bulk) |
|------------|------|------------|----------------|----------------|
| Bull Point | 12"  | 48-62-2000 | -              | 48-62-2100     |

#### SPLINE OR ROUND/HEX DEMOLITION STEEL

| Style             | Size                        | 1 Pack     | 15 Pack (Bulk) | 25 Pack (Bulk) |
|-------------------|-----------------------------|------------|----------------|----------------|
| Bull Point        | 18"                         | 48-62-2010 | -              | 48-62-2110     |
| Bushing Tool      | 1-3/4" x 9-1/2"             | 48-62-2070 | 48-62-2170     | -              |
| Clay Spade        | 4-1/2" x 16-3/4"            | 48-62-2095 | -              | -              |
| Flat Chisel       | 1" x 12"                    | 48-62-2020 | -              | 48-62-2120     |
| Flat Chisel       | 1" x 18"                    | 48-62-2030 | -              | 48-62-2130     |
| Ground Rod Driver | 10"L - 5/8" & 3/4" Rod Dia. | 48-62-2046 | -              | -              |
| Scaling Chisel    | 1-1/2" x 12"                | 48-62-2040 | -              | -              |
| Scaling Chisel    | 2" x 12"                    | 48-62-2050 | -              | 48-62-2150     |
| Scaling Chisel    | 3" x 12"                    | 48-62-2055 | -              | 48-62-2155     |
| Scaling Chisel    | 4-1/2" x 14"                | 48-62-2057 | -              | -              |
| Scraping Chisel   | 2" x 12"                    | 48-62-2065 | -              | -              |
| Seam Tool         | 1" x 12"                    | 48-62-2080 | -              | -              |
| Slotting Chisel   | 1-1/4" x 12"                | 48-62-2060 | -              | -              |
| Tamper Plate      | 5" x 5"                     | 48-62-3060 | -              | -              |
| Tamper Shank      | 12"                         | 48-62-2097 | -              | -              |

## 3/4" HEX DEMOLITION STEEL



#### 3/4" HEX DEMOLITION STEEL

| Style             | Size                           | Part No.   |
|-------------------|--------------------------------|------------|
| Asphalt Cutter    | 5" x 16-1/2"                   | 48-62-3090 |
| Bull Point        | 12"                            | 48-62-3000 |
| Bull Point        | 18"                            | 48-62-3005 |
| Bushing Tool      | 1-3/4" x 9-1/2"                | 48-62-3085 |
| Clay Spade        | 4-1/2" x 16-3/4"               | 48-62-3040 |
| Flat Chisel       | 1" x 12"                       | 48-62-3010 |
| Flat Chisel       | 1" x 18"                       | 48-62-3015 |
| Ground Rod Driver | 9-3/4"L - 5-8" & 3/4" Rod Dia. | 48-62-3070 |
| Scaling Chisel    | 1-1/2" x 12"                   | 48-62-3020 |
| Scaling Chisel    | 2" x 12"                       | 48-62-3035 |
| Scaling Chisel    | 3" x 12"                       | 48-62-3030 |
| Scraping Chisel   | 2" x 12"                       | 48-62-3025 |
| Tamper Shank      | 12"                            | 48-62-3065 |