## PLASTIC & CAST IRON TWO FINGER FLANGE



## **Two Finger Flange**

- Positive seal
- Redesigned to fit oblong horns
- Easy to push to install or adjust
- Flush fit
- Choice of closet bolt slots or slide positioning
- Double lip seal gasket
- May be used on PVC, ABS, or Cast Iron pipe and on old lead pipe that is in good condition
- Pushes easily into 3" or 4" cast iron or Schedule 40 DWV PVC pipe
- ASTM C-564 rubber gasket
- No tear out or caulking required of existing pipe
- Patent #: 5,937,450



ones Stephens Corp.



JSC South 3249 Moody Parkway Moody, AL 35004 Phone 800-355-6637

Fax 800-462-6991

JSC North 50 Keystone Blvd. East Pottsville, PA 17901 Phone 800-325-8999 Fax 866-922-0076

00861-01

## **Two Finger Flange**

- Positive seal
- Redesigned to fit oblong horns
- Easy to push to install or adjust
- Flush fit
- Choice of closet bolt slots or slide positioning
- Double lip seal gasket
- May be used on PVC, ABS, or Cast Iron pipe and on old lead pipe that is in good condition



•	Pushes easily into 3" or 4" cast iron or
	Schedule 40 DWV PVC pipe

- ASTM C-564 rubber gasket
- No tear out or caulking required of existing pipe
- Patent #: 5,937,450

PART NO.	SIZE	MATERIAL	CTN QTY
C4733P	3″ × 3″	WHITE PLASTIC	6
C4733A	3″ × 3″	BLACK PLASTIC	6
C4743P	4" x 3"	WHITE PLASTIC	6
C4743A	4" x 3"	BLACK PLASTIC	6



\* 3" x 4", 4" x 4" and 4" x 6": for areas without the bend close to the flange or broken pipe

PART NO.	SIZE	MATERIAL	CTN QTY
C47320	3″ x 2″	CAST IRON	8
C47340	3″ x 4″	CAST IRON	4
C47420	4" x 2"	CAST IRON	8
C47430	4" x 3"	CAST IRON	4
C47440	4" x 4"	CAST IRON	4
C47460	4″ x 6″	CAST IRON	2

Contact a Jones Stephens Representative for more information. Specifications and pricing available upon request.