

Tubing - Polyethylene



Polyethylene Tubing Features:

- Conforms to FDA, NSF and USDA Standards.
- Temperature Range -100° F to +140° F
- Economical.
- Extremely Flexible.
- Translucent.
- Resists Corrosion.
- **NOT FOR USE WITH HOT WATER**



- **SOLD IN COIL LENGTHS ONLY.**
- ORDER BY THE NUMBER COIL LENGTHS REQUIRED.
Ex: For 500' of MV4040-5 order Qty 1 MV4040-5

Part Number Bulk Boxed	Part Number Dispenser Box	OD	ID	Wall Thickness	Max PSI @ 70°F	Coil Length
MV4040-1BLACK		1/4"	.17"	0.04"	135	100'
MV4040-1		1/4"	.17"	0.04"	135	100'
MV4040-5		1/4"	.17"	0.04"	135	500'
MV4040M		1/4"	.17"	0.04"	135	1000'
MV4062-1		1/4"	1/8"(.125)	1/16"(.062)	180	100'
MV4062-5		1/4"	1/8"(.125)	1/16"(.062)	180	500'
MV4062M		1/4"	1/8"(.125)	1/16"(.062)	180	1000'
MV5062-1		5/16"	3/16"(.1875)	1/16"(.062)	140	100'
MV5062-5		5/16"	3/16"(.1875)	1/16"(.062)	140	500'
MV5062M		5/16"	3/16"(.1875)	1/16"(.062)	140	1000'
MV6062-1		3/8"	1/4"(.250)	1/16"(.062)	120	100'
MV6062-5		3/8"	1/4"(.250)	1/16"(.062)	120	500'
MV6062-5BLACK		3/8"	1/4"(.250)	1/16"(.062)	120	500'
MV6062M		3/8"	1/4"(.250)	1/16"(.062)	120	1000'
MV8062-1		1/2"	3/8"(.375)	1/16"(.062)	90	100'
MV8062-5		1/2"	3/8"(.375)	1/16"(.062)	90	500'
MV10062-1		5/8"	1/2"(.500)	1/16"(.062)	70	100'
MV10062-5		5/8"	1/2"(.500)	1/16"(.062)	70	500'
MV12075-1		3/4"	.6	.075	60	100'
MV16093-1		1"	.814	3/32"(.094)	55	100'
TP309		5/16"	3/16"(.1875)	1/16"(.062)		100'



POLYETHYLENE TUBING SIZING GUIDE

