

THIN HIGH SPEED CUT-OFF



GENERAL PURPOSE

A24R

- Aluminum oxide grain
- General purpose, long life

METAL Ferrous metals (iron, steel, welds, etc.)



FAST CUTTING

A36T

- Aluminum oxide grain
- Hard bond for aggressive cutting on rough applications

METAL Ferrous metals (iron, steel, welds, etc.)

STAINLESS Stainless steel



BURR FREE

A60T

- Hard bond for smooth cutting
- For use in nuclear, aerospace, automotive, foundry industries, and plant maintenance

METAL Ferrous metals (iron, steel, welds, etc.)

STAINLESS High tensile metals



PREMIUM PERFORMANCE

SAITECH ULTIMATE PERFORMANCE™

- High performance, ceramic aluminum oxide grain
- Very uniform, high density grain structure is extremely durable and self sharpening for long life and cooler cut
- High Performance
- Combines fast cutting with extremely long life

STAINLESS Stainless steel, high tensile alloys


METAL Ferrous and/or non-ferrous metals

DIA	THICK	ARBOR	MAX RPM	QTY	A24R General Purpose	A36T Fast Cutting	A60T Burr Free	SAITECH ULTIMATE PERFORMANCE™
2"	1/16"	1/4"	30,558	50	–	23004	23005	–
2"	1/16"	3/8"	30,558	50	–	23002	23003	–
2"	.035"	1/4"	30,558	100	–	23012	23013	–
2"	.035"	3/8"	30,558	100	–	23010	23011	–
2-1/2"	1/16"	1/4"	24,446	50	–	23022	23023	–
2-1/2"	1/16"	3/8"	24,446	50	–	23020	23021	–
2-1/2"	.035"	1/4"	24,446	100	–	23032	23033	–
2-1/2"	.035"	3/8"	24,446	100	–	23030	23031	–
3"	1/16"	1/4"	25,000	50	–	23042	23043	23142
3"	1/16"	3/8"	25,000	50	–	23040	23041	23140
3"	.035"	1/4"	25,000	100	–	23052	23053	23152
3"	.035"	3/8"	25,000	100	–	23050	23051	23150
3"	1/8"	3/8"	20,372	25	23060	–	–	–
4"	1/16"	1/4"	19,000	50	–	23067	23068	23167
4"	1/16"	3/8"	19,000	50	–	23065	23066	23165
4"	1/16"	5/8"	19,000	50	–	23061	23062	23161
4"	.035"	1/4"	19,000	100	–	23071	23072	23171
4"	.035"	3/8"	19,000	100	–	23069	23070	23169
4"	.035"	5/8"	19,000	100	–	23063	23064	23163
4"	1/8"	3/8"	15,278	25	23075	–	–	–

1/4" shank adapters for wheels up to 3" diameter available on page 130

TECH INFO

- Type 1 / Type 41 shape for square, burr-free cutting
- Saitech™, manufactured with premium ceramic grain, is designed to outlast standard aluminum oxide wheels
- Externally reinforced with fiberglass layers to provide ultimate safety in a thin wheel



Type 1 / Type 41



Die Grinder