

PC 657[®]

Shurtape[®]
TRUE TO YOUR WORK[™]

HEAVY DUTY, PROFESSIONAL GRADE CO-EXTRUDED CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- For use in high performance motorsports applications, pre-manufactured housing and RV assembly, critical industrial applications and for protection during metal-peening and sandblasting operations

PRODUCT FEATURES

- Excellent holding power
- Easy to unwind and tear
- Withstands extreme temperature fluctuations
- Made using Polybonded CO-EX Technology[®]

CONSTRUCTION

Overall Grade/Function: Heavy Duty Professional
Backing: Waterproof polyethylene film with a cloth carrier
Adhesive: Natural rubber

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes


APPLICABLE STANDARDS

Tested in accordance with UL 723; FSI 15/SDI 40

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES STANDARD METRIC

Tensile Strength	45 lbs/in width	78.8 N/10 mm
Adhesion to Stainless Steel	100 oz/in width	10.95 N/10 mm
Thickness	14.5 mils	0.37 mm
Elongation	14%	14%
Service Temperature Range	40 F to 200 F	4 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

