115 Standard Duty Loop Hanger – 1150300EG











The 115 Standard Duty Loop Hanger is ideal for suspending stationary, non-insulated pipe lines, including CPVC pipes, in fire sprinkler systems. A knurled insert nut helps simplify vertical adjustments and flared edges on the base [1/2" to 4" sizes] help protect pipes from coming into contact with any sharp edges of the hanger.

- Flared edges help prevent any sharp surfaces from coming into contact with the pipe (1/2" to 4" sizes)
- Retained insert nut helps ensure the loop hanger and insert nut stay together
- Recommended for the suspension of stationary non-insulated pipe lines
- Manufactured to use the minimum rod size permitted by NFPA® for fire sprinkler piping
- Conforms with Federal Specification WW-H-171 (Type 10), Manufacturers Standardization Society (MSS) SP-58 (Type 10)







Part Number	1150300EG
Material	Steel
Finish	Pregalvanized
Pipe Size	3"
Outer Diameter (OD)	3 1/2"
Rod Size (RS)	3/8"
А	6 9/16"
В	3 1/2"
С	1 15/16"
Static Load (F)	525 lb
Certifications	cULus FM
Standard Packaging Quantity	50 pc
UPC	78285633960
EAN-13	8711893090611



FM is a registered certification mark of FM Approvals LLC, LTD. NFPA is a registered trademark of National Fire Protection Association, Inc. UL, UR, cUL, cUR, cULus and cURus are ${\sf registered} \ {\sf certification} \ {\sf marks} \ {\sf of} \ {\sf UL} \ {\sf LLC}.$

nevent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

