

PFXCH

Corrugated Water Heater Connector



Product Features

- Stainless steel corrugated
- Kink resistant
- IAPMO listed
- NSF/ANSI 61 compliant
- AB 1953 compliant
- ASME A112.18.6
- Max Pressure: 125 PSI
- Working Temperature: 40°F–160°F
- Max Temperature: 180°F
- Built-in dielectric sleeve to prevent possible galvanic corrosion
- 100% leak tested
- Exterior Clear Coat – Provides enhanced corrosion resistance against chemical exposure and aggressive environmental conditions that can contribute to localized attack and pinhole leaks.



PFXCHGU18N

Materials

- Tubing: Stainless steel 304 (ASTM A240)
- Nut: Chrome-plated brass 3771
- Gasket: High-quality EPDM

Codes and Certifications



Product Specifications

Model Number	Description	Length (in.)	Length (mm)
PFXCHF18PN	LF 3/4" FIP x F1807	18	457.2
PFXCHF18PPN	LF 3/4" FIP x F1960	18	457.2
PFXCHF24PN	LF 3/4" FIP x F1807	24	609.6
PFXCHF24PPN	LF 3/4" FIP x F1960	24	609.6
PFXCHFT18NN	LF 3/4" FIP	18	457.2
PFXCHFT24NN	LF 3/4" FIP	24	609.6
PFXCHF18NN	LF 3/4" FIP x PUSH	18	457.2
PFXCHFW18NN	LF 3/4" FIP x SWT	18	457.2
PFXCHFW24NN	LF 3/4" FIP x SWT	24	609.6
PFXCHGFT24NN	LF 1" x 3/4" FIP	24	609.6
PFXCHGT18N	LF 1" FIP	18	457.2
PFXCHGT24N	LF 1" FIP	24	609.6
PFXCHHT18N	LF 1-1/4" FIP	18	457.2
PFXCHJT18N	LF 1-1/2" FIP	18	457.2

For detailed warranty information, visit ferguson.com/PROFLO-1-year-warranty.