

Quick Zip Pipe Hanger

Job Name	_____
Location	_____
Engineer	_____
Contractor	_____
Tag	_____ PO# _____

Specifications

- Neatly hangs and safely secures pipes and cables, including PVC/DWV, Copper, PEX, and more
- 14" or 26" hanger stick
- Hanger stick features embossed measurements for accurate placement
- Constructed of corrosion-resistant polypropylene
- Nails are included
- Straps can support 1" CTS to 6" IPS pipes
- Working temperature: 0°~140°F (-17.8°C~60°C)
- Can support up to a 50 lb load

Applications

- DWV (Drain, Waste, And Vent)


Materials

- Stem: ABS, U.V. resistant, corrosion-proof, impact-resistant
- Strap: High-heat polypropylene, U.V. resistant
- Nail: 1.575" rust-resistant, zinc-plated, continuous rink shank

Dimensions and Product Offerings

Part No.	Size	A	B	C	D
QZH14	14"	20"	.76"	1"	13.79"
QZH26	26"	20"	.76"	1"	25.79"

Certifications/Listings/Approvals



Safe Working Loads

Fahrenheit	Celcius	Load Capacity
32°F	0°C	50 lbs
72°F	22.2°C	50 lbs
140°F	60°C	25 lbs

