THREADED ACCESSORIES



COACH SCREW ROD

FIG. 40

Function: Designed for use as a vertical hanger attachment to wood

structures.

Material: Carbon steel

Finish: Plain or electro-galvanized

Ordering: Specify figure number, rod size, length (D), and finish.

l - .	-D	
		− B−−
-0000000000000000000000000000000000000		
***************************************	Α-	

	Rod Size A	Minimum Length			Max. Rec Load		Wt. Each										
							Length D										
		Machine B		Coach		lbs.	kN	4 (101.6)		6 (152.4)		8 (203.2)		10 (254.0)		12 (304.8)	
					С	IDS.	KIN	lbs.	kg	lbs.	kg	lbs.	kg	lbs.	kg	lbs.	kg
Ī	3/8	2	(50.80)	2	(50.80)	390	(1.73)	.12	(0.05)	.19	(0.09)	.25	(0.11)	.31	(0.14)	.37	(0.17)
	1/2	2	(50.80)	21/2	(63.50)	640	(2.85)	.22	(0.10)	.34	(0.15)	.44	(0.20)	.56	(0.25)	.67	(0.30)

CPVC STRAPS

CENTER LOAD BEAM CLAMPS

PIPE SHIELDS, INSULATION, & SADDLES