

UNDERGROUND PIPE CLAMPS



FUNCTION: Designed to secure tie rods when used in conjunction with Fig. 580 two bolt underground pipe clamp.

MATERIAL: Low carbon steel. Cast Iron ($\frac{3}{4}$ " Tie Rod Only)

FINISH: Plain

ORDERING: Specify tie rod size and figure number.

**Fig. 585
WASHER
For Fig. 580**

Available in stainless steel except for $\frac{3}{4}$ " tie rod.

To order, specify 304 or 316 and add suffix SS to figure number.

Price on request.

Tie Rod Size	Dia B	C	D	E	For Pipe Sizes	Wt. Each (in lbs.)
$\frac{3}{4}$	$\frac{7}{8}$	$\frac{5}{8}$	$1\frac{3}{4}$	$2\frac{5}{16}$	3 - 12	.80
1	$1\frac{1}{8}$	$\frac{5}{8}$	$1\frac{7}{8}$	$3\frac{3}{16}$	14	1.45
$1\frac{1}{8}$	$1\frac{1}{4}$	$\frac{5}{8}$	3	4	16	2.31
$1\frac{1}{4}$	$1\frac{3}{8}$	$\frac{5}{8}$	3	4	18	2.26
$1\frac{3}{8}$	$1\frac{1}{2}$	$\frac{3}{4}$	3	4	20	2.87
$1\frac{1}{2}$	$1\frac{5}{8}$	$\frac{3}{4}$	3	4	24	2.71
$1\frac{3}{4}$	$1\frac{7}{8}$	1	3	4	30 - 36	4.17

Note: Tie rod size $\frac{3}{4}$ " made of cast iron material.

