



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-1182 - Momentum; 8 Foot LED Connectable Linear Strip; Up and Down Selectable; White Finish

- Wattage Selectable
- Flicker Free
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	60W/80W/100W
Volts:	120V-347V
Lumens:	6600L/8800L/11000L
Lamp Base :	Integrated - Integrated
Efficacy:	110.00 LPW
Lamp Shape :	Integrated LED
CRI:	80+
CCT (Kelvins):	30K/40K/50K - Soft White to Natural Light
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V
Dimmable Down To %:	100 to 10 percent
Incandescent Equivalent :	275W-400W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Surge Protection :	Built-in surge protection - 2KV
THD:	10.30%
Power Factor :	0.93
Voltage Type:	Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923654251
Each Quantity:	1
Each Dimensions:	94.29 x 4.72 x 3.66

INFO

Specification Note:	Max Wattage when connected at 120V: 700W; Max Wattage when connected at 277V: 1400W; Max Wattage when connected at 347V: 1700W
---------------------	--

PHYSICAL

Fixture Type:	Linear
Finish:	White
Lens Finish:	White
Lens Material:	Polycarbonate (PC)
Dimensions:	L:92.76" W:2.36" H:3.40"
Height Max:	72
Weight (Lbs.):	12.35
Material:	Aluminum

INSTALLATION

Sloped Ceiling Compatible:	When suspended
----------------------------	----------------

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-HT85NN
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

	65-1183	Momentum; L-Connector for LED Linear System; White Finish
	65-1184	Momentum; X-Connector for LED Linear System; White Finish
	65-1185	Momentum; T-Connector for LED Linear System; White Finish
	65-1186	Momentum; Y-Connector for LED Linear System; White Finish
	65-1190	Momentum; Power Cord for LED Linear System; 6 Foot; White Finish
	65-1191	Momentum; PC Cover Roll for LED Connectable Linear System; White Finish; 65 foot length
	65-1192	Momentum; Single Unit Suspension Kit With Canopy & Ancor Cover for LED Linear System; White Finish
	65-1194	Momentum; Suspension Kit Run Starter With Canopy for LED Linear System; White Finish
	65-1196	Momentum; Run Joiner Suspension Kit With Joing Bracket & Ancor Cover for LED Linear System
	65-1197	Momentum; Wall Mount Accessory for LED Connectable Linear System
	65-1198	Momentum; Ceiling Mount Accessory for LED Connectable Linear System
	65-1232	Momentum; 8 Foot Flange Kit; White Finish
	86-230	Momentum; PIR Sensor for LED Connectable Linear Strip Fixtures; Side Mount; White Finish
	86-232	Momentum; PIR Sensor for LED Connectable Linear Strip Fixtures; Side Mount; Black Finish



65-1182 - Momentum; 8 Foot LED Connectable Linear Strip; Up and Down Selectable; White Finish

DIMMER COMPATIBILITY

Legrand	ADPD4FBL3P2W4
Legrand	CD4FBLW
Eaton	DF10P
Leviton	DS710-10Z
Lutron	DVSCSTV
Lutron	DVSTV
Lutron	DVTV + PP347H 347V ONLY
Leviton	IP710-LFZ
Lutron	MS-Z101
Lutron	MS-Z101-V
Lutron	NFTV
Lutron	NTSTV-DV
Legrand	RH4FBL3PTCCCV6
Lutron	RMJS-8T-DV-B + PJ2-3BRL-GWH-L01