Simmons

Bronze Check Valves



500 SB SERIES CERTIFIED LEAD FREE Check Valve

- Silicon bronze cast body.
- Silicon bronze stemmed poppet.
- Female threads.
 MADE IN U.S.A.



1/2" - 2" are VFD Compatible

2-1/2" - 6" See page 9 for VFD Compatible



2500 SB SERIES CERTIFIED LEAD FREE Stemless Check Valve

- Silicon bronze cast body.
- Silicon bronze stemless poppet.
- Female threads. MADE IN U.S.A.



Not VFD Compatible




CERTIFIED LEAD FREE Submersible Check Valve

- Silicon bronze cast body.
- · Silicon bronze cast stemmed poppet.
- Female-Male threads. MADE IN U.S.A.

1" - 2" are VFD Compatible

3" - 6" See page 9 for VFD Compatible



513SB* has longer threads.

514SB** has longer threads.

510SB*** has 5" male threads both ends.

Part No.	Size	Weight Each Ibs.
2503SB	1	1.3
2504SB	1 1/4	1.8
2505SB	1 1/2	2.1
2506SB	2	3.7

Part No.	Size	Weight Each Ibs.
610SB**	1 x 1 Long	1.4
611SB** 1	1/4 x 1 1/4 Long	2.0
616SB	1 x 1	1.4
617SB	1 x 1 1/4	1.4
618SB	1 1/4 x 1 1/4	1.8
622SB	2 x 2	3.9
623SB	3 x 3	10.4
624SB	4 x 4	22.6
625SB	6 x 6	41.4

** Extended male and female threads



CERTIFIED LEAD FREE Dual Purpose Check Valve

- Silicon bronze cast body.
- Silicon bronze cast stemmed poppet.
- Female-Male threads both ends. *MADE IN U.S.A.*

VFD Compatible



NSF/ANSI 372

Weight
Part No.Size
FxMSize
FxMEach
Ibs.641SB1 x 1 1/41 x 1 1/41.2

Check Valves furnished with Buna-N O-Ring, stainless steel spring, stainless steel washer, and stainless steel locknut. All valves 1/2" through 1-1/2" have a working pressure of 400 psi. All valves 2" and larger have a working pressure of 600 psi. 190⁰ F. Maximum Temperature Rating

