


Victaulic® Vic-Flange Adapters

Styles 741 and 743




Style 741
2 – 12"/DN50 – DN300



Exaggerated for clarity




Style 741
14 – 24"/DN350 – DN600



Exaggerated for clarity



Style 743
2 – 12"/DN50 – DN300



Exaggerated for clarity

1.0 PRODUCT DESCRIPTION

Available Sizes

- **Style 741:** 2 – 24"/DN50 – DN600
- **Style 743:** 2 – 12"/DN50 – DN300

Maximum Working Pressure

- **Style 741:** Up to 300 psi/2068 kPa/20 Bar
- **Style 743:** Up to 720 psi/4964 kPa/49 Bar

Application

- Designed to transition from flanged to grooved piping systems

Pipe Material

- Carbon steel
- For use with stainless steel pipe, refer to Victaulic [publication 17.09](#) for pressure ratings and end loads.
- For use with PVC pipe, refer to Victaulic [publication 32.01](#) for pressure ratings.
- For use with aluminum pipe, refer to Victaulic [publication 21.04](#) for pressure ratings and end loads.
- For exceptions reference section 6.0 Notifications

ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.

System No.		Location	
Submitted By		Date	

Spec Section		Paragraph	
Approved		Date	

2.0 CERTIFICATION/LISTINGS



NOTE

- See Victaulic [publication 02.06](#): Victaulic Potable Water Approvals ANSI/NSF for potable water approvals if applicable.

3.0 SPECIFICATIONS - MATERIAL

Housing: Ductile iron conforming to ASTM A536, Grade 65-45-12. Ductile iron conforming to ASTM A395, Grade 65-45-15, is available upon special request.

Housing Coating: (specify choice)

Standard: Black enamel.

Optional: Hot dipped galvanized.

Optional: Contact Victaulic with your requirements for other coatings.

Gasket: (specify choice¹)

Victaulic Grade “E” EPDM

EPDM (Green stripe color code). Temperature range –30°F to +230°F/–34°C to +110°C. May be specified for hot water service within the specified temperature range plus a variety of dilute acids, oil-free air and many chemical services. UL Classified in accordance with ANSI/NSF 61 for cold +73°F/+23°C and hot +180°F/+82°C potable water service and ANSI/NSF 372. **NOT COMPATIBLE FOR USE WITH PETROLEUM SERVICES OR STEAM SERVICES.**

Victaulic Grade “T” Nitrile

Nitrile (Orange stripe color code). Temperature range 20°F to +180°F/29°C to +82°C. May be specified for oil related services, including air with oil vapor, this gasket may be specified for temperatures rated up to +180°F/+82°C. For water related services, this gasket may be specified for temperatures rated up to +150°F/+66°C. For oil free, dry air services, this gasket may be specified for temperatures rated up to +140°F/+60°C. **NOT COMPATIBLE FOR USE WITH HOT WATER SERVICES OR STEAM SERVICES.**

Others

For alternate gasket selection, reference [publication 05.01](#): Victaulic Seal Selection Guide.

¹ Services listed are General Service Guidelines only. It should be noted that there are services for which these gaskets are not compatible. Reference should always be made to the latest [Victaulic Seal Selection Guide](#) for specific gasket service guidelines and for a listing of services which are not compatible.


Draw Bolts/Nuts (14 – 24”/DN350 – DN600 only):

Carbon steel oval neck track bolts meeting the mechanical property requirements of ASTM A449 (imperial) and ISO 898-1 Class 9.8 (metric). Carbon steel hex flange nuts meeting the mechanical property requirements of ASTM A563 Grade B (imperial - heavy hex nuts) and ASTM A563M Class 9 (metric - hex nuts). Track bolts and hex flange nuts are zinc electroplated per ASTM B633 ZN/FE5, finish Type III (imperial) or Type II (metric).

4.4 DIMENSIONS

Style 743

Grooved pipe adapter to ANSI Class 300 flanges



Shaded area of mating face must be free from gouges, undulations or deformities of any type for effective sealing.

Exaggerated for clarity

Size		Assembly Bolt/Nut ²		Sealing Surface		Dimensions				Weight
Nominal inches DN	Actual Outside Diameter inches mm	Qty.	Size inches	"A" Max. inches mm	"B" Min. inches mm	W inches mm	X inches mm	Y inches mm	Z inches mm	Approximate (Each) lb kg
2 DN50	2.375 60.3	8	5/8 x 3	2.38 60	3.41 87	7.75 197	6.50 165	5.00 127	1.00 25	4.8 2.2
2½	2.875 73.0	8	¾ x 3¼	2.88 73	3.91 99	8.63 219	7.50 191	5.88 149	1.13 29	7.4 3.4
3 DN80	3.500 88.9	8	¾ x 3½	3.50 89	4.53 115	9.50 241	8.25 210	6.63 168	1.25 32	9.1 4.1
4 DN100	4.500 114.3	8	¾ x 3¾	4.50 114	5.53 141	11.38 289	10.00 254	7.88 200	1.38 35	15.3 6.9
5	5.563 141.3	8	¾ x 4	5.56 141	6.72 171	12.38 314	11.00 279	9.25 235	1.50 38	17.7 8.0
6 DN150	6.625 168.3	12	¾ x 4½	6.63 168	7.78 198	13.88 352	12.50 318	10.63 270	1.50 38	23.4 10.6
8 DN200	8.625 219.1	12	7/8 x 4¾	8.63 219	9.94 252	16.75 425	15.00 381	13.00 330	1.75 44	34.3 15.6
10 DN250	10.750 273.0	16	1 x 5¼	10.75 273	12.31 313	19.25 489	17.50 445	15.25 387	2.00 51	48.3 21.9
12 DN300	12.750 323.9	16	1 1/8 x 5¾	12.75 324	14.31 363	22.25 565	20.50 521	17.75 451	2.13 54	70.5 32.0

² Total assembly bolts required to be supplied by installer.