# **REZNOR®**

#### **IMPORTANT**


- Always include complete heater model and serial number so that any specification change can be considered for parts shipment. It can save time and expense.
- 2. Specifications are subject to change without notice.
- 3. We reserve the right to substitute functional replacements.
- 4. Order either by Kit or Component Part No.

# Functional Replacement Pilots

	Quick Reference Replacement Pilot Kit Selection Table							
	(Refer to FIGURES 1-12, pages 1-4, for illustrations and component part numbers.)							
Type of	Model Designation*/Sizes		Match Lit Pilot Kits			Spark Pilot Kits**		
Heater			Propane	FIGURE	Natural	Propane	FIGURE	
Infrared	T, TR-H 50	-	-	-	110854	110854	2	
	T, TR-H 75-200	-	-	-	110853	110853	2	
Unit	F, B 25-400	110851	110852	1	110853	110854	2	
Heaters	FE, BE 25-400	•	-	•	110853	110854	2	
	UA, XL, XLB, CXL, CXLB 30-105	110855	110856	3	110857	110858	4	
	XL, XLB, CXL, CXLB 125-400	110859	110860	5	110861	110862	6	
	EEXL, EEXLB, CEEXL, CEEXLB 30-105	-	-	-		110858	4	
	EEXL, EEXLB, CEEXL, CEEXLB 125-400	-	-	-	110861	110862	6	
	SCA, SCB prior to Series 6	-	-	-	110861	110862	6	
	SCA, SCB Series 6				131457	131458	8	
Duct	EEDU, HEEDU Series 6	-	-	-	110853	110854	2	
Furnaces	EEDU, HEEDU prior to Series 6				110861	110862	6	
and	X, XA, XB, XC, XD, XE, XG XJ, PAK, DFAH prior to 9/73	110863	110864	8	-	-	-	
Packaged	X, XA, XB, XC, XD, XE, XG XJ, PAK, DFAH, CX, CXE, CPAK	110859	110860	5	110861	110862	6	
Systems	beginning 9/73	110057	110000	·	110001	110002	v	
(Also	SC, SCE Series 6	-	-	-	131457	131458	8	
applies to	RX, REB, RXE, RXJ, CRX, CREB, CRXE, RPAK, CRPAK, SC, SCE,							
Models	SCJ prior to Series 6; RPV, RPVE, RPBE, RPVAK, CRPV, CRPVE,				110071	110862	6	
with	CRPBE, CRPVAK Series 6; RG, CRG, RP, CRP, RGB, CRGB, RPB,	-	-	-	110861			
prefix	CRPB, RGBL, CRGBL, RPBL, CRPBL, SSCBL							
"H")	RPV, RPBE, RPVE, RPVAK RPVJ. CRPV, CRPBE, CRPVE,				110075	110066		
	CRPVAK prior to Series 6	-	-	-	110865	110866	9	
Heating/	RCG 7-1/2, 10 ton	-	-	-	110865	110866	9	
Cooling	RCG2-5 ton - with vertical pilot	-	-	-	110867	110868	10	
	- with horizontal pilot	-	-	-	110861	110862	6	
Direct	ADF, ADFH with hot surface ignition	-	-	-	120048	120048	11	
Fired	RDFwith spark ignition and flame probe	-	-	-	110869	110869	11	
	-with spark ignition and ultraviolet sensor	-	-	-	110918	110918	11	
	-with hot surface ignition	-	-	-	120048	120048	11	
	DV with hot surface ignition	-	-	-	120048	120048	11	
	DFA with hot surface ignition	-	-	-	120048	120048	11	

<sup>\*</sup> If the replacement pilot changes with the introduction of a Model Series, the Series is indicated in the Selection Table. The Series indicator is on the heater rating plate; it is the suffix number on the Model Size (Ex: SC400-6; "6" is the Series).


## **Pilot Kits and Components**



Replacement		Natural Gas - P/N 110851
Pilot Kits		Propane Gas - P/N 110852
Code P/N		Component Description
1 96360		Natural Gas Pilot Assembly with orifice, pilot tubing, and
		thermocouple; less fitting (Johnson #J994HKA-9731-715)
96361		Propane Gas Pilot Assembly with orifice, pilot tubing, and
		thermocouple; less fitting (Johnson #J994HKA-9733-410)
2	103034	Natural Gas Orifice only, Johnson #9731-715 (brass)
	98695	Propane Gas Orifice only, Johnson #9733-410 (black)
3 <b>98698</b>		Pilot Tubing, 1/8" x O.D. x 18" long, Johnson #B10499-995-11
97572		Compression Fitting, FTG75 (2 required when replacing pilot tubing)
4 84761		Thermocouple, 24", #K15FA-24D


<sup>\*\*</sup> Spark pilot kits for all indirect-fired products are for use with Model G60, G65, G67, or G770 ignition controllers only. Pilot kits are not available for other spark ignition systems used on indirect-fired products.

FIGURE 2 - Vertical Spark
Pilot for Unit Heater Models
F/FE/B/BE, Infrared Models
TR/TR-H, and Duct Furnace
Models EEDU/HEEDU Series 6



	Replac	ement	Models F/FE/B/BE	Natural Gas - P/N 110853; Propane Gas - P/N 110854			
	Pilot K	its	Model TR 50	Natural Gas - P/N 110854; Propane Gas - P/N 110854			
	Models TR 75-200		Natural Gas - P/N 110853; Propane Gas - P/N 110853				
			Models (H)EEDU	Natural Gas - <b>P/N 110853</b> ; Propane Gas - <b>P/N 110854</b>			
			Series 6	Natural Gas - P/N 11	0855; Propane Gas - P/N 110854		
ô	Code	P/N	Application	Gas	Component Description		
	1	97534	F/FE/B/BE and	Natural	Pilot Assembly with orifice, pilot tubing,		
			(H)EEDU Series 6	Naturai	and flame rod; less flame sensor lead and		
			TR 75-200	Natural & Propane	fitting (Johnson #J982HKW-9731-713		
		97535	F/FE/B/BE and	Dronono	Pilot Assembly with orifice, pilot tubing,		
			(H)EEDU Series 6		and flame rod; less flame sensor lead and		
		TR 50 Natural & Propane		fitting (Johnson #J982HKW-9733-410)			
	2	103034	F/FE/B/BE and	Natural	Orifice only, Johnson # 9731-713 (brass)		
			(H)EEDU Series 6	Naturai			
			TR 75-200	Natural & Propane			
		98695	F/FE/B/BE and	Propane	Orifice only, Johnson # 9733-410 (black)		
			(H)EEDU Series 6	Tiopane			
			TR 50	Natural & Propane			
	3	98698			Pilot Tubing, 1/8" OD x 18" lg, Johnson		
					#B10499-99-11		
		97572	F/FE/B/BE/TR and	Natural & Propane	Compression Fitting, FTG75 (2 required		
			(H)EEDU Series 6	radulal & Hopane	when replacing pilot tubing)		
	4 98697			Flame Rod, Johnson #Y75AA-10			
	5 97575				Flame Sensor Lead, 21"		

FIGURE 3 - Horizontal Match Lit Pilot for Models UA, XL, XLB, CXL, CXLB 30 - 105



Replacement		Natural Gas - P/N 110855				
Pilot Kits		Propane Gas - P/N 110856				
Code	P/N	Component Description				
1	40964	Natural Gas Pilot Assembly with				
		orifice; less pilot tubing, less				
		thermocouple (Baso #J999HKA4213)				
40420		Propane Gas Pilot Assembly with				
		orifice; less pilot tubing, less				
		thermocouple (Baso #J999HKA4207)				
2	40966	Natural Gas Orifice only, #4213				
40965		Propane Gas Orifice only, #4207				
3 5145		Pilot Tubing, 22" long				
9664		Nut with breakaway ferrule (2 required				
		when replacing pilot tubing)				
4 84761		Thermocouple, TC2-24"				

FIGURE 4 - Horizontal Spark Pilot for Models EEXL, EEXLB, CEEXL, CEEXLB 30 - 105. May also be used on XL, XLB, CXL CXLB when equipped with G60, G65 or G67 ignition controller (with or without Serial No. Suffix "B")



Replac	ement	Natural Gas - P/N 110857
Pilot Kits		Propane Gas - P/N 110858
Code	P/N	Component Description
1	93971	Natural Gas Pilot Assy with orifice and high tension lead; less pilot
		tubing, less flame probe, less sensor lead (Baso #J983HKW7715)
	93972	Propane Gas Pilot Assy with orifice and high tension lead; less pilot
		tubing, less flame probe, less sensor lead (Baso #J983HKW4709)
2	93973	Natural Gas Orifice only, #7715
	93974	Propane Gas Orifice only, #4709
3	5145	Pilot Tubing, 22" long
	9664	Nut with breakaway ferrule (2 required when replacing pilot tubing)
4	50450	Sensor lead, 16" lg
5	43594	Flame probe, Y75BA

Above pilot replaces Baso #J987HKW, natural gas P/N 50449 and propane gas P/N 51330. Also replaces General Controls #26C27113 with 16" high tension lead, natural gas pilot P/N 64463 and propane gas P/N 64464; and General Controls #26C27113 with 24" high tension lead, natural gas pilot P/N 73614 and propane pilot P/N 73615.

FIGURE 5 - Horizontal Match Lit Pilot - Starting 9/73 for Models X, XA, XB, XC, XD, XE, XG, XJ, PAK, DFAH, HX, HXE, CX, CXE, HCX, HCXE, CPAK; Also XL, XLB, CXL, CXLB 125-400




_	Renlacement		Natural Gas - P/N 110859			
	Pilot Kits		Propane Gas - P/N 110860			
	Code	Code P/N Component Description				
	1	17890	Natural Gas Pilot with orifice; less pilot tubing, less thermocouple (Basc	#J963HXA6218)		
		46136	Propane Gas Pilot with orifice; less pilot tubing, less thermocouple (Bas	o #J963HXA4211)		
	2	46392	Natural Gas Orifice only, #6218			
		42089	Propane Gas Orifice only, #4211	This pilot		
	3	7671	Pilot Tubing, 26" lg for X Series	may be used		
		9664	Nut with breakaway ferrule (2 required when replacing pilot tubing)	in place of		
	3A	5145	Pilot Tubing, 22" lg for XL, XLB, CXL, CXLB 125-400	GC		
		9664	Nut with breakaway ferrule (2 required when replacing pilot tubing)	#26C23114.		
	4	84761	Thermocouple TC2, 24" lg for X Series			
	4A	84760	Thermocouple TC2, 18" lg for XL, XLB, CXL, CXLB 125-400			

### FIGURE 6 - Horizontal Spark Pilots for Models

XL, XLB, CXL, CXLB 125-400

EEXL, EEXLB, CEEXL, CEEXLB 125-400; EEDU, HEEDU prior to Series 6 Starting 9/73 for X, XA, XB, XC, XD, XE, XG, XJ, PAK, DFAH, CX, CXE, CPAK RX, REB, RXE, RXJ, CRX, CREB, CRXE, RPAK, CRPAK, SC, SCA, SCB, SCE, SCJ Prior to Series 6; RPV, RPVE, RPBE, RPVAK, CRPV, CRPVE, CRPBE, CRPVAK Series 6; RG, CRG, RP, CRP, RGB, CRGB, RPB, CRPB, RGBL, CRGBL, RPBL, CRPBL, SSCBL



RCG 2 through 5 ton with horizontal pilot


#### NOTES:

- Horizontal spark pilots for ignition systems other than G60, G65, G67 and G770 are no longer available.
- Kits also apply to models listed with the prefix "H" \*Included in all kits. Used only with the above models equipped with any Model G60 ignition controller, a Model G67BG-2, or a Model G67NG-2. Not used with ignition controller Models G67BG-5 and G770NGC-4. See Instructions on page 4.
- This pilot replaces Baso #J991HXW, natural gas P/N 45150, propane P/N 45141; #J994HXW, natural gas P/N 47303, propane P/N 47384. May be used as a substitution for J993HXW and J999HXW.

\*See instructions on page 4.

Replac	ement	Natural Gas - P/N 110861		
Pilot Kits		Propane Gas - P/N 110862		
Code	P/N	Component Description		
1	61145	Natural Gas Pilot Assy with orifice, high tension lead, flame probe;		
		less pilot tubing, less flame sensor lead (Baso #J992HXW7221)		
	61146	Propane Gas Pilot Assy with orifice, high tension lead, flame probe;		
		less pilot tubing, less flame sensor lead (Baso #J992HXW9817)		
2	63088	Natural Gas Orifice only, #7221		
	37801	Propane Gas Orifice only, #4209		
3	5145	Pilot Tubing, 22" lg		
	9664	Nut with breakaway ferrule (2 required when replacing pilot tubing)		
4	50450	Sensor lead, 16" lg		
5*	112647	Crimp-on, 90° Rajah terminal connector		
6*	112648	90° Boot Terminal Protector		

# FIGURE 7 - Vertical Spark Pilot for Models SC, SCA, SCB,




Replacement		cement	Natural Gas - <b>P/N 131457</b>
Pilot Kits		Kits	Propane Gas - <b>P/N 131458</b>
	Code	P/N	Component Description
	1	125251	Natural Gas Pilot Assy with orifice, pilot tubing,
			and flame probe; less flame sensor lead and
			fitting (Johnson #J981HKW-9731-713
		125671	Propane Gas Pilot Assy with orifice, pilot tubing,
			and flame probe; less flame sensor lead and
			fitting (Johnson #J981HKW-9715-413)
	2 103034		Natural Gas Orifice only, Johnson # 9731-713
			(brass)
		126024	Propane Gas Orifice only, Johnson # 9715-413
			(black)
	3	98698	Pilot Tubing, 1/8" OD x 18" lg, Johnson #B10499-
			99-11
		97572	Compression Fitting, FTG75 (2 required when
			replacing pilot tubing)
	4 126104		Flame Probe, Johnson #Y75AA-2
5 126101		126101	Auxiliary flame probe w/bracket, J/C Y5-GB-1
	6	125401	(2) Sensor lead assy, 18 ga x 14", 150°C

FIGURE 8 -	D 1 (N) 1 C DN 1100				
Vertical Match	Replacement		Natural Gas - P/N 110863		
Lit Pilot for	Pilot Kits		Propane Gas - P/N 110864		
	Code	P/N	Component Description		
Models X, XA,	1	9661	Natural Gas Pilot Assy		
XB, XC, XD,			with orifice; less pilot		
XE, XG, XJ,			tubing, less thermocouple		
PAK, DFAH			(Baso J915HHA6221)		
prior to 9/73		30126	Propane Gas Pilot Assy		
			with orifice; less pilot		
1			tubing, less thermocouple		
1			(Baso J915HHA4211)		
40000	2	44048	Natural Gas Orifice only,		
75			#6221		
111 7		42089	Propane Gas Orifice only,		
2			#4211		
171	3	7671	Pilot Tubing, 26" lg		
1		9664	Nut with breakaway ferrule		
1			(2 required when replacing		
3			pilot tubing)		
	4	84761	Thermocouple, TC2, 24" lg		

FIGURE 9 - Vertical Spark Pilot for Models RPV, RPBE, RPVE, RPVJ, RPVAK, HRPV, HRPBE, HRPVE, CRPV, HCRPV, CRPBE, HCRPBE, CRPVE, HCRPVE; CRPVAK prior to Series 6 and RCG 7-12/, 10 ton equipped with

**G60 or G67 ignition Controller** 



\*See Instructions, page 4.

NOTE: Vertical spark pilots for ignition systems other than G60 and G67 are no longer available.


Replacement Pilot Kits		Natural Gas - P/N 110865 Propane Gas - P/N 110866
Code	P/N	Component Description
1	41775	Natural Gas Pilot Assy with orifice, high tension lead; less pilot
		tubing, less flame probe, less sensor lead (Baso #J999HHW6221)
	44673	Propane Gas Pilot Assy with orifice, high tension lead; less pilot
		tubing, less flame probe, less sensor lead (Baso #J999HHW4209)
2	44048	Natural Gas Orifice only, #6221
	37801	Propane Gas Orifice only, #4209
3	92848	Sensor lead assembly, 16" lg and 21" lg wires (not illustrated)
4	43594	(2) Flame probe Y75BA-3
5	44678	Bracket Y59DD-1
6*	112647	Crimp-on, 90° Rajah terminal connector
7*	112648	90° Boot Terminal Protector
8	7671	Pilot tubing 26" lg (not illustrated)
	9664	Nut with breakaway ferrule (2 required when replacing pilot tubing)

# FIGURE 10 - Vertical Spark Pilot for Models RCG 2 - 5 ton with Vertical Pilot

\*See instructions below.

Replace Pilot I		Natural Gas - P/N 110867 Propane Gas - P/N 110868
Code	P/N	Component Description
1	47484	Natural Gas Pilot with orifice, high tension lead and built-in flame probe; less
		pilot tubing, less sensor lead (Baso #J993HHW6221)
	47485	Propane Gas Pilot with orifice, high tension lead and built-in flame probe; less
		pilot tubing, less sensor lead (Baso #J993HHW4211)
2	44048	Natural Gas Orifice only, #6221
	42089	Propane Gas Orifice only, #4211
3	44183	Sensor lead, 38" lg
4	7671	Pilot tubing 26" lg
	9664	Nut with breakaway ferrule (2 required when replacing pilot tubing)
5*	112647	Crimp-on, 90° Rajah terminal connector
6* 112648 90° Boot Terminal Protector		90° Boot Terminal Protector

# FIGURE 11 - Pilot Systems used on Direct-Fired Models RDF/ ADF/ADFH/DFA/DV



\*P/N 135435 is a replace-

ment flame sensor only kit

for ADF/ADFH units manu-

factured prior to 11/94.

Replacement		<b>w/Flame Probe - P/N 110869</b> (Includes Codes 1, 2, 3)	RDF with spark pilot
Pilot 1	Kits	w/Ultraviolet Sensor - P/N 110918 (Includes Codes 1, 2, 4)	RDF with spark pilot
		w/Hot Surface Ignition - P/N 120048 (Includes	ADF/DFA/RDF/DV with
		Codes 5, 6, 7, and 8)	hot surface ignition
Code	P/N	Component Description	Applies to
1		Pilot Supply Connection including: (1) brass elbow,	
		<b>P/N 93388</b> ; (3) connectors, <b>P/N 95188</b> ; (1) long nut,	
		P/N 95189	RDF Models
2	87936	Spark Plug, 27750-1-31, Maxon #18075	with a spark pilot
3	87937	Flame Probe, Auburn AA67-7892-1 - Standard on	and either a probe or
		units with date code prior to ANI (9/88)	ultraviolet
4	89411	Ultraviolet Minipeeper, #C7027A - Standard on units	flame sensor
		with date code from ANI (9/88) through AVB (2/96) -	
		optional on prior units	
5	122840	Pilot Plate and Tubing Assembly	ADF/ADFH*; DFA;
6	134706*	Flame Sensor, J/C #Y75M K-1D	DV; and RDF with
7	121865	Ignitor, Norton #401E	hot surface
8	121730	Pilot Bushing	ignition

Hot Surface Ignition Kits below include all components needed to change RDF units from a spark pilot system with either a flame probe or ultraviolet sensor to hot surface ignition NOTE: Model, Serial No., and

- for an RDF unit with a 200VA Transformer - P/N 146268

- for a 115V RDF unit with an 80VA transformer - P/N 146318

Wiring Diagram No. MUST be - for a 208V RDF unit with an 80VA transformer - P/N 146319 provided when ordering

- for a 240V, 480V, or 575V RDF unit with an 80VA transformer - P/N 146320 these kits.

# Instructions for connecting ignitor lead on replacement spark pilots to Model G60 and G67 ignition controllers (applies to Pilot Kits in FIGURES 6, 9, and 10):




Crimp-on, 90° Rajah Terminal Connector, P/N 112647

Protective Boot. P/N 112648

Effective with replacement pilots purchased 9/91, these parts are required (in the kit or separately) when the replacement pilot is for heater Models listed in FIGURES 6, 9 and 10 equipped with a Model G60 or G67BG-NG-2 ignition controller. (Note: These parts are not required when the ignition controller is a Model G67BG-5 or G770NGC-4.)

- 1. Identify the ignitor wire attached to the pilot electrode. Slip the 90° protective boot on to the wire, as illustrated è.
- 2. On the "open" leg of the 90° crimp-on terminal (P/N 112647), locate a flat, triangular spike tab punched in the metal. With the tip of a small, straight screwdriver, force the spike tab toward the inside of the connector. Straighten the tab to a vertical position.
- 3. Insert the ignitor wire into that same connector leg (just to the 90° bend) and push the wire onto the protruding spike tab, making sure that the tab penetrates the insulation. (Do not strip the ignitor wire.) Using a crimping tool or pliers, squeeze the sides of the terminal to form a "C" shape. The ignitor wire should now be firmly held by the terminal.
- 4. Slide the protective boot over the terminal. Holding the boot, attach the 90° Rajah terminal to the ignitor lead Rajah connector on the Model G60 or G67BG/ NG-2 ignition controller.



## www.RezSpec.com; 800-695-1901

©2010 Thomas & Betts. All rights reserved.

Trademark Note: Reznor® is registered in at least the United States. 11/10 P-PILOTS (Version .2)