EV1414C5D-35 | DC 14" ROUND SELECTABLE LED FLUSHMOUNT BRUSHED NICKEL

Project: Date:
Prepared By:
Comments:



FEATURES

- 5 Year Warranty
- Energy Savings of up to 85%
- Dimmable with Triac Dimmers
- Lumen Maintenance over 70% at 50,000+ Hours
- Life Expectancy 45-years based on 3-hours per day usage
- Suitable for Damp Locations
- Long Lasting Integrated LEDs

Optics

- White Diffuser
- Ceiling Installations for General Ambient Lighting in Homes
- Corridors, Lobbies, and Stairways

Certifications

- cETLus Listed
- CA Title 24 Compliant

SPECIFICATIONS

- Lumens: 1500 lm
- Wattage: 25 W
- Efficacy: 60 lm/W
- Voltage: 120V
- Power Factor: 0.9
- Color Rendering Index (CRI): 90
- Kelvin Temp. (CCT): 2700K, 3000K, 3500K, 4000K & 5000K Multi-White
- Ambient Temperature Range: -20°C to 40°C (-4°F to 104°F)
- Expected Life: 50,000 hrs

DIMENSIONS

- Width: 14"
- Depth: 14"
- Height: 4"

DIMMABLE LIGHT

Intertek

Envirolite
(855) 573-6156 | info@envirolite-led.com

Specifications subject to change without notice

© Copyright 2025