

D U C T M A T E

LAG-IT



Lagging Adhesive



Premium Quality

- Crack and peel resistant
- Water resistant
- Low odor
- UV resistant
- Excellent workability
- High strength and durability
- No VOC's!
- Sag resistant
- Non-Flammable in wet state
- Fire retardant in dry state
- Manufactured by S.M.W.I.A. local 12
- Exceptional coverage
- Good dry time
- Qualifies for LEED EQ, Credit 4.1



DUCTMATE®
Industries, Inc.

DESCRIPTION

LAG-IT is a premium quality interior/exterior, water based lagging adhesive/sealant.

BASIC USE

LAG-IT is used for bonding and sealing jackets of canvas, cloth or other fabrics/insulators to air-conditioning ducts, cold water pipes, etc...

SPECIAL CHARACTERISTICS

- ASTM E-84 Certified
- Crack and peel resistant
- Water resistant
- Low odor
- UV resistant
- Excellent workability
- High strength and durability
- Will not discolor with time
- Sag resistant
- Non-Flammable in wet state
- Fire retardant in dry state
- Exceptional coverage
- Good dry time
- No VOC's!

PACKAGING INFORMATION

PART NO.	DESCRIPTION	QUANTITY & WEIGHTS
LAGIT1	1 Gal	4-1 gal pails @ 50 lbs
LAGIT5	5 Gal	1-5 gal pail @ 64 lbs
LAGIT54	54 Gal	1-54 gal drum @ 700 lbs

TECHNICAL INFORMATION

BASE:	Acrylic Latex
COLOR:	White
WEIGHT/GAL:	11 ± 2%
SOLIDS:	62 ± 2%
VISCOSITY:	app. 75,000 cps
SERVICE TEMPERATURE:	-25° F to +175° F
APPLICATION TEMPERATURE:	40° F to +110° F
STORAGE TEMPERATURE:	40° F to +100° F
FLAMMABILITY:	None
FLASH POINT:	No Flash
DRY TIME:	TOUCH: 1 hour THROUGH: 6 hours <i>Depending on temperature, humidity, and thickness.</i>
FREEZE THAW:	5 Cycles
COVERAGE:	50 sq. ft. - 200 sq. ft. <i>Depending on application rate.</i>
BONDING TIME:	40 Minutes
SHELF LIFE:	2 Years

APPLICATION

Can be applied to dirt free, metal, cloth or duct board surfaces using a trowel, brush, hand (rubber gloves recommended), or airless spray. Apply per industry standards. Tools can be cleaned with water.

ASTM E-84
Flame Spread 0 Smoke Developed 0

Tested when applied at 200 sq. ft./gal. in two 3" strips, 8" on center.

LIMITED PRODUCT WARRANTY

Manufacturer is not liable for consequential, incidental or special damages. There are no statutory or implied warranties including the warranties of fitness for a particular purpose and merchantability. There are no warranties other than as set forth below and factory neither assumes nor authorizes any person to assume any liability or other obligation in connection with LAG-IT.

LAG-IT is warranted to be free from any and all defects in material and workmanship only at the time of shipment from our factory. If material is shown to be defective at the time of shipment from our factory, manufacturer will at its sole option, replace or issue credit for the original purchase price only.

Manufacturer does not guarantee the results from the use of LAG-IT because of the extreme differences in surface texture of coated material and the possibility of structural movement or externally caused damages.

Distributed By:



DUCTMATE
Industries, Inc.

CHARLEROI, PA
210 Fifth Street
Charleroi, PA 15022
800-245-3188
724-258-0500
FAX: 724-258-5494

LODI, CA
810 S. Cluff Avenue
Lodi, CA 95240-3141
800-344-3270
209-333-4680
FAX: 209-333-4678

www.ductmate.com

