Vu-Flow Screen Filters

NT Series

T Style Screen Filter Features:

- 180° in-line "T" style installation.
- 1-100 GPM models.
- 1/2" MPT cleanout with purge valve.
- Supplied with polyester filter screens.

- **WATER USE ONLY**

NO LEAD
< 0.25% Pb by weighted avg
Third Party Certified to NSF / ANSI 372





Part Number	Inlet/Outlet "P"	Mesh # Size	Mesh Opening	Min*/Max Flow GPM	"L"	"W"
IPS x IPS						
NT75-24P	3/4" x 3/4"	24 (711 mic)	0.028	1-25	11 3/8"	5"
NT75-60P	3/4" x 3/4"	60 (254 mic)	0.010	1-25	11 3/8"	5"
NT75-100P	3/4" x 3/4"	100 (152 mic)	0.006	1-25	11 3/8"	5"
NT75-140P	3/4" x 3/4"	140 (104 mic)	0.004	1-25	11 3/8"	5"
NT75-250P	3/4" x 3/4"	250 (61 mic)	0.0024	1-25	11 3/8"	5"
NT75-500P	3/4" x 3/4"	500 (30 mic)	0.0012	1-25	11 3/8"	5"
NT75-1000P	3/4" x 3/4"	1000 (15 mic)	0.0006	1-25	11 3/8"	5"
Slip x Slip						
NT100-24P	1" x 1"	24 (711 mic)	0.028	1-25	11 3/8"	5"
NT100-30P	1" x 1"	30 (533 mic)	0.021	1-25	11 3/8"	5"
NT100-40P	1" x 1"	40 (381 mic)	0.015	1-25	11 3/8"	5"
NT100-60P	1" x 1"	60 (254 mic)	0.01	1-25	11 3/8"	5"
NT100-100P	1" x 1"	100 (152 mic)	0.006	1-25	11 3/8"	5"
NT100-140P	1" x 1"	140 (104 mic)	0.004	1-25	11 3/8"	5"
NT100-250P	1".x 1"	250 (61 mic)	0.0024	1-25	11 3/8"	5"
NT100-500P	1" x 1"	500 (30 mic)	0.0012	1-25	11 3/8"	5"
NT100-1000P	1" x 1"	1000 (15 mic)	0.0006	1-25	11 3/8"	5"
Slip x Slip						
NT150-24P	1-1/2" x 1-1/2"	24 (711 mic)	0.028	10-50	15 3/8"	5 1/4"
NT150-30P	1-1/2" x 1-1/2"	30 (533 mic)	0.021	10-50	15 3/8"	5 1/4"
NT150-40P	1-1/2" x 1-1/2"	40 (384 mic)	0.015	10-50	15 3/8"	5 1/4"
NT150-60P	1-1/2" x 1-1/2"	60 (254 mic)	0.010	10-50	15 3/8"	5 1/4"
NT150-100P	1-1/2" x 1-1/2"	100 (152 mic)	0.006	10-50	15 3/8"	5 1/4"
NT150-140P	1-1/2" x 1-1/2"	140 (104 mic)	0.004	10-50	15 3/8"	5 1/4"
NT150-250P	1-1/2" x 1-1/2"	250 (61 mic)	0.0024	10-50	15 3/8"	5 1/4"
NT150-500P	1-1/2" x 1-1/2"	500 (30 mic)	0.0012	10-50	15 3/8"	5 1/4"
NT150-1000P	1-1/2" x 1-1/2"	1000 (15 mic)	0.0006	10-50	15 3/8"	5 1/4"
Slip x Slip						
NT200-24P	2" x 2"	24 (711 mic)	0.028	18-100	17 7/8"	5 1/2"
NT200-30P	2" x 2"	30 (533 mic)	0.021	18-100	17 7/8"	5 1/2"
NT200-40P	2" x 2"	40 (384 mic)	0.015	18-100	17 7/8"	5 1/2"
NT200-60P	2" x 2"	60 (254 mic)	0.010	18-100	17 7/8"	5 1/2"
NT200-100P	2" x 2"	100 (152 mic)	0.006	18-100	17 7/8"	5 1/2"
NT200-140P	2" x 2"	140 (104 mic)	0.004	18-100	17 7/8"	5 1/2"
NT200-250P	2" x 2"	250 (61 mic)	0.0024	18-100	17 7/8"	5 1/2"
NT200-500P	2" x 2"	500 (30 mic)	0.0012	18-100	17 7/8"	5 1/2"
NT200-1000P	2" x 2"	1000 (15 mic)	0.0006	18-100	17 7/8"	5 1/2"

* Minimum flow needed for "spin-out" action.

• Do not install filters with purge valve on suction side of pump.

Carton Quantity of 10 for all products