





Z806-HDG

SPECIFICATION SHEET

6 [159] WIDE REVEAL FIBER REINFORCED POLYMER TRENCH DRAIN TAG SYSTEM WITH HEAVY-DUTY GALVANIZED FRAME ASSEMBLY

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice

SPECIFYING ENGINEER IS RESPONSIBLE FOR CONCRETE ENCASEMENT AND REINFORCING BASED UPON APPLICATION AND LOCAL CODES



NOTE: + Actual Channel length is 122 1/2 [3112] to allow for overlap.

ENGINEERING SPECIFICATION: Zurn Z806-HDG Channels shall be 120 [3048] long, 6 [152] wide and have a 4 [102] throat. Modular channel sections shall be made of Fiber Reinforced Polymer (FRP). Shall have a positive mechanical connection between channel sections that will not separate during the installation and shall mechanically lock into the concrete surround every 10 [254]. Channels shall weigh less than 2.31 lbs.[1.05kg] per linear foot, have a smooth, 1.5 [38] radiused self cleaning bottom with a Manning's coefficient of 0.009 and 0.75% or neutral 0% built in slope. Channels shall have rebar clips standard to secure trench in its final location. Shall be provided with standard GDC grates that lock down to frame. Zurn 6 [152] wide reveal Galvanized Ductile Iron Slotted Grate conforming to ASTM specification A536-84, Grade 80-55-06. Ductile Iron grate is rated class C per the DIN EN1433 top load classifications. Supplied in 20 [508] nominal lengths with 0.50 [13] wide slots, and 0.75 [19] bearing depth. Grate has an open area of 18.57 sq. in per ft. [39,307 sq. mm per meter]. The 0.25 [6.35] thick Heavy-Duty Carbon Steel Galvanized Frame Assembly conforms to ASTM specification A36 and Galvanizing conforms to ASTM specification A123 with 12 - 4 [102] long concrete anchors per 120 [3048]. Grate lockdown bars are to be integral to the frame. All welds must be performed by a certified welder per ASTM standard AWS D1.1. Frames Shall be produced in the U.S.A.

PREFIX OPTIONS (Check/specify appropriate options)

- Z Ten-foot Fiber Reinforced Polymer (FRP)*
- ZV Ten-foot Fiber Reinforced Vinylester

SUFFIX OPTIONS (Check/specify appropriate options)

Outlet Adapters Add/Each

- E1 Closed End Cap
- E2 2 [51] No-Hub End Outlet
- E3 3 [76] No-Hub End Outlet
- E4 4 [102] No-Hub End Outlet
- E6 6 [152] No-Hub End Outlet
- U2 2 [51] No-Hub Bottom Outlet
- U3 3 [76] No-Hub Bottom Outlet
- U4 4 [102] No-Hub Bottom Outlet
- U6 6 [152] No-Hub Bottom Outlet

Grate Options (Load Classifications are per DIN EN1433)

- BDC Black Acid Resistant Epoxy Coated Ductile Grate - Class C
- BDE Black Acid Resistant Epoxy Coated Ductile Grate - Class E
- DC Ductile Iron Solid Cover - Class C
- DGC Ductile Iron Slotted Grate - Class C
- DGE Ductile Iron Slotted Grate - Class E
- GDC Galvanized Ductile Slotted Grate - Class C *
- GDE Galvanized Ductile Slotted Grate - Class E
- GHPD Galvanized Heel-Proof Ductile Grate - Class C
- HPD Heel-Proof Ductile Slotted Grate - Class C
- HPP Heel-Proof Polyethylene Grate - Class A
- LD Ductile Iron Longitudinal Slotted Grate - Class B
- RFG Reinforced Galvanized Steel Slotted Grate - Class B
- RPG Reinforced Galvanized Perforated Grate - Class B

Miscellaneous Options

- DB Bottom Dome Strainer
- JC Joint Connector
- RC Rebar Clip (Set of 2)
- SW 8.1 [206] High Sidewall Extension Adapter (Per Pair)
- VP Vandal-Proof Lockdown

Trench No.	Flow		Flow		
	'A' Shallow Inv.	'B' Deep Inv.	(cfs)	(gpm)	(lps)
1001	3.50 [89]	4.40 [112]	.196	88	6
1002	4.40 [112]	5.30 [135]	.296	133	8
1002N	5.30 [135]	5.30 [135]	-	-	-
1003	5.30 [135]	6.20 [157]	.397	178	11
1004	6.20 [157]	7.10 [180]	.501	225	14
1004N	7.10 [180]	7.10 [180]	-	-	-
1005	7.10 [165]	8.00 [203]	.604	271	17
1006	8.00 [203]	8.90 [203]	.711	319	20
1007	8.90 [226]	9.80 [249]	.816	366	23
1008	9.80 [249]	10.70 [272]	.922	414	26
1008N	10.70 [272]	10.70 [272]	-	-	-
1009	10.70 [272]	11.60 [295]	1.029	462	29
1010	11.60 [295]	12.50 [318]	1.136	510	32

Decorative Grate Options (Load Classifications are per DIN EN1433)

- BCD Bronze Circular Decorative Grate - Class A
- BDD Bronze Diagonal Decorative Grate - Class A
- DCD Ductile Iron Circular Decorative Grate - Class C
- DDD Ductile Iron Diagonal Decorative Grate - Class A
- DOG Ductile Iron Decorative Grate - Class A
- DWV Ductile Wave Decorative Grate - Class A
- HPB Heel-Proof Bronze Slotted Grate - Class A

MADE in the U.S.A. (Load Classifications are per DIN EN1433)

- AWG Aluminum Wire Grate - Class A
- BDE-USA Black Acid Resistant Epoxy Coated Ductile Grate - Class E
- DGC-USA Ductile Iron Slotted Grate - Class C
- DGE-USA Ductile Iron Slotted Grate - Class E
- FG Fabricated Galvanized Steel Slotted Grate - Class A
- GDC-USA Galvanized Ductile Slotted Grate - Class C
- GDE-USA Galvanized Ductile Slotted Grate - Class E
- PG Perforated Galvanized Steel Grate - Class A
- PPC Plastic Perforated Grate - Class C

Decorative MADE in the U.S.A. (Load Classifications are per DIN EN1433)

- BZ Bronze Decorative Grate - Class A
- NBZ Nickel Bronze Decorative Grate - Class A

*REGULARLY FURNISHED UNLESS OTHERWISE SPECIFIED

REV. A DATE: 04/01/11 C.N. NO. 121111
DWG. NO. 302086 PRODUCT NO. Z806-HDG

ZURN INDUSTRIES, LLC ♦ SPECIFICATION DRAINAGE OPERATION ♦ 1801 Pittsburgh Ave. ♦ Erie, PA 16514

Phone: 814455-0921 ♦ Fax: 814454-7929 ♦ World Wide Web: www.zurn.com

In Canada: ZURN INDUSTRIES LIMITED ♦ 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2 ♦ Phone: 905405-8272 Fax: 905405-1292