

PRODUCT SPECIFICATIONS

Cane Apron for EZ Gray. Overall dimensions are 17-5/8" x 9-9/16" x 5-1/2".

Finish:	Gray (GRY)
Dimensions:	17-5/8" x 9-9/16" x 5-1/2"
Shipping Weight:	2 lbs.

Special Note: For use with EZ style models.

- Cane touch apron designed for use in specific bi-level applications
- For when coolers or bottle fillers are installed on an exposed wall
- For use with EZ models
- Provides the mandatory 27" (686 mm) floor-to-underside requirement for detection in a circulation path when properly installed
- Light Gray vinyl finish is durable and attractive



Included with Product: Cane apron assembly

A Century of Tradition and Quality.

For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



[Installation Instructions \(PDF\) - 97629c](#)

PART: _____ QTY: _____

PROJECT: _____

CONTACT: _____

DATE: _____

NOTES: _____

APPROVAL: _____

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

36-7/16"
(926 mm)

18-3/8"
(467 mm)

Technical drawing of a wall-hung toilet showing required clearances and dimensions:

- Overall width: 19" (483 mm)
- Top rim height: *38-3/8" (975 mm) ORIFICE HEIGHT
- Second rim height: *32-7/8" (835 mm) ORIFICE HEIGHT
- Third rim height: *31-5/16" (795 mm) RIM HEIGHT
- ADA Requirement: *27" (686 mm)
- Trap arm horizontal distance: 8-1/16" (205 mm)
- Trap arm vertical distance: 1-1/2" (38 mm) TRAP NOT FURNISHED
- Trap arm horizontal distance: 5-7/8" (149 mm)
- Trap arm vertical distance: *12-1/2" (318 mm)
- FLOOR LINE

© 2026 Page 2
LKAPREZL spec.pdf