


CHAIN SLING HARDWARE

Eye Cradle Grab Hook – Code G

- For use with both G80 and G100 chain.
- Unique cradle grab design.
- Quenched and tempered alloy steel.
- 100% proof-tested.
- Fatigue rated.
- Durable powder-coated finish.
- Design factor 4:1.



Grade	Chain Size (in.)	1Rated Cap.* (lbs.)	Part Number	Dimensions (in.)										Wgt. Ea. (lbs.)
				B	D	E	G	H	I	K	L	M	P	
100	7/32	2,700	732DECGH	1.20	1.68	0.33	3.22	0.33	0.92	0.99	0.55	2.20	0.69	0.35
100	9/32	4,300	932DECGH	1.40	1.93	0.39	3.72	0.39	1.07	1.07	0.63	2.58	0.76	0.55
100	3/8	8,800	38DECGH	1.78	2.86	0.52	0.48	0.52	1.38	1.38	0.75	3.27	1.02	1.39
100	1/2	15,000	12DECGH	2.28	3.69	0.63	6.36	0.63	1.81	1.81	1.06	4.23	1.53	3.05
100	5/8	22,600	58DECGH	2.75	4.53	0.75	7.62	0.75	2.13	2.13	1.25	5.06	1.80	4.36
100	3/4	35,300	34DECGH	3.50	5.23	0.91	9.54	1.00	2.88	2.88	1.52	6.70	1.85	9
80	7/8	34,200	78G8ECGH	3.75	5.69	1.00	9.63	1.00	3.00	3.75	1.75	6.50	2.12	10.4
80	1	47,700	1G8ECGH	4.31	7.00	1.19	12.44	1.22	3.88	4.31	1.88	8.09	3.12	20.9
80	1-1/4	72,300	114GE8CGH	5.38	8.50	1.50	15.56	1.56	2.50	5.50	2.25	10.50	3.50	40


~ 1-1/4" is a Non-Cradle type. Also, Non-Cradle Grab Hooks are available for other sizes upon request.

¹ Rated Capacity also referred to as Working Load Limit.

Rigging Hardware

Clevis Cradle Grab Hook – Code G

- For use with both G80 and G100 chain.
- Unique cradle grab design.
- 100% proof-tested.
- Quenched and tempered alloy steel.
- Fatigue rated.
- Durable powder-coated finish.
- Replacement pin available.
- Design factor 4:1.



Chain Size (in.)	1Rated Capacity* (lbs.)	Part Number	Dimensions (in.)									Weight Each (lbs.)
			D	G	H	J	K	L	M	P	R	
9/32	4,300	932DCGH	2.18	3.39	0.38	0.82	0.97	0.36	0.38	0.82	1.86	0.63
3/8	8,800	38DCGH	2.72	4.33	0.47	1.18	1.29	0.51	0.47	1.03	2.47	1.30
1/2	15,000	12DCGH	3.65	5.27	0.65	1.39	2.01	0.63	0.60	1.19	3.04	2.10
5/8	22,000	58DCGH	4.50	6.54	0.77	1.55	2.42	0.75	0.77	1.41	3.76	4.20
3/4	35,300	34DCGH	5.40	8.80	0.88	2.05	2.69	0.88	0.91	1.89	5.30	10.50

¹ Rated Capacity also referred to as Working Load Limit.

* **WARNING** Do not exceed rated capacities. Sling capacity decreases as the angle from horizontal decreases. Do not use slings at angles of less than 30°. Refer to the Effect of Angle chart found in the General Information section of this catalog.