# **RIDGID** Kollmann

**Ridge Tool Company** 400 Clark St., Elyria, Ohio 44035-6001 U.S.A. Catalog Sheet No. R-01-L Effective Date: November 15, 2001 Visit us on the internet: www.ridgid.com or call Customer Service at 1-888-743-4333

## Demand the Best. . . New!

Introducing the professional's new choice in high powered drain cleaning machines . . .

## K-6200 Drain Cleaning Machine

The RIDGID/Kollmann K-6200 drum style drum cleaner provides the professional with a powerful yet compact machine for cleaning 3" to 6" drain lines. Superior maneuverability and a small footprint allow easy access to tight work areas. It comes equipped with either IC (Inner Core) cable for ultimate flexibility or IW (Integral Wound) cable, a new more durable solid core alternative cable. Several new features include:

**New Torque Limiter** – Causes the drum to slow down when the blade becomes lodged in a blockage. Protects cable by limiting potential for cable flipover.

**Direct Drive Design** – Powerful 4/10 Hp universal motor and gearbox bear down as torque builds. Audible warnings let operator know when blockage is encountered. Drum requires no adjustments to stay aligned and tight on drive shaft. Makes easy work of tough blockages such as roots and hardened grease.

**Easy Maintenance Construction** – Drum separates from machine in seconds. Inner drum and guide tube easily removed to maintain or replace cable.

**Durable, Stable Design** – Low center of gravity frame design and custom Kollmann kickstand keep machine firmly anchored during operation. Rugged, corrosion resistant polyethylene drum is rust and dent proof. Double tubular frame is lightweight and designed for extra strength.

Autofeed and Standard Accessories – Powerful feed mechanism is built to last and is easily maintained. Autofeed, toolbox, and selection of cutters included in all models.

**Converts Easily to \frac{1}{2}^{"} Machine** – Accepts K-3800 drum, with adaptors, to run up to 90' of  $\frac{1}{2}^{"}$  cable for use in floor drains and other interior piping systems up to 4".

### **Ordering Information**

### Machine Options – Power Feed

Catalog No. 115V	Model No.	Description	
95737	K-6200	Machine w/5/8" Pigtail & Standard Accessories	
95732	K-6200 w/C-24	Machine, Standard Accessories and 5/8" x 100' Inner Core Cable	
93557	K-6200 w/C-24-IW	Machine, Standard Accessories and 5/8" x 100' IW Solid Core Cable	





### RIDGID Kollmann. K-6200 Drain Cleaner

### **Specifications**

### Tools and Replacement Blades — Fits C-24, C-25, C-26, C-27,C-24 IW, C25 IW, C-26 IW, C-27 IW, C-24HC, C-27HC

	Catalog Model			Replacement	
	No.	No.	Description	Blade(s)	Holder*
S	92485 92490	T-403 T-404	P-Trap Cutter, 3" P-Trap Cutter, 3 <sup>1</sup> / <sub>2</sub> "	92835 92840	92900 92900
<b>ap</b>	92495	T-406	Spear Blade	92850	92915
	92500	T-407	Retrieving Auger	—	_
Ð	92505	T-408	Sawtooth Cutter	92890	92915
-3103300//////	51762	T-409	H-D Bulb Auger	_	_
	92510 92515 92520 92525 92530	T-411 T-412 T-413 T-414 T-416	Double Cutter, 2" Double Cutter, 2'/2" Double Cutter, 3" Double Cutter, 4" Double Cutter, 6"	92815 92820 92825 92830 92855	92905 92905 92910 92910 92910
E	92535 92540 92545 92550	T-432 T-433 T-434 T-436	3-Blade Cutter, 2" 3-Blade Cutter, 3" 3-Blade Cutter, 4" 3-Blade Cutter, 6"	92860 92865 92870 92875	92895 92895 92895 92895 92895

### **Optional Accessories**

- Cat. #95812 Autofeed K-6200
- Cat. #49032 Front Guide Hose Assembly
- Cat. #95797 Lifting Hook K-6200
- Cat. #95792 Swivel Loading Wheel Assembly
- Cat. #95802 K-6200 Drum Assy. w/5/8" Pigtail
- Cat. #95807 K-3800 Drum Assy. w/6200 Adapters
- Cat. #95822 K-3800 to K-6200 Adapter Kit Only
- Cat. #59982 Cable Rust Inhibitor 1 QT.
- Cat. #95587 Cable Rust Inhibitor 1 Gal.

### **Cables and Flexible Leaders**

	Catalog No.	Model No.	Description
<b>∽</b> ∽ 5/₃″ (16mm)	92460 92465 92470 43647	C-25 C-26 C-27 C-24	25' I.C. Cable (7,6m) 50' I.C. Cable (15,2m) 75' I.C. Cable (22,9m) 100' I.C. Cable (30,5m)
د <b>الي المراجع (1</b> 5/ه″ (16mm)	32737 58192	C-27HC C-24HC	75' Hollow-Core (22,9m) 100' Hollow-Core (30,5m)
	95762 95757 95752 95747	C-25 IW C-26 IW C-27 IW C-24 IW	25' I.W. Cable (7,6m) 50' I.W. Cable (15,2m) 75' I.W. Cable (22,9m) 100' I.W. Cable (30,5m)
2000 / 1000 C	92555	T-458	<sup>5</sup> /8" x 2' Leader
Summing and a second se	44122	_	⁵/₃″ Pigtail
	91047	_	<sup>5</sup> / <sup>s</sup> " Cable Repair Coupling (Fits over end of cable)



Standard Equipment Included In All Machine Options



**Machine In Reclined Position** 

