

M	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com LOCATION																
	FLOOR DRAINS																
	WITH 8 1/2"(215) ROUND ADJUSTABLE TOP AND "SAFE-SET" SEDIMENT BUCKET																
	Load Rating: Light Duty having a Safe Live (Static) Load less than 2,000 lbs. (900 kg) per ASME A112.6.3 Floor Drain Standard. For the specific Safe Live Load rating of any grate, contact the Smith representative or factory direct.																
DRAWING NUMBER S2350	SIZE A	SCALE: NONE	DATE: 5-17-85	Fig. 2350C . . . CAULK OUTLET Fig. 2350Y . . . NO-HUB OUTLET Fig. 2355C . . . CAULK OUTLET Fig. 2355T . . . THREADED OUTLET <table border="1" style="width: 100%; border-collapse: collapse; font-size: 10px;"> <tr> <th>A SIZE</th> <td>02 (50)</td> <td>03 (75)</td> <td>04 (100)</td> <td>06 (150)</td> </tr> <tr> <th>B</th> <td colspan="2">3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded</td> <td colspan="2">3 3/4 (95) NO-HUB Only</td> </tr> </table> REGULARLY FURNISHED: Ducto Cast Iron Body and Flashing Collar with Adjustable Top and Bar Grate with Sediment Bucket. ▲ Not available in Safe-Set design. Full grate is provided with a suspended bucket. VARIATIONS: ▲ ☐ Dome Grate -D ☐ Extension (Specify Height) -E ☐ Flat Bottom Strainer -FBS ☐ L Speedi-Set Service Weight (Fig. 2350 only) ☐ LXH Speedi-Set Extra Heavy (Fig. 2350 only) ☐ NO-HUB Adaptor (Specify Fig. 2646Y) (Fig. 2355 only) ☐ Square Top -S ** ☐ Trap Primer Connection -P050 1/2"(13) & -P075 3/4"(19) ☐ Vandal Proof Top -U ☐ T Threaded Outlet ☐ Quad Close Trap Seal (Specify Fig. 2692) (Fig. 2350 Only) OPTIONAL MATERIALS: ☐ Ductile Iron Bucket and Grate -MGB ☐ Galvanized Cast Iron -G ☐ Nickel Bronze Top -NB ☐ Polished Bronze Top -PB **Not available on Fig. 2350T threaded outlet drain. NOTE: Dimensions shown in parentheses are in millimeters.				A SIZE	02 (50)	03 (75)	04 (100)	06 (150)	B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only	
A SIZE	02 (50)	03 (75)	04 (100)					06 (150)									
B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only														
WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA																	
DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE																	
APPROVED BY: TD																	
CHECKED BY: TD				2350, 2355 FIGURE NUMBER 2350, 2355													
DRAWN BY: PJ																	
FIGURE NUMBER																	
REV.																	
DATE				DESCRIPTION													
BY				CKD. BY													
WEIGHT POUNDS				VOLUME CUBIC FEET													
FIGURE NUMBER				FIGURE NUMBER													



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov