




Schedule 80 PVC Technical Schedule 80 Tank Adapters

Tank Adapter, PVC Old Style with Neoprene Gasket

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°
F (23°C)

Dimensions Also Applicable to
871E-XXX EPDM Gasket




Part Number	Size	L	L1	M	M1	N	R	Approx. Wt. (Lbs.)
871-005	1/2	2-27/32	2-3/16	2-3/8	1- 9/32	1-11/32	5/8	.24
871-007	3/4	2-23/32	2-1/16	2-5/8	1- 5/8	29/32	5/8	.29
871-010	1	2-25/32	2- 1/8	2-13/16	1- 7/8	25/32	21/32	.33
871-012	1-1/4	3- 1/8	2- 7/16	3-29/32	2-11/32	27/32	5/8	.65
871-015	1-1/2	3- 5/32	2-21/32	3-29/32	2-11/32	3/4	5/8	.54
871-020	2	3- 3/16	2-17/32	4-31/32	3-15/32	13/16	3/4	1.33
871-030	3	4-19/32	3-13/16	6- 7/16	4-15/32	31/32	1- 3/16	2.46
871-040	4	4- 7/16	3-23/32	7- 7/16	5- 1/2	1/2	1- 1/4	3.16

Tank Adapter, PVC Old Style with Neoprene Gasket

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°
F (23°C)

Dimensions Also Applicable to
872E-XXX EPDM Gasket




Part Number	Size	L	L1	M	M1	N	R	Approx. Wt. (Lbs.)
872-005	1/2	2-27/32	2-3/16	2-3/8	1- 9/32	1-15/32	5/8	.24
872-007	3/4	2-23/32	2-1/16	2-5/8	1- 5/8	1-1/4	5/8	.30
872-010	1	2-25/32	2-1/8	2-7/8	1- 7/8	1-5/16	5/8	.34
872-012	1-1/4	3- 1/8	2-7/16	3-15/16	2-11/32	1- 1/8	5/8	.66
872-015	1-1/2	3- 1/8	2-7/16	3-15/16	2-11/32	1- 1/16	5/8	.57
872-020	2	3-3/16	2- 3/8	5-3/32	3-15/32	3/4	3/4	1.37
872-030	3	4-19/32	3-11/16	6-19/32	4-7/16	1-1/8	1- 3/16	2.55
872-040	4	4-15/32	3-17/32	7-11/16	5- 1/2	17/32	1- 1/4	3.34

Tank Adapter, Spigot PVC with EPDM Gasket

Spigot

150 psi Maximum Internal Pressure Rating @ 73°
F (23°C)



Part Number	Size	A	L	L1	M	Approx. Wt. (Lbs.)
8173E-005	1/2	1-3/16	3	1-3/4	1-1/2	.11
8173E-007	3/4	1-1/4	3	2	1-11/16	.14