


Water Closet -43/4"-PUSH BUTTON (TYPE AND LOCATION SUPPLY OPTIONAL) (DN 25mm) CONNECTION THROUGH 16" WALL NOT CENTER LINE (406mm) SUPPLIED OF FIXTURE SLOANTER LINE OF WASTE 4 1/8" max. (105mm) 2 1/8" min. (54mm) 3 1/4" (83mm) FIN. FIN LONG FLUSH TUBE **FLQOR** WALL (for connection behind wall)



© Copyright 1997 SLOAN VALVE COMPANY Printed in U.S.A.

Hydraulic Royal® Prison Model Flushometer



Description

Concealed Hydraulically Operated Water Closet Flushometer, for Stainless Steel back spud water closets and Combination Fixtures. For use with: Acorn® • Bradley® • Metcraft® • Willoughby® and similar fixtures.

Flush Cycle

- Model 9603 Water Saver (3.5 gpf/13.2 Lpf)
- ☐ Model 9603-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

Specifications

Quiet, Concealed, Diaphragm Type, Rough Brass Closet Flushometer for either left or right hand supply with the following features:

- Dual Filtered By-Pass
- Diaphragm, Handle Packing, Stop Seat and Vacuum Breaker to be molded from PERMEX™ rubber compound for Chloramine resistance
- ADA Compliant Non-Hold-Open feature type Actuator (specify Actuator type listed below)
- 1" I.P.S. Wheel Handle Bak-Chek™ Angle Stop
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker
- Elbow Flush Connection and Coupling for 1½" NPT Back Inlet (for connection in the pipe chase flush connection through the wall not provided by Sloan)
- Sweat Solder Adapter
- Exposed parts Chrome Plated

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.6, and Military Specification V-29193.

Actuator Types: (please check one)

☐ MBFW Metal Button Fixture Wall Actuator (HY-100-A) (rear access)

☐ MBPM Metal Button Panel Mount (HY-108-A) for use only with Wall Box or when Access Panel is provided in combination fixture

See Hydraulic Flushometer Section of the Sloan catalog for details on Actuators.

Variations

☐ **AFD** Shorter Vacuum Breaker - for use with Anti-Flood Device (Anti- Flood Device NOT provided by Sloan)

Trap Primer Elbow

▶ Prison Flushometers can also be provided in Regal® Models. All rough-in dimensions remain the same.

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.







This space for Architect/Engineer approval

NI

The information contained in this document is subject to change without notice.

Made in the U.S.A.

SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL 60131 PHONE: 1-800 982-5839 • FAX: 1-800 447-8329 • http://www.sloanvalve.com