

Specifications: 3 Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Mfg. Plant	Shipping Weight
			H	W	D		
2TTA3030A3000A	200-230/3/60	30,000	33	33	30	TY	225
2TTA3036A3000A	200-230/3/60	36,000	33	33	30	TY	216
2TTA3042A3000B	200-230/3/60	42,000	33	37	34	TY	245
2TTA3048A3000A	200-230/3/60	48,000	41	37	34	TY	303
2TTA3060A3000A	200-230/3/60	60,000	41	37	34	TY	292
2TTA3030A4000A	460/3/60	30,000	33	33	30	TY	225
2TTA3036A4000A	460/3/60	36,000	33	33	30	TY	219
2TTA3042A4000B	460/3/60	42,000	33	37	34	TY	246
2TTA3048A4000A	460/3/60	48,000	41	37	34	TY	305
2TTA3060A4000A	460/3/60	60,000	41	37	34	TY	293

Accessories:

Model Number	Description	Used With	Mfg. Plant	Shipping Weight
Extended Warranties	(See Extended Warranty Section)			
Controls	(See Control Section)			
AY28X079	Evap. Defrost Control Kit	All Cooling Models	TY	1
BAY24X045	ID Fan Delay Kit	All Cooling Models	TY	1
TAYASCT501A①	Anti-Short Cycle Timer	All Cooling Models	TY	1
BAYECMT001	Extreme Condition Mounting Kit	All Cooling Models	TY	2
BAYSDEN001	Sound Enclosure 1 Cycle Recip	2.5 Ton Models	TY	8
BAYSDEN002	Sound Enclosure 2 Cycle Recip	3.5 - 4 Ton Models	TY	8
BAYSDEN003	Sound Enclosure Small Scroll	3 Ton Models	TY	8
BAYSDEN004	Sound Enclosure Large Scroll	5 Ton Models	TY	8
BAYLEGS002	Snow/Sand Legs	All Cooling Models	TY	1
BAYLEGS003	4" Extension	All Cooling Models	TY	1
BAYSEAC001	Seacoast Kit	All Cooling Models	TY	1
BAYLOAM103	Low Ambient Kit	All Cooling Models	TY	1
BAYISLT101	Rubber Isolators	All Cooling Models	TY	1

① Not for use with digital controls.

Features:

- **Climatuff®** compressor
- All aluminum **Spine Fin™** coil
- **WeatherGuard™** fasteners
- **Quick-Sess™** cabinet, service access and refrigerant connections with full coil protection
- **DuraTuff™** base, fast complete drain, weather proof
- **Comfort"R"™** mode approved
- Glossy corrosion resistant finish
- Internal compressor high/low pressure & temperature protection
- Compressor Sump Heat
- Liquid line filter-drier
- Polyslate gray cabinet with anthracite gray badge & cap
- Low pressure switch
- R-22 refrigerant
- **5 year limited warranty on compressor, coil, and internal functional parts (Residential Use Only)**
- **5 year limited warranty on compressor, coil, and 1 year on parts (Commercial Use Only)**
- **Extended warranties available**
- S.E.E.T. design testing
- 100% line run test
- Low ambient cooling to 55°F as shipped
- Low ambient cooling to 30°F with AY28X079
- Low ambient cooling to 0°F with BAYLOAM103

