

Flip-Top Fiberglass Enclosures

- **Easy Maintenance Access** - Flip top lid design provides quick access.
- **Weatherproof & Vandal Resistance** - Overlapping lid seam design helps keep vandals and mother nature out. Also includes a lockable top and steel anchors (padlocks are not included).
- **Durable & Corrosion Resistant** - Reinforced fiberglass with a smooth, UV resistant gelcoat provides a corrosion proof finish that both looks good and stands up to the elements.
- **Superior Freeze Protection** - Wall-mounted heater or self-regulating heat trace tape provides freeze protection.
- **Peace of Mind** - ASSE 1060 certification ensures that requirements for structural strength, drainage capacity, material construction, equipment access, and functional design are met.



Note: Standard fiberglass color is beige (optional colors are available-see page 49 for details). Also available as uninsulated enclosures (see page 35).

For unheated units, replace the “H” in the part# with an “L”. Pad size=inside Dimensions + 12”.

Catalog Part Number	Model Number	Inside Width (in)	Inside Length (in)	Inside Height (in)	Heater(s)	Glass Pad	Weight #
HF011019022	HB.75	10	18	23	30W	GG019027005	28
HF013027023	HB1	13	26	23	60W	GG021035005	32
HF013027035	HB1T	13	26	36	60W	GG021035005	57
HF013039028	HB2	13	38	29	90W	GG021047005	54
HF013039036	HB2T	12	38	36	90W	GG021047005	65
HF013047028	HB2S	10	44	28	90W	N/A	64
HF013047036	HB2ST	13	47	36	90W	N/A	98
HF021033025	HB1.5	21	33	25	60W	GG029042005	55
HF025039028	HB2-D	25	39	28	(2) 90W	N/A	124
HF025039036	HB2-DT	25	39	36	(2) 90W	N/A	148
HF025047028	HB2-DS	25	47	28	(2) 90W	N/A	139
HF025047036	HB2-DST	25	47	36	(2) 90W	N/A	168
HF026070045	HB3N	27	70	46	1000W	N/A	241
HF026070055	HB3E	26	70	55	1500W	N/A	322
HF026083045	HB3NS	26	83	45	1500W	N/A	308
HF026083055	HB3ES	26	83	55	1500W	N/A	374
HLO35045035	HB3000	35	44	35	1000W	N/A	170
HLO44053044	HB4000	44	53	45	1000W	N/A	251
HLO52061052	HB5000	52	61	51	1500W	N/A	320

For unheated units, replace the “H” in the part# with an “L”. Pad size=inside Dimensions + 12”.