



PRODUCT SPECIFICATIONS

Pipe Type	Plastic, clay, concrete, cast iron & cement asbestos
Color	Amber
pH (1%)	9.5
Alkalinity	100 mg KOH/g Equivalent
Free Fatty Acid	1-3%
Performance Specification	NSF/ANSI 61, NSF/ANSI 372, AWWA
Penetration	300-350- 1/10mm @ 77F (25C) 200-250 1/10mm @ 0F (-18C)
Specific Gravity	Typical 1.118 +/- 0.04
Industry Listing	 Certified to NSF/ANSI 61-G
Max VOC Emissions	<5% per SCAQMD Rule 1168 Method 316A 
Shelf Life	3 Years
LEED Compliant	Low VOC formulation can earn credit toward the U.S. Green Building Council's LEED certification for green buildings. 

PRO-LUBE™

Christy's **Pro-Lube** is a water dispersible, high performance pipe joint lubricant that has been certified by NSF for use in potable water supply systems. The creamy consistency allows the installer to apply a smooth, consistent coating to both gasket and pipe.

- **Water Soluble, Non-Toxic Petroleum and Phosphate Free**
- **Does not dry out when gaskets are stored in sealed plastic bags or container**
- **Maintains soft paste consistency and color**
- **Ideal for all types of pipe (asbestos cement, cast iron, concrete, plastic and clay)**
- **Does not deteriorate natural or synthetic rubber or plastic gaskets**
- **Low VOC**

CASE PACK CONFIGURATIONS

Item #	Can Size	Cans/Cs	Can UPC
RH-PRO-QT	Quart, 32 oz (946 ml)	12	044752410083
RH-PRO-GL	Gallon, 128 oz (3.785 l)	4	044752410168
RH-PRO-5	5 Gallon, 640 oz (640 l)	1	044752131278

Estimated Usage Chart

PIPE SIZE	LBS. PER 100 JOINTS	PIPE SIZE	LBS. PER 100 JOINTS
4"	3	30"	22
6"	4	36"	28
8"	5	42"	32
10"	6	48"	40
12"	9	54"	45
15	11	60"	54
18"	13	66"	60
21"	16	72"	67
24"	17	78"	70
27"	19	84"	77

T. Christy Enterprises, Inc.



655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE