



RATCHET ASSEMBLIES

		Series 5,000			Series 10,000		
WEB WIDTH		2"			2"		
*ULTIMATE BREAKING STRENGTH		5,000 lbs.			10,000 lbs.		
WORKING LOAD LIMIT		1,600 lbs.			3,300 lbs.		
End Fitting	Length** (ft.)	Standard Part No.	Tuff-Edge® Part No.	Weight (lbs.)	Standard Part No.	Tuff-Edge Part No.	Weight (lbs.)
Flat Hook 	27	60501	TE60501	4.6	61001	TE61001	5.8
	30	60502	TE60502	4.8	61002	TE61002	6.0
Stamped Triangle 	27	60503	TE60503	4.2	61003	TE61003	5.2
	30	60504	TE60504	4.4	61004	TE61004	5.4
Stamped Snap Hook 	27	60505	TE60505	4.6	61005	TE61005	6.2
	30	60506	TE60506	4.8	61006	TE61006	6.4
Twisted Snap Hook 	27	60507	TE60507	5.2	61007	TE61007	5.6
	30	60508	TE60508	5.4	61008	TE61008	5.8
Forged Snap Hook 	27	60509	TE60509	5.8	61009	TE61009	6.4
	30	60510	TE60510	6.0	61010	TE61010	6.6
D-Ring 	27	60511	TE60511	4.2	-	-	-
	30	60512	TE60512	4.4	-	-	-
U-Hook 	27	60513	TE60513	4.6	26422	TE26422	5.8
	30	60514	TE60514	4.8	26423	TE26423	6.0
Hook & Keeper 	27	60515	TE60515	4.8	-	-	-
	30	60516	TE60516	5.0	-	-	-
Chain Anchor Assembly 	27	-	-	-	61013	TE61013	13.0
	30	-	-	-	61014	TE61014	13.2
Type A (Endless) 	27	60517	TE60517	3.8	61011	TE61011	4.4
	30	60518	TE60518	4.0	61012	TE61012	4.6


* Ultimate breaking strength of assembly when new.

** Non-standard lengths available.

Note: Since end terminations vary proportionally with size, check with Lift-All if precise dimensions are required.

CORNER GUARD

- Movable, rust-proof copolymer design.
- Protects from sharp edges.
- Tough enough for chain or webbing.
- Corner Guard is to be used with 2"- 4" webbing.
- Part Number **CG**



⚠ WARNING Always protect Tiedowns from being cut by corners and edges. **Always protect synthetic slings from being cut by corners and edges. See the Sling Protection section in this catalog.**