# Single Size Pneumatic Pipe Plugs

The Single Size Pneumatic Pipe Plug is designed for the testing of pipelines or to temporarily stop the flow. Each size is designed for one specific pipe size. These plugs can be used in a variety of fitting applications and are suitable for most pipe materials. Because they are pneumatic they conform to irregular pipe shapes and seal effectively. Manufactured from a durable natural rubber compound these plugs are flexible yet rugged. Plugs up through 6" come with a 12" chain and a ring assembly attached to a molded inflation valve. Larger plugs come with a replaceable tank valve and an eyebolt for tethering. A metal cap/core tool is also included.

| Floor Drain | Roof Vent | Municipal Storm Drain | Closet Bend | Test Tee | Sanitary Tee |

Boxed		Pipe Use Range						Maximum Back Pressure			
Nominal Size (inches)	Product Code	Minimum Pipe Diameter (inches)	Maximum Pipe Diameter (inches)	Plug Diameter (inches)	Plug Length (inches)	Overall Plug Length (inches)	Inflation Pressure (psig)	Water Head (feet)	Air (psig)	Units / Case	Shipping Weight (pounds)
1 1/4-1 1/2	83621	1.18	1.75	1.13	3.75	5.25	40	30	13	6	2.1
2	83622	1.85	2.25	1.75	1.50	3.00	40	30	13	6	2.3
3	83623	2.63	3.25	2.5	3.25	4.75	35	30	13	6	3.2
4	83624	3.41	4.25	3.25	4.25	5.75	30	30	13	6	4.3
5	83625	4.46	5.25	4.25	5.75	7.25	30	30	13	1	1.5
6	83626	5.25	6.25	5.25	7.25	8.75	30	30	13	1	2.7
8	83628	7.09	8.25	6.75	9.50	11.50	25	40	17	1	4.7
10	83630	8.92	10.25	8.50	11.50	13.50	25	40	17	1	7.8
12	83632	11.02	12.25	10.50	13.75	15.75	25	40	17	1	11.0
15	83635	13.39	16.25	12.75	18.00	21.50	25	40	17	1	24.8

Bulk		Pipe Use Range						Maximum Back Pressure			
Nominal Size (inches)	Product Code	Minimum Pipe Diameter (inches)	Maximum Pipe Diameter (inches)	Plug Diameter (inches)	Plug Length (inches)	Overall Plug Length (inches)	Inflation Pressure (psig)	Water Head (feet)	Air (psig)	Units / Case	Shipping Weight (pounds)
1 1/4-1 1/2	83611	1.18	1.75	1.13	3.75	5.25	40	30	13	12	3
2	83612	1.85	2.25	1.75	1.50	3.00	40	30	13	12	3
3	83613	2.63	3.25	2.5	3.25	4.75	35	30	13	12	6
4	83614	3.41	4.25	3.25	4.25	5.75	30	30	13	12	9