

Liquid Tite Flexible Conduit

Product Liquid Tite Flexible Conduit

Purpose The DiversiTech liquid tite flexible conduit is for electrical applications inside, outside, and industrial uses including transformer connections, air conditioning, and heating.

- Features**
- Easy to install.
 - Joins with metallic or non-metallic connectors.
 - Easy to cut.
 - Will not kink.

- General Specifications**
- Max Temp:
 - 176°F Dry
 - 140°F Wet
 - 158°F Oil
 - UV Resistant: Titanium Dioxide and Carbon Black act as a UV inhibitor
 - Impact resistant
 - Chemical Resistant
 - UL and cUL Listed
 - Warranty - 1 year
 - For use as indicated in Article 351 of the 1987 NEC
 - Outdoor direct burial

Printed on Conduit: DIVERSITECH NON-METALLIC
LIQUID-TIGHT CONDUIT 75 C FNMC-8 OUTDOOR
DIRECT BURIAL 80° C DRY 60° C WET
70° C OIL RES C(UL)US LISTED 3FF0



750-10100

General Characteristics

Model	Size	Metallic or Non-Metallic	Length	Weight
750-10100	1 inch	Non-Metallic	100 feet	12.5 lbs
750-10500	1 inch	Non-Metallic	500 feet	26.6 lbs
750-12100	1/2 inch	Non-Metallic	100 feet	12.5 lbs
750-121000	1/2 inch	Non-Metallic	1000 feet	144 lbs
750-12100BOX	1/2 inch	Non-Metallic	100 feet	14.2 lbs
750-125100	1.25 inch	Non-Metallic	100 feet	12.5 lbs
750-15100	1.5 inch	Non-Metallic	100 feet	12.5 lbs
750-1550	1.5 inch	Non-Metallic	50 feet	12.5 lbs
750-2050	2 inch	Non-Metallic	50 feet	33.8 lbs
750-34100	3/4 inch	Non-Metallic	100 feet	16 lbs
750-34800	3/4 inch	Non-Metallic	800 feet	151 lbs
750-38100	3/8 inch	Non-Metallic	100 feet	12.5 lbs
750-500	1/2 inch	Metallic	500 feet	27.4 lbs
750-600	3/4 inch	Metallic	100 feet	44 lbs