

rupture, creating serious risks of suffocation, fire and Earthquake Valve Manufacturer to offer a complete line of explosion. Little Firefighter Earthquake Gas Shut-Off Valves Valves (3/4" - 2" npt) for both Horizontal and Vertical insafeguard your loved ones, home and belongings 24 hours a stallations to fit most meter and piping configurations. dav.

Model	Pipe Size	Max. Pressure	L	w	Н	Wt. (Ibs)	Flow at 0.5" W .C. Pressure Drop	Flow at 1" W .C. Pressure Drop	Cν	Equivalent Pipe Length
A G V -075	3/4"	5 psi	3"	1.5"	3"	1	692,000 BTU/HR	977,000 BTU/HR	14.8	4
A G V -100	1"	5 psi	4 "	1.7"	3.5"	1.5	1,153,000 BTU/HR	1,628,000 BTU/HR	30.2	3
AGV-125	1-1/4"	5 psi	4 "	2.3"	4.6"	2	1,889,000 BTU/HR	2,677,000 BTU/HR	48.1	5
A G V -150	1-1/2"	5 psi	6"	3"	5.5"	6	4,079,000 BTU/HR	4,079,000 BTU/HR	76.3	5
A G V -150H P	1-1/2"	60 psi	6"	3"	5.5"	6	4,079,000 BTU/HR	4,079,000 BTU/HR	76.3	5
A G V -200	2"	5 psi	6"	3"	5.5"	6	4,079,000 BTU/HR	4,079,000 BTU/HR	90.7	15
A G V -200H P	2"	60 psi	6"	3"	5.5"	6	4,079,000 BTU/HR	4,079,000 BTU/HR	90.7	15
V A G V -075	3/4"	10 psi	2.5"	2"	3.4"	1	600,000 BTU/HR	895,000 BTU/HR	16.4	3
V A G V -100	1"	10 psi	2.5"	2"	3.4"	1	515,000 BTU/HR	765,000 BTU/HR	14.1	10
V A G V -125	1-1/4"	10 psi	2.5"	2"	3.4"	1	440,000 BTU/HR	650,000 BTU/HR	12	75
V A G V -125H F	1-1/4"	2 psi	4.2"	3.3"	5.2"	7	2,200,000 BTU/HR	3,100,000 BTU/HR	56.5	4
V A G V -150	1-1/2"	2 psi	4.2"	3.3"	5.2"	7	2,400,000 BTU/HR	3,700,000 BTU/HR	68.8	6
V A G V -1 50 H P	1-1/2"	60 psi	4.2"	3.3"	5.2"	7	2,400,000 BTU/HR	3,700,000 BTU/HR	68.8	6
V A G V -200	2"	2 psi	4.2"	3.3"	5.2"	7	1,800,000 BTU/HR	2,500,000 BTU/HR	46.8	40
V A G V -200H P	2"	60 psi	4.2"	3.3"	5.2"	7	1,800,000 BTU/HR	2,500,000 BTU/HR	46.8	40



