

Raci Spacer Options: **Medium**

| Type F, G 25, 41, 60, 75 mm | | | | | |
|------------------------------------|-------------------|-------------------|-----|--------------------------------|---|
| O.D. range inches | | O.D. range mm | | No. of elements to make a ring | |
| min | max | min | max | F | G |
| 3.62 | 4.53 | 92 | 115 | 1 | 1 |
| 4.57 | 5.98 | 116 | 152 | 2 | - |
| 6.02 | 7.40 | 153 | 188 | 2 | 1 |
| 7.44 | 8.82 | 189 | 224 | 3 | - |
| 8.86 | 10.24 | 225 | 260 | 3 | 1 |
| 10.28 | 11.61 | 261 | 295 | 4 | - |
| 11.65 | 12.32 | 296 | 313 | 4 | 1 |
| 12.36 | 14.80 | 314 | 376 | 5 | - |
| 14.84 | 17.56 | 377 | 446 | 6 | - |
| 17.60 | 20.79 | 447 | 528 | 7 | - |
| Elements | Runner Height In. | Max Load Per Ring | | | |
| | | Lbs | | Kg | |
| F/G 25 | 0.98 | 1540 | | 700 | |
| F/G 41 | 1.61 | 1870 | | 850 | |
| F/G 60 | 2.36 | 1870 | | 850 | |
| F 75 | 2.95 | 1870 | | 850 | |