



Service Saddle

Double Stainless Steel Strap

317



Description: Double strap Ductile Iron service saddle with TaperSeal™ gasket and wraparound 304 Stainless Steel strap for added corrosion resistance

Application: For outlets of 5/8" through 4".

Key Features:

- Meets applicable AWWA C800 Standards
- The wide saddle body provides stability on the pipe
- Designed with PVC and other soft or brittle pipe in mind
- The gasket fully bonds to the cavity to hold it in place
- NPT, CC and other threaded outlets available in sizes 5/8" thru 4"
- Wide bands spread the load over larger area to prevent damage to the pipe when tightening the straps
- A closed lug on one side, combined with the strap, acts as a hinge for easier installation

Materials Specifications (subject to change):

BODIES: Ductile Iron per ASTM A536

STRAPS: Type 304 Stainless Steel. Double Strap 1.50" wide

NUTS: Type 304 Stainless Steel fluoropolymer coated

WASHERS: Type 304 Stainless Steel

STUDS: Type 304 Stainless Steel

GASKET: Nitrile (Buna N) NSF 61® compounded to resist oil, acids, alkalis, most (aliphatic) hydrocarbon fluids, water and other chemicals

Temperature Range: -20°F to 180°F

FINISH: Flexi-Coat® Fusion-Bonded Epoxy Finish per AWWA C213

Working Pressure: Up to 300 PSI, depending on size and application

Pipe Applications: Steel, Ductile Iron, Cast Iron, Asbestos Cement, PVC and HDPE (with spring washers)

Taps: 5/8", 3/4", 1", 1 1/4", 1 1/2" and 2" CC Taps; 3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2", 3" and 4" NPT Taps

Sizes (in inches): Varies by tap type; see tables for size details

1¼", 1½", 2" and 2½" NPT Taps

*Sized for use on C900 PVC Pipe

STANDARD			CATALOG NUMBER				CTN. QTY	METRIC		
NOM. SIZES INCHES	O.D. RANGE INCHES	WT. EACH LBS.	1-1/4" NPT/32 MM	1-1/2" NPT/40 MM	2" NPT/50 MM	2-1/2" NPT/65 MM		NOM. SIZE MM	O.D. RANGE MM	WT. EACH KG.
2	2.35-2.56	3	317-00025610-000	317-00025612-000	-	-	6	50	60-65	1
3	2.97-3.54	5	317-00035410-000	317-00035412-000	317-00035414-000	-	6	80	76-89	2
3-4	3.74-4.13	8	317-00041310-000	317-00041312-000	317-00041314-000	317-00041316-000	6	80-100	95-105	3
4	4.40-4.50	6	317-00045010-000	317-00045012-000	317-00045014-000	317-00045016-000	6	100	112-114	3
4*	4.40-4.80	6	317-00048010-000	317-00048012-000	317-00048014-000	317-00048016-000	6	100	112-122	3
4-5	4.74-5.14	6	317-00051410-000	317-00051412-000	317-00051414-000	317-00051416-000	6	100	120-130	3
4-5	5.00-5.63	9	317-00056310-000	317-00056312-000	317-00056314-000	317-00056316-000	4	100-125	121-143	4
6	6.94-6.70	9	317-00066310-000	317-00066312-000	317-00066314-000	317-00066316-000	4	150	151-170	4
6*	5.94-6.90	9	317-00069010-000	317-00069012-000	317-00069014-000	317-00069016-000	4	150	151-175	4
6	6.84-7.60	7	317-00076010-000	317-00076012-000	317-00076014-000	317-00076016-000	4	150	174-193	3
6-8	7.69-8.72	11	317-00087210-000	317-00087212-000	317-00087214-000	317-00087216-000	4	150-200	195-221	5
6-8*	7.69-9.05	11	317-00090510-000	317-00090512-000	317-00090514-000	317-00090516-000	4	150-200	195-230	5
8-10	8.54-10.10	9	317-00101010-000	317-00101012-000	317-00101014-000	317-00101016-000	4	200-250	217-256	4
10*	10.75-11.10	9	317-00111010-000	317-00111012-000	317-00111014-000	317-00111016-000	4	250	273-282	5
10-12	10.64-12.12	11	317-00121210-000	317-00121212-000	317-00121214-000	317-00121216-000	4	250-300	271-307	5
12*	12.75-13.20	9	317-00132010-000	317-00132012-000	317-00132014-000	317-00132016-000	4	300	324-335	6
12-14	12.62-14.32	14	317-00143210-000	317-00143212-000	317-00143214-000	317-00143216-000	4	300-350	321-363	6
12-14	14.73-15.65	18	317-00156510-000	317-00156512-000	317-00156514-000	317-00156516-000	1	300-350	375-397	8
14-16	15.95-17.25	19	317-00172510-000	317-00172512-000	317-00172514-000	317-00172516-000	1	350-400	406-438	9
16	17.25-17.80	19	317-00178010-000	317-00178012-000	317-00178014-000	317-00178016-000	1	410	438-452	9
16-18	17.40-18.88	19	317-00188810-000	317-00188812-000	317-00188814-000	317-00188816-000	1	400-450	442-479	9
18*	19.38-19.68	19	317-00195010-000	317-00195012-000	317-00195014-000	317-00195016-000	1	450	492-500	9
20*	21.55-21.65	19	317-00216010-000	317-00216012-000	317-00216014-000	317-00216016-000	1	500	547-500	9
24*	25.75-25.85	30	317-00258010-000	317-00258012-000	317-00258014-000	317-00258016-000	1	600	654-657	14

When properly sized from the factory, this product (denoted by *) meets the requirements listed in the Uni-Bell PVC Pipe Association's "Handbook of PVC Pipe" and in the AWWA's "Manual M23: PVC Pipe Design and Installation."

3" and 4" NPT Taps

*Sized for use on C900 PVC Pipe

STANDARD			CATALOG NUMBER		CTN. QTY	METRIC		
NOM. SIZES INCHES	O.D. RANGE INCHES	WT. EACH LBS.	3" NPT/80 MM	4" NPT/100 MM		NOM. SIZE MM	O.D. RANGE MM	WT. EACH KG.
6	6.84-7.60	13	317-00076017-000	317-00076018-000	2	150	174-193	6
8-10	8.54-10.10	15	317-00101017-000	317-00101018-000	3	200-250	217-256	7
10*	10.75-11.10	14	-	-	-	-	-	-
10-12	11.30-12.12	14	317-00121017-000	317-00121018-000	2	250-300	271-307	6
12*	12.75-13.20	18	-	-	-	-	-	-
12-14	13.40-14.32	18	317-00143017-000	317-00143018-000	2	300-350	321-363	8

When properly sized from the factory, this product (denoted by *) meets the requirements listed in the Uni-Bell PVC Pipe Association's "Handbook of PVC Pipe" and in the AWWA's "Manual M23: PVC Pipe Design and Installation."