

# **Pressure Gauge Accessories**

## **Pressure & Temperature Test Port Plugs**

Type 910.14.100

## Accessories, Mechanical

#### Application

Pressure and temperature test port plugs allow media access ideally for hydronic pressure and temperature measurement without disturbing the process. Units are equipped with a self sealing pierceable rubber diaphragm. A seperate master test pressure gauge or thermometer with piercing stem is required.

## **Standard Features**

### **Pressure Connection**

1/4" NPT or 1/2" NPT male

Material Brass; body neoprene or nordel diaphragm core

Self-sealing diaphragm material Neoprene or nordel


Pressure Rating Brass 1/4" NPT - VAC to 1000 PSI 1/2" NPT - VAC to 1000 PSI

SS 1/4" NPT - VAC to 1000 PSI 1/2" NPT - VAC to 1000 PSI


#### **Temperature Rating**

Neoprene 32-200°F max. Nordel 32-350°F max.





4339950 & 4343591



4339968 & 4343603

## THE MEASURE OF Total Performance™

#### **Ordering Information:**

State computer part number (if available) / model number / size / range / connection size and location / options required.

Specifications given in this price list represent the state of engineering at the time of printing. Modifications may take place and the specified materials may change without prior notice



WIKA Instrument Corporation 1000 Wiegand Boulevard Lawrenceville, Georgia 30043-5868 Tel: 770-513-8200 Fax: 770-338-5118 http://www.wika.com e-mail: info@wika.com