




Schedule 40 Fittings Technical
Schedule 40 Fittings Dimensions & Information

**Reducer Bushing
Flush Style**

Spigot x Socket



(Continued)

¹ Sized with Bushing
* Fabricated

Part Number	Size	L	N	Approx. Wt. (Lbs.)
437-585	8X6	4-13/32	1- 3/8	3.99
437-623 ¹	10X3	6	3-17/32	9.36
437-624 ¹	10X4	6	3- 3/4	8.85
437-626	10X6	5- 11/32	2- 5/16	6.76
437-628	10X8	5- 11/32	1- 5/16	7.19
437-666 ¹	12X6	6-11/16	3- 3/4	15.00
437-621 ¹	10X2	6	4	10.02
437-666F*	12X6	6-5/16	3-5/16	18.74
437-668	12X8	6- 1/2	2- 7/16	11.01
437-670	12X10	6- 11/32	1- 9/32	11.89
437-670F*	12X10	6	1	11.31
437-696F*	14X6	7-5/8	4-5/8	24.18
437-698F*	14X8	7- 5/16	3- 5/16	20.19
437-700F*	14X10	7-5/16	2-5/16	21.07
437-702F*	14X12	7	1	9.18
437-756F*	16X6	8-5/8	5-5/8	42.59
437-758F*	16X8	8- 5/16	4- 5/16	38.87
437-760F*	16X10	8-5/16	3-5/16	40.96
437-762F*	16X12	8	2	27.85
437-764F*	16X14	8	1	18.67
437-786F*	18X6	9-5/8	6-5/8	66.56
437-788F*	18X8	9-5/16	5-5/16	59.62
437-790F*	18X10	9-5/16	4-1/4	64.55
437-792F*	18X12	9	3	51.55
437-794F*	18X14	9	2	43.08
437-796F*	18X16	9	1	23.70
437-816F*	20X6	10-5/8	7-5/8	97.95
437-818F*	20X8	10- 5/16	6- 5/16	92.92
437-820F*	20X10	10-5/16	5-1/4	93.80
437-822F*	20X12	10	4	81.91
437-824F*	20X14	10	3	73.74
437-826F*	20X16	10	2	54.05
437-828F*	20X18	10	1	30.35
437-906F*	24X6	12-5/8	9-5/8	180.06
437-908F*	24X8	12- 5/16	8- 5/16	173.31
437-910F*	24X10	12-5/16	7-1/4	174.19
437-912F*	24X12	12	6	162.29
437-914F*	24X14	12	5	153.82
437-916F*	24X16	12	4	136.14
437-918F*	24X18	12	3	110.74