WIRE PIPE HOOK

506 series

SPECIFICATION

Sioux Chief 506 series wire pipe hooks shall be used where necessary to secure CTS tubing and IPS piping overhead from ceiling or floor joists in residential applications. Wire pipe hooks shall be made of 10-gauge material and offered in plain steel, copper plated steel or plastic coated steel options. Wire pipe hooks shall feature 20-degree "wow-bend" at the prong for easier installation into the wood joist.

MATERIALS

10-gauge wire (.135")

INSTALLATION


Intall wire pipe hook with hammer, striking each prong at wire bend. Drive prongs in evenly. Follow local or national codes when determining hanger spacing requirements.

TEMPERATURE RATING


melting point: 200°F (93°C) plastic coated models only

DIMENSIONS

Item No.	Finish	Α	В	С	D	Ε
506-24	Plain Steel	1/2"	4"	2.0"	1.22"	n/a
506-26	Plain Steel	1/2"	6"	2.0"	1.22"	n/a
506-34	Plain Steel	3/4"	4"	2.0"	1.22"	n/a
506-36	Plain Steel	3/4"	6"	2.0"	1.22"	n/a
506-38	Plain Steel	3/4"	8"	2.0"	1.22"	n/a
506-46	Plain Steel	1"	6"	2.0"	1.22"	n/a
506-56	Plain Steel	11/4"	6"	2.0"	1.22"	n/a
506-66	Plain Steel	1½"	6"	2.0"	1.22"	n/a
506-22C	CU Plated	1/2"	2.5"	1.51"	0.75"	n/a
506-32C	CU Plated	3/4"	2.5"	1.75"	0.75"	n/a
506-24C	CU Plated	1/2"	4"	2.0"	1.22"	n/a
506-34C	CU Plated	3/4"	4"	2.0"	1.22"	n/a
506-26C	CU Plated	1/2"	6"	2.0"	1.22"	n/a
506-36C	CU Plated	3/4"	6"	2.0"	1.22"	n/a
506-38C	CU Plated	3/4"	8"	2.0"	1.22"	n/a
506-46C	CU Plated	1"	6"	2.0"	1.22"	n/a
506-24P	Plastic Coated	1/2"	4"	1.22"	2.0"	2.5"
506-26P	Plastic Coated	1/2"	6"	1.22"	2.0"	3.0"
506-34P	Plastic Coated	3/4"	4"	1.22"	2.0"	2.5"
506-36P	Plastic Coated	3/4"	6"	1.22"	2.0"	3.0"
506-38P	Plastic Coated	3/4"	8"	1.22"	2.0"	3.0"
506-46P	Plastic Coated	1"	6"	1.22"	2.0"	3.0"







Create Item Number

506-ABC

e.g. 506-24CP = 4" long copper plated, plastic coated wire pipe hook for ½" CTS or IPS

	9				
<u>A</u>	TUBE SIZE	<u>B</u>	HOOK LENGTH	C_	FINISH
□ 2	½" nominal	□ 2	2.5" - copper plated only	□ _	plain steel - leave blank
□ 3	¾" nominal	□ 4	4"	□ C	copper plated
□ 4	1" nominal	□ 6	6"	□P	plastic coated
□ 5	11/4" nominal - plain steel only	□ 8	8"	□ СР	copper plated, plastic coated
□ 6	1½" nominal - plain steel only				