

Rev. 4-14 Shaded area indicates changes

- ☐ Catalog number---
A-2600-6-01BB flanged ends, with bronze disc facing
A-2602-6-01B1 flanged ends, with rubber disc facing
- ☐ Sizes---2", 2-1/2", 3", 4", 6", 8", 10", 12"
- ☐ Meets all applicable parts of ANSI/AWWA C508 Standard
- ☐ Epoxy coated interior & exterior for corrosion resistance
- ☐ Certified to ANSI/NSF 61
- ☐ Flanged end dimensions and drilling comply with ANSI B16.1, class 125
- ☐ Iron body, bronze mounted (IBBM)
- ☐ Choice of bronze or rubber disc facing
- ☐ For vertical or horizontal installation
- ☐ O-ring sealed stuffing box
- ☐ Adjustable weight to control opening and closing of clapper, lever can be installed on either side of valve
- ☐ 200 psig (1400 kPa/14 barg) maximum working pressure, 400 psig (2800 kPa/28 barg) test pressure




**A-2600-6-01BB**

Options

- ☐ Stainless Steel Nuts & Bolts ☐ Tapped Bosses
- ☐ Allen Bradley Limit Switch ☐ PN 10/PN 16 Flange Drilling 4"-12"

Check Valve Parts (2011-present)

Catalog Part No.	Description	Material	Material Standard
C-301	Retaining Plug	Brass	ANSI B21
C-306	O-ring C	Rubber	ASTM D2000, BK 707
C-307	O-ring B	Rubber	ASTM D2000, BK 707
C-308	Gasket	Rubber	ASTM D2000, BK 807
C-309	Cover Bolt	Zinc Coated Steel	ASTM A307 Grade B
C-310	Washer	Brass	ANSI B21
C-311	Spacer	Brass	ANSI B21
C-312	Disc Nut	Brass	ANSI B21
C-313	Disc Stud	Brass	ANSI B21
C-314	Snap Ring	Stainless Steel	ASTM A276 Type 420
C-315	Weight Bolt & Nut	Zinc Coated Steel	ASTM A307 Grade B
C-318	Pin	Stainless Steel	ASTM A276 Type 304
C-319	Test Plug	Malleable Iron	ASTM A47
C-320	Key	Stainless Steel	ASTM A276 Type 304
C-321	Hinge Pin	Stainless Steel	ASTM A276 Type 304
C-322	Weight Arm	Ductile Iron	ASTM A536 ▼
C-323	Bolt & Nut	Zinc Coated Steel	ASTM A307 Grade B
C-325	Seat Nut	Brass	ANSI B21
C-327	Body Seat Ring	Bronze	ANSI B62
C-329	Arm	Ductile Iron	ASTM A536 ▼
C-330	Weight	Cast Iron	ASTM A126 Cl. B
C-331	Cover	Cast Iron	ASTM A126 Cl. B
C-332	Disc	Cast Iron	ASTM A126 Cl. B
C-333	Body	Cast Iron	ASTM A126 Cl. B
Rubber Faced Disc Parts			
C-316	Disc Seat Bolt	Stainless Steel	ASTM A276 Type 304
C-326	Disc Seat Ring	Rubber	ASTM D2000, BK 807
C-328	Seat Holder	Cast Iron*	ASTM A126 Cl. B
Bronze Faced Disc Parts			
C-326	Disc Seat Ring	Bronze	ANSI B62



Valve body and clapper
Rubber faced disc shown
**Rubber faced disc clapper****Bronze faced disc clapper**
Hinge pin
and stuffing box
Lever assembly and weight

*2"- 6" sizes are cast iron, ASTM A126 Cl. B, 8"- 12" sizes are ductile iron ASTM A536

▼ Material strength ASTM A536 65-45-12 minimum

2"-12" SWING TYPE LEVER AND WEIGHT CHECK VALVE DIMENSIONS-FL.X FL.

Shaded area indicates change Rev. 6-15



Dimension**	Size*			
	2"	2-1/2"	3"	4"
Q (bore)	2.00	2.50	3.00	4.00
R	6.00	7.00	7.50	9.00
FF	8.00	8.50	9.50	11.50
X1	5.13	5.13	6.31	7.13
X2	2.81	3.56	4.06	4.94
A	4.94	5.69	6.06	6.88
P (hinge pin diameter)	.38	.38	.50	.50
B (number and size of bolts)	4--.75	4--.75	4--.75	8--.75
UU (bolt circle diameter)	4.75	5.50	6.00	7.50
Weight	35	51	62	84

Dimension**	Size*			
	6"	8"	10"	12"
Q (bore)	6.00	8.00	10.00	12.00
R	11.00	13.50	16.00	19.00
FF	14.00	19.50	24.50	27.50
X1	8.69	10.88	12.25	14.38
X2	5.94	8.06	9.19	10.81
A	8.50	9.94	11.19	13.56
P	.75	.88	1.00	1.13
B (number and size of bolts)	8--.88	8--.88	12--1.00	12--1.00
UU (bolt circle diameter)	9.50	11.75	14.25	17.00
Weight	156	277	418	638

*Nominal

**All dimensions are in inches. All weights are in pounds and are approximate.