

APPLICATION:		PRODUCT NAME: PRE-RINSE, SPRING STYLE, BACKSPLASH MOUNT	
JOB NAME:		☐ SPECIAL CONFIGURATION ☐ CHECK BASE MODEL AND OPTIONS	
QUANTITY:	ITEM NO.	MODEL:	
		☐ 13390 ULTRA SPRAY VALVE, WALL BRACKET ☐ 13366 ULTRA SPRAY VALVE, NO WALL BRACKET	
		OPTIONS OR MODIFICATIONS: ☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH ☐ ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE ☐ IN-LINE DUAL CHECK VALVE ☐ BRUSH ☐ ELBOWS ☐ VANDAL RESISTANT KIT ☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE ☐ OTHER _____	
		FEATURES CONTROL VALVE * 8" BACKSPLASH MOUNT * INTERNAL SPRING LOADED CHECK VALVES * SWIVELLING SEAT DISKS * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS * 1/2" SLIP JOINT KIT	
		HOSE * 36" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * 3 PLY FIBER REINFORCED INTERNAL RUBBER HOSE * REPAIRABLE IN FIELD WITH SIMPLE TOOLS	
		ULTRA SPRAY VALVE * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI * CLEANS FASTER - TEST PROVEN * ENGINEERED TO LAST - NO 'O' RINGS TO LEAK * INTERCHANGEABLE - FITS ALL BRANDS	
		SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC	
		SHIPPING WEIGHT * 12.0 LBS	
ROUGH-IN: 			