

# Open Snoot Assembly

## FNPT x FNST\* Connection



### Description

The single outlet open snoot is constructed of cast brass.

The single swivel is complete with gasket and comes standard with pin lugs. Outlet is 2 1/2" NPT female thread. Comes standard with 2 1/2" NST female swivel. Kit includes: open snoot, 2 1/2" brass plug with chain, and 2 1/2" FDC Brass Wall Plate.

### Installation

Installation can be achieved with tools readily available in the field using common installation practices. Make sure male threads of pipe to which the snoot is being attached are liberally coated with a pipe thread sealant such as PipeFit Thread Sealant with PTFE or PTFE Thread Seal-

ant Tape. Tighten the snoot until hand tight. Tighten one additional turn past hand tight to achieve a water tight seal of the threads. **DO NOT OVER TIGHTEN! Over Tightening may cause thread failure as well as cracking of the snoot body.**

### Specifications

Material:  
Cast brass

Size:  
2 1/2" FNPT x F Swivel\*

\*Available Swivels:

NST	3.0686" x 7.5TPI
BCT	3.000" x 8TPI
ONT	3.125" x 5TPI
QST	3.031" x 7TPI
PHX	3.062" x 6TPI
TEM	3.075" x 6TPI
CLV	3.078" x 8TPI
DET	3.125" x 7.5TPI

Check thread dimensions for other 2 1/2" applications.

