



## SANIFLUSH ELONGATED TOILET BOWL

ADA Compliant Close-Couple Toilet – 1.28 GPF (4.8 Liter Flush)

### SANIFLUSH 005 & 007

#### ◆ 007 Elongated Bowl

- Vitreous China
- Integral P-trap and a spigot rear outlet
- Seating Height: 16-3/4" (ADA Compliant)
- Large 3" trapway
- Wash down style toilet
- Low flush toilet; it uses 1.28 gallons (4.8L) per flush
- Toilet supplied with a set of lag screws, plastic anchors and china protectors
- Water spot measures 6 x 5 inches
- 1 Year Warranty

#### ◆ 005 Tank

- Vitreous China
- Insulated tank to prevent condensation
- The zero re-fill fill valve is easily adjustable
- The flush valve has a silicone flapper seal
- Water level mark applied to the overflow tube
- Toilet tank supplied with bowl screws, washers and wing nuts.
- 1 Year Warranty
- Warranty for fill and flush valve as per manufacturer.

#### Nominal Dimensions:

32" x 17-3/4" x 28-1/2"  
(813mm x 451mm x 724mm)

#### Fixture Dimensions and Hydraulic Performance – Meets or Exceeds the Following Specifications

- ANSI/ASME A112.19.2M and CAN/CSA B45 Requirements
- IAPMO/UPC Certificate of Listing

#### Notes

- Available in white
- Toilet Seat Recommended – Church model 585EC or equal. (not supplied)
- Replacement Fill Valve Recommended - Fluidmaster 400A or equal. (not supplied)



*Elongated Bowl with Tank (005 & 007)*

#### Care & Cleaning

- When cleaning toilet, wash it with mild soapy water or liquid cleaners that are not chlorine or bleach based. Avoid using detergents.
- We do not recommend the use of in-tank cleansers. Products containing chlorine can cause damage to the fittings inside the tank and cause them to fail prematurely.



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES. CHECK WITH LOCAL CODES





# SANIFLUSH ELONGATED TOILET BOWL

ADA Compliant Close-Couple Toilet – 1.28 GPF (4.8 Liter Flush)

**SANIFLUSH 005 & 007**

## Drawings and Dimensions

