

Campbell

Sediment Filters



part	flow (gpm)	inlet/ outlet connect.	overall length	bowl	cartridge*	PLASTIC FILTER (heavy duty)	
						master	ctn
1PS**	2 to 6	3/4	12-3/8	clear	1SS		6
1PS-B**	2 to 6	3/4	12-3/8	clear	1SS		6
1PS-B1**	2 to 6	1	12-3/8	clear	1SS		6
1PP**	2 to 6	3/4	12-3/8	opaque	1SS		1
1PP-B**	2 to 6	3/4	12-3/8	opaque	1SS		1
1PP-B1**	2 to 6	1	12-3/8	opaque	1SS		1
2PS	4 to 12	3/4	22-1/2	clear	1SS (2)		1
2PS-B	4 to 12	3/4	22-1/2	clear	1SS (2)		1
2PS-B1	4 to 12	1	22-1/2	clear	1SS (2)		1
2PP**	4 to 12	3/4	22-1/2	opaque	1SS (2)		1
2PP-B**	4 to 12	3/4	22-1/2	opaque	1SS (2)		1
2PP-B1**	4 to 12	1	22-1/2	opaque	1SS (2)		1



Rugged, industrial-strength plastic filters.

"B" models feature a pressure-release button for easy cartridge changing.

Double-length models have twice the sediment-holding capacity.

Max. pressure: 125 PSI. Max. temperature: 100°F.

Service Wrench included.

part	flow (gpm)	inlet/ outlet connect.	overall length	bowl	cartridge*	PLASTIC FILTER (standard)	
						master	ctn
SF10	2 to 6	3/4	13-1/4	clear	1SS		6

High-impact plastic filter features pressure-release button to vent housing, making cartridge changing easy. Service Wrench included.

Max. pressure: 125 PSI. Max. temperature: 100°F.



part	flow (gpm)	inlet/ outlet connect.	overall length	bowl	cartridge*	PLASTIC FILTER (valve-in-head)	
						master	ctn
VIH	2 to 10	3/4	14	clear	1SS		6

High-impact plastic filter features a built-in 2-position valve (ON for filtering OFF to change cartridge). Service Wrench included.

Max. pressure: 125 PSI. Max. temperature: 100°F.



Sediment Filters are used primarily at the point-of-entry on the main line for whole-house filtering: remove rust particles, sand, and algae appearing as cloudiness, rust, specks, dirt, particles on bottom of drinking glass or faucet aerator, stains on fixtures, or low water pressure.

All filters are individually cartoned.

* Standard cartridge included with filter housing.

Optional Mounting Brackets and Installation Kits available.

Campbell Manufacturing, Inc.
127 East Spring Street, P.O. Box 207
Bechtelsville, PA 19505-0207
800-523-0224, Fax 610-369-3580

Printed 5/05