

E	SMITH JAY R. SMITH MFG. CO. DIVISION OF SMITH INDUSTRIES, INC. POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF:				LOCATION	
	OPTIONAL STRAINER HEADS					
	DRAWING NUMBER PM0457 SH 1 of 2					
	SIZE A					
SCALE NONE						
DATE: 5-17-85						
APPROVED BY: TD						
CHECKED BY: TD						
DRAWN BY: PJ						
FIGURE NUMBER						










ASSUME NO RESPONSIBILITY OR USE OF SUPERSEDED OR VOID DATA
 DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

ROUND STRAINER MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: *Hinged Grate (Specify Suffix -AH) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.7em;"> <tr> <th>B DIA</th> <th>05 (125)</th> <th>06 (150)</th> <th>07 (180)</th> <th>08 (205)</th> <th>09 (230)</th> <th>10 (255)</th> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/2 (64)</td> <td>2 3/4 (70)</td> </tr> <tr> <td>X MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> </tr> <tr> <td>X MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/2 (64)</td> <td>2 3/4 (70)</td> </tr> </table> Specify Type, Size & Finish eg: A05NB *Not available for 05" (125) size SUFFIX -A	B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)	FLAPPER TYPE BACKWATER VALVE FUNCTION: Provides backwater protection at point where protection is needed. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: *Hinged Grate (Specify Suffix -AH) Vandal Proof Screws -U <table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.7em;"> <tr> <th>B DIA</th> <th>05 (125)</th> <th>06 (150)</th> <th>07 (180)</th> <th>08 (205)</th> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> </tr> <tr> <td>X MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> </tr> <tr> <td>X MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> </tr> </table> Specify Type, Size & Finish eg: AV05NB *Not available for 05" (125) size SUFFIX -AV	B DIA	05 (125)	06 (150)	07 (180)	08 (205)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)
B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)																																											
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)																																											
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)																																											
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)																																											
B DIA	05 (125)	06 (150)	07 (180)	08 (205)																																													
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)																																													
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																													
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																													
SQUARE STRAINER MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -BV) 05 (125), 06 (150), 07 (180) or 08" (205) sizes only *Hinged Grate (Specify Suffix -BH) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.7em;"> <tr> <th>B DIA</th> <th>05 (125)</th> <th>06 (150)</th> <th>07 (180)</th> <th>08 (205)</th> <th>09 (230)</th> <th>10 (255)</th> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> </tr> <tr> <td>X MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> </tr> <tr> <td>X MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/4 (57)</td> <td>2 3/8 (60)</td> </tr> </table> Specify Type, Size & Finish eg: B05NB *Not available for 05" (125) size SUFFIX -B	B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 1/4 (57)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 3/8 (60)	ADJUSTABLE STRAINER HEAD MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Gasketed Water Tight Cover -GC Secured Cover -SC Strainer Grate -SG Specify Type, Size & Finish eg: BSNB SUFFIX -BS																				
B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)																																											
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 1/4 (57)																																											
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)																																											
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 3/8 (60)																																											
REINFORCED ROUND STRAINER FUNCTION: Used in finished floors where light wheeled loads are anticipated. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -CV) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.7em;"> <tr> <th>B DIA</th> <th>05 (125)</th> <th>06 (150)</th> <th>08 (205)</th> <th>10 (255)</th> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/2 (64)</td> <td>2 3/4 (70)</td> </tr> <tr> <td>MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> <td>1 7/8 (48)</td> </tr> <tr> <td>MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 3/4 (70)</td> </tr> </table> Specify Type, Size & Finish eg: C06NB SUFFIX -C	B DIA	05 (125)	06 (150)	08 (205)	10 (255)	H	2 (51)	2 (51)	2 1/2 (64)	2 3/4 (70)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 7/8 (48)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 3/4 (70)	REINFORCED TRACTOR STRAINER FUNCTION: Used in finished floors where medium weight wheeled loads are anticipated and loose set non-tilt tractor grate is desired. MATERIALS: Cast Iron -CI Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -DV or -EV) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.7em;"> <tr> <th>SUFFIX</th> <th>B DIA</th> <th>H</th> <th colspan="2">X</th> </tr> <tr> <td></td> <td></td> <td></td> <td>MIN</td> <td>MAX</td> </tr> <tr> <td>-D</td> <td>07 (180)</td> <td>3 1/4 (83)</td> <td>2 5/8 (67)</td> <td>3 1/2 (89)</td> </tr> <tr> <td>-E</td> <td>09 (230)</td> <td>3 1/2 (89)</td> <td>2 3/4 (70)</td> <td>3 1/2 (89)</td> </tr> </table> Specify Type, Size & Finish eg: D09PB E09PB SUFFIX -D-E	SUFFIX	B DIA	H	X					MIN	MAX	-D	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)	-E	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)								
B DIA	05 (125)	06 (150)	08 (205)	10 (255)																																													
H	2 (51)	2 (51)	2 1/2 (64)	2 3/4 (70)																																													
MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 7/8 (48)																																													
MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 3/4 (70)																																													
SUFFIX	B DIA	H	X																																														
			MIN	MAX																																													
-D	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)																																													
-E	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)																																													
TILE FLANGE FUNCTION: Provides integral flange set 5/32" (4) below rim to receive floor covering. Flange may have option of tapped holes for securing pan and gasket. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -FV) Holes in Flange -SH Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.7em;"> <tr> <th colspan="3">X</th> </tr> <tr> <td>MIN</td> <td colspan="2">MAX</td> </tr> <tr> <td>1 1/4 (32)</td> <td colspan="2">2 1/8 (54)</td> </tr> </table> Specify Type, Size & Finish eg: F06NB SUFFIX -F	X			MIN	MAX		1 1/4 (32)	2 1/8 (54)		ADJUSTABLE STRAINER HEAD FUNCTION: Used in a non-traffic area when a funnel type strainer head is required and space does not allow use of the 3500 series funnel. The extended rim allows use as an anti-flood and anti-splash drip pan. VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -F37V or F38V) MATERIALS: Cast Iron -CI Chrome Plated -CP Galvanized Cast Iron -G Polished Bronze -PB Nickel Bronze -NB <table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.7em;"> <tr> <th>SUFFIX</th> <th>-F37</th> <th>-F38</th> </tr> <tr> <td>B DIA</td> <td>07 (180)</td> <td>09 (230)</td> </tr> <tr> <td>H</td> <td>3 1/4 (83)</td> <td>3 1/2 (89)</td> </tr> <tr> <td>MIN</td> <td>2 5/8 (67)</td> <td>2 3/4 (70)</td> </tr> <tr> <td>X MAX</td> <td>3 1/2 (89)</td> <td>3 1/2 (89)</td> </tr> </table> Specify Type, Size & Finish eg: F37NB F38CP SUFFIX -F37-F38	SUFFIX	-F37	-F38	B DIA	07 (180)	09 (230)	H	3 1/4 (83)	3 1/2 (89)	MIN	2 5/8 (67)	2 3/4 (70)	X MAX	3 1/2 (89)	3 1/2 (89)																								
X																																																	
MIN	MAX																																																
1 1/4 (32)	2 1/8 (54)																																																
SUFFIX	-F37	-F38																																															
B DIA	07 (180)	09 (230)																																															
H	3 1/4 (83)	3 1/2 (89)																																															
MIN	2 5/8 (67)	2 3/4 (70)																																															
X MAX	3 1/2 (89)	3 1/2 (89)																																															

REV.	DATE	DESCRIPTION	BY	CKD. BY		FIGURE NUMBER
						2010 SERIES OPTIONAL STRAINER HEADS
						1 of 2

NOTE: Dimensions shown in parenthesis are in millimeters.

SEE BACK SHEET

2010 SERIES OPTIONAL STRAINER HEADS	DRAWN BY: PJ	CHECKED BY: TD	APPROVED BY: TD	DATE: 5-17-85	SCALE NONE	SIZE A	DRAWING NUMBER PM0457 SH 2 of 2	H		SMITH® JAY R. SMITH MFG. CO. DIVISION OF SMITH INDUSTRIES, INC. POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com		MEMBER OF:  		LOCATION																																																																		
								OPTIONAL STRAINER HEADS																																																																								
								LOW DOME STRAINER		SOLID HINGED COVER		SPANNER WRENCH COVER																																																																				
								FUNCTION: Used in gutters and recessed areas where excessive debris build-up is expected. Dome insures drainage even when partly covered. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -GV) Sediment Bucket -B Vandal Proof Screws -U		FUNCTION: Used in areas where intermittent drain use is required. Solid cover prevents intrusion of chips, saw-dust, etc., which are swept up before cover is opened for washdown. The secondary strainer prevents debris from entering the waste line. MATERIALS: Cast Iron -CI Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -GV) Vandal Proof Screws -U		FUNCTION: Solid gas tight, vandal proof, threaded cover for areas where intermittent drain use is required. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -JV) Holes in Flange -SH Sediment Bucket -B Vandal Proof Screws -U																																																																				
								 <table><tr><td>B DIA</td><td>05 (125)</td><td>06 (150)</td><td>08 (205)</td></tr><tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/2 (64)</td></tr><tr><td>MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td></tr><tr><td>MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr></table>		B DIA	05 (125)	06 (150)	08 (205)	H	2 (51)	2 (51)	2 1/2 (64)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	 <table><tr><td>B DIA</td><td>05 (125)</td><td>06 (150)</td><td>07 (180)</td><td>08 (205)</td></tr><tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr><tr><td>X MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td></tr><tr><td>X MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr></table>		B DIA	05 (125)	06 (150)	07 (180)	08 (205)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	 <table><tr><td colspan="2">X</td></tr><tr><td>MIN</td><td>MAX</td></tr><tr><td>2 (51)</td><td>3 (76)</td></tr></table>		X		MIN	MAX	2 (51)	3 (76)																									
								B DIA	05 (125)	06 (150)	08 (205)																																																																					
								H	2 (51)	2 (51)	2 1/2 (64)																																																																					
								MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																																																					
								MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																																																					
								B DIA	05 (125)	06 (150)	07 (180)	08 (205)																																																																				
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)																																																																												
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																																																												
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																																																												
X																																																																																
MIN	MAX																																																																															
2 (51)	3 (76)																																																																															
SUFFIX -G Specify Type, Size & Finish eg: G08PB		SUFFIX -H Specify Type, Size & Finish eg: H05CP		SUFFIX -J Specify Type, Size & Finish eg: J06NB																																																																												
REINFORCED SQUARE STRAINER		RECTANGULAR STRAINER		ANGLE STRAINER																																																																												
FUNCTION: Used in finished floors where some light wheeled traffic is anticipated. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -KV) Sediment Bucket -B Vandal Proof Screws -U		FUNCTION: Used in finished floors where light wheeled loads and or heavy foot traffic are anticipated. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Sediment Bucket -B Vandal Proof Screws -U		FUNCTION: Shower room drain set at wall and floor junction. Vertical grate openings prevent drain stoppage should flat surface become covered. MATERIALS: Cast Iron -CI Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Vandal Proof Screws -U																																																																												
 <table><tr><td>B SQ</td><td>05 (125)</td><td>06 (150)</td><td>07 (180)</td><td>08 (205)</td></tr><tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr><tr><td>MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td></tr><tr><td>MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr></table>		B SQ	05 (125)	06 (150)	07 (180)	08 (205)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	 <table><tr><td>SUFFIX</td><td>L</td><td>M</td><td>N</td><td>P</td><td>R</td><td>T</td></tr><tr><td>B x B'</td><td>4 1/2 (115) x 8 (205)</td><td>4 (100) x 12 (305)</td><td>5 (125) x 9 (230)</td><td>5 (125) x 13 (330)</td><td>6 (150) x 10 (255)</td><td>5 (125) x 17 (430)</td></tr><tr><td>H</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 1/4 (57)</td><td>3 (76)</td><td>2 1/4 (57)</td><td>3 (76)</td></tr><tr><td>MIN</td><td>1 3/8 (35)</td><td>1 7/8 (48)</td><td>1 3/8 (35)</td><td>2 1/8 (54)</td><td>1 3/8 (35)</td><td>2 1/4 (57)</td></tr><tr><td>MAX</td><td>2 3/8 (60)</td><td>2 3/4 (70)</td><td>2 3/8 (60)</td><td>3 (76)</td><td>2 3/8 (60)</td><td>3 1/8 (79)</td></tr></table>		SUFFIX	L	M	N	P	R	T	B x B'	4 1/2 (115) x 8 (205)	4 (100) x 12 (305)	5 (125) x 9 (230)	5 (125) x 13 (330)	6 (150) x 10 (255)	5 (125) x 17 (430)	H	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	3 (76)	2 1/4 (57)	3 (76)	MIN	1 3/8 (35)	1 7/8 (48)	1 3/8 (35)	2 1/8 (54)	1 3/8 (35)	2 1/4 (57)	MAX	2 3/8 (60)	2 3/4 (70)	2 3/8 (60)	3 (76)	2 3/8 (60)	3 1/8 (79)	 <table><tr><td>SUFFIX</td><td>B</td><td>C</td><td>D</td><td>X</td></tr><tr><td></td><td></td><td></td><td></td><td>MIN MAX</td></tr><tr><td>-V</td><td>3 1/2 (89)</td><td>3 1/2 (89)</td><td>4 1/2 (115)</td><td>1 5/8 (41) 2 5/8 (67)</td></tr><tr><td>-W</td><td>6 3/4 (170)</td><td>6 3/4 (170)</td><td>6 1/2 (165)</td><td>1 5/8 (41) 2 5/8 (67)</td></tr></table>		SUFFIX	B	C	D	X					MIN MAX	-V	3 1/2 (89)	3 1/2 (89)	4 1/2 (115)	1 5/8 (41) 2 5/8 (67)	-W	6 3/4 (170)	6 3/4 (170)	6 1/2 (165)	1 5/8 (41) 2 5/8 (67)
B SQ	05 (125)	06 (150)	07 (180)	08 (205)																																																																												
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)																																																																												
MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																																																												
MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																																																												
SUFFIX	L	M	N	P	R	T																																																																										
B x B'	4 1/2 (115) x 8 (205)	4 (100) x 12 (305)	5 (125) x 9 (230)	5 (125) x 13 (330)	6 (150) x 10 (255)	5 (125) x 17 (430)																																																																										
H	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	3 (76)	2 1/4 (57)	3 (76)																																																																										
MIN	1 3/8 (35)	1 7/8 (48)	1 3/8 (35)	2 1/8 (54)	1 3/8 (35)	2 1/4 (57)																																																																										
MAX	2 3/8 (60)	2 3/4 (70)	2 3/8 (60)	3 (76)	2 3/8 (60)	3 1/8 (79)																																																																										
SUFFIX	B	C	D	X																																																																												
				MIN MAX																																																																												
-V	3 1/2 (89)	3 1/2 (89)	4 1/2 (115)	1 5/8 (41) 2 5/8 (67)																																																																												
-W	6 3/4 (170)	6 3/4 (170)	6 1/2 (165)	1 5/8 (41) 2 5/8 (67)																																																																												
SUFFIX -K Specify Type, Size & Finish eg: K07CP		SUFFIX -L-M-N-P-R-T Specify Type, Size & Finish eg: LNB		SUFFIX -V -W Specify Type, Size & Finish eg: VPB, WNB																																																																												
EXTENSION ADAPTOR		OVERFLOW WITH STANDPIPE		HEAVY DUTY ADJUSTABLE																																																																												
FUNCTION: Used when a strainer head must be raised to accommodate deeper floor fill. REGULARLY FURNISHED: Duco Cast Iron -CI MATERIALS: Cast Bronze -CB Galvanized Cast Iron -G NOTE: Extension can be stacked for increased maximum adjustment.		FUNCTION: Used as overflow drain in decorative pools, fish ponds or similar areas. Dome prevents floating objects from entering drain line.  <table><tr><td>SUFFIX</td><td>A</td><td>X</td></tr><tr><td>SIZE</td><td>MIN MAX</td><td>MIN MAX</td></tr><tr><td>-Y</td><td>2 (51) 3/4 (19)</td><td>2 1/8 (54)</td><td></td></tr><tr><td>-Z</td><td>3 (76) 3/4 (19)</td><td>2 1/8 (54)</td><td></td></tr></table>		SUFFIX	A	X	SIZE	MIN MAX	MIN MAX	-Y	2 (51) 3/4 (19)	2 1/8 (54)		-Z	3 (76) 3/4 (19)	2 1/8 (54)		 MATERIALS: Polished Bronze -PB Rough Bronze -RB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -69V) Sediment Bucket -B Vandal Proof Screws -U eg: A06NB-69																																																														
SUFFIX	A	X																																																																														
SIZE	MIN MAX	MIN MAX																																																																														
-Y	2 (51) 3/4 (19)	2 1/8 (54)																																																																														
-Z	3 (76) 3/4 (19)	2 1/8 (54)																																																																														
SUFFIX -X		SUFFIX -Y-Z Specify Type, Size & Finish eg: YCP, ZCP		SUFFIX -69																																																																												
 Fig. 3580		 Fig. 3581		 Fig. 3590		 Fig. 3591																																																																										
H G T E D		TBW CMD TBW EMB		BS BS BS		FIGURE NUMBER 2010 SERIES OPTIONAL STRAINER HEADS 2 of 2																																																																										
REV.		DATE		DESCRIPTION		BY		CKD. BY																																																																								

NOTE: Dimensions shown in parenthesis are in millimeters.