

### About The Mill-Rose Company

The Mill-Rose Company is the largest U.S. manufacturer of twisted-in-wire brushes used in virtually every type of industry throughout the world. Mill-Rose is a multi-division, family-owned organization now in its fourth generation that takes pride in its history of serving satisfied customers. Our company-wide philosophy has always been "The customer is king" and we believe knowledge, integrity and trust are the cornerstone on which solid relationships are built. Mill-Rose knows about solid relationships, having served many of its customers over the past 100 years!

Mill-Rose experienced significant growth from its humble beginnings in 1919, and today operates manufacturing and warehouse facilities throughout the United States and Mexico. A 64,000 square foot production facility in Mentor, Ohio and 33,000 square foot production facility in Mexico feature the latest in manufacturing techniques and quality-control programs. Production was recently complemented by a new 70,000 square foot U.S. distribution center with state-of-the-art inventory management and distribution.

Mill-Rose is uniquely suited to manufacture brushes as tiny as .018" in diameter up to 15" wire wheel brushes using a diverse range of metals and natural or synthetic fibers for bristle material. Production runs vary from high-volume standard or custom orders, to small-volume specialty orders. Styles and types of brushes include, but are not limited to, twisted-in-wire, strip brushes, staple set, end, cup, wheel, drawn and more. Mill-Rose manufactures well over 100,000 standard and not-so-standard items.

### **About Clean-Fit Products**

Strong demand for Mill-Rose brushes by the plumbing, heating and cooling industry led to the formation of Clean-Fit Products, a fast-growing division serving professional contractors through wholesalers and Do-It-Yourself home centers. While Clean-Fit Products' principle product line is brushes, the division offers thousands of complementary products including a complete line of abrasives, PTFE thread sealants and specialty tools. Several years ago a brand by the name of Blue Monster® was developed offering PHC contractors high-end, time saving products. A Blue Monster trade character was specially developed to help market the brand which continues to grow at a rapid pace. The Blue Monster brand is widely recognized by the trades for quality and reliability.

### About Mill-Rose Laboratories

Mill-Rose Laboratories manufactures a complete line of disposable and reusable cytology brushes, snares, baskets and related products for the Gastrointestinal and Pulminary areas of medicine. Mill-Rose Laboratories is the leading source for biopsy/micro brushes and stainless steel wire forms used in a broad range of medical products. On any given day, Mill-Rose engineers are working with medical personnel from around the world developing new proprietary items that help properly diagnose and lead to life-saving treatments.







Clean-Fit Products' manufacturing and distribution facility in Mentor, Ohio





#### **Ordering Procedure**

The Mill-Rose Company has an extensive network of local distributors throughout the country to assist with product recommendations and support. To place an order, contact a distributor in your area or call **Customer Service at 800.321.3598** for the distributor nearest you. For custom-designed brushes, contact our engineering department at 800.321.3533.

### **Warranty**

Mill-Rose Company warrants all Clean-Fit products to be free from defects in material and workmanship. Mill-Rose's liability is limited to replacing any product proven defective, when returned prepaid to our factory. Returns must be authorized prior to shipment. No other warranty is expressed or implied. Mill-Rose neither assumes nor authorizes any person to assume any liability in connection with the sale of its products.

# Contents



2
8
8

2

11

15

20



**PTFE Thread Compounds & Tapes** 

Stainless Steel Thread Sealing Tape, Nickel-Guard, Copper-filled & Copper Guard Tape, Copper and Nickel Anti-Seize Lubrucants



3-Wrap Full-Density Teflon® Tapes, Packing and Pipe Thread Sealants and Cord Packing

Fitting & Tube Brushes Plumbing, Refrigeration, Power-Deuce, 4-in-1 and 6-in-1 Tools, Power Tube Brushes, Fitting Brushes, O.D. Tube Brushes and Kits

> Abrasive Products Sandcloth, Open Mesh, Grit Pads and Mini-Strips

- Condenser Tube & Heat Exchanger Brushes 18 Brushes, Extension Rods and Accessories
  - Flue & Boiler Tube Brushes
- Boiler, Burner, Radiator, Specialty and Heavy-Duty Brushes, Soot Saw
  - Chimney & Flue Cleaning Brushes 24 Target Products, Brushes, Handles, Extensions
    - 28

### Maintenance and Applicator Brushes

Parts Brushes, Platers Brushes, Scratch Brushes, Scrub Brushes, Whisk Brushes and Brooms, Bowl Brushes, Deck Scrub Brushes, Acid/Flux/Dope Brushes, Chip/Paint Brushes



## 4-in-1/6-in-1 Screwdrivers: Slot/Phillips, Offsets, Power Nut Drivers/Bits, Deburring Tool, Ringcrusher,

76-In-1 Screwarivers: Slot/Hnillips, Uttsets, Power Nut Drivers/Bits, Deburring 1001, Ringcrusher, Razorback Wrench, Tube Cutters, Pipe and Hack Saws, Stackable Utility Cases



### Hand Tools, Heat Shielding Products and Flame Blankets 38

Quick-Release Pliers, Plumber's Third Hand, Torch-Guard, The Insurance Pad, Blankets and Curtains, etc.



# MR MILE SE

### **PTFE Tapes & Thread Sealants**

### Blue Monster® PTFE Thread Seal Tape - Mini-Monster Contractor Grade

Rugged, general purpose tape in a monstrous 1429" roll! Ideal for hundreds of applications.

Blue Monster is a higher-quality PTFE sealing tape that is easier to apply. Blue Monster has not been stretched during the manufacturing process, so it is thicker and creates a more effective seal with less tape, and no need for pipe dope. Use Blue Monster on threads made from galvanized steel, iron brass copper aluminum stainless steel u

iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS, fiberglass and more.

### **Specifications:**

Composition:	99.6% PTFE < 0.4% Pigment
Color:	Blue
Thickness:	0.0035" +/-10% (0.0889 mm +/-10%)
Density:	0.8g/cm <sup>3</sup>
Elongation:	100%
PSI rating:	10,000 PSI (69,000 kPa) water and oil
Temperature range:	-450°F to +500°F (-268°C to +260°C) PTFE is completely
stable up to $\pm 500^{\circ}$ E o	$r \pm 260^{\circ}$ C. Decomposition is slow up to $\pm 750^{\circ}$ E or $\pm 400^{\circ}$ C.

stable up to  $+500^{\circ}$ F or  $+260^{\circ}$ C. Decomposition is slow up to  $+750^{\circ}$ F or  $+400^{\circ}$ C. Decomposition will occur on contact with naked flames.

Tensile strength: 115N/mm<sup>2</sup>

### Blue Monster® Gas Guard PTFE Thread Seal Tape

Monstrous 1000" roll! Color coded yellow for easy identification by gas companies worldwide.

Blue Monster Gas Guard PTFE thread sealing tape is designed specifically for gas lines. This is a full or maximum-density thread sealing tape. Blue Monster Gas Guard tape is approved by relevant authorities and used by the gas industry world-wide. It's color-coded



yellow so fitters and inspectors can easily recognize it as an approved tape. Ideally suited for natural gas, propane and butane lines. Use on threads of approved gas piping systems. Do not use Blue Monster Gas Guard Thread Seal Tape on oxygen systems.

> Blue Monster Gas Guard PTFE Thread Seal Tape is available in an attractive point-of-sale shelf and counter display.



Cat #	Description	Std. Pkg.	Master Pkg.	Wgt./Pkg.
70659	1/4" x 520"	10	100	0.5 lbs.
70660	1/2" x 260"	144	720	5.5 lbs.
70661	1/2" x 520"	144	720	7.5 lbs.
70662	3/4" x 260"	100	500	5.0 lbs.
70663	3/4" x 520"	100	500	7.0 lbs.
70664	1" x 260"	120	600	8.0 lbs.
70665	1" x 520"	120	600	11.0 lbs.
70885	1/2" x 1429"	45	270	5.5 lbs.
70886	3/4" x 1429"	27	162	5.0 lbs.
70887	1" x 1429"	27	162	5.75 lbs.
70888	2" x 1429"	27	162	11.40 lbs.



Blue Monster PTFE Thread Seal Tape is available in a point-of-sale shelf and counter display.



Cat #	Description	Std. PKg.	Master Pkg.	Wgt./Pkg.
70826	1/2" x 1000"	30	180	4.0 lbs.
70827	3/4" x 1000"	24	144	5.0 lbs.
Specific	cations:			(JL)

Composition:	99.0% PTFE <1.0% Pigment
Color:	Yellow
Thickness:	0.004" +/-10% (0.102mm +/-10%)
Density:	1.5g/cm <sup>3</sup> +/-10%
Elongation:	>100%
Tomporatura rongo	• 400°E to 1 500°E ( 260°C to 1 260°C) DT

**Temperature range:** -400°F to +500°F (-268°C to + 260°C) PTFE is completely stable up to +500°F or +260°C. Decomposition is slow up to 750°F or 400°C. Decomposition will occur on contact with naked flames. **Tensile strength:** 10-17 N/mm<sup>2</sup>

Certified to comply with the provisions of MilSpec T-27730A, UL-listed, CSA approved



### 3-Wrap Yellow Gas Thread Seal Tape

Just 3 wraps is all you need for leak-proof joints.

Mill-Rose 3-Wrap Yellow Gas Seal Tape is a PTFE thread sealing tape designed





Will-Rose 3-wrap yellow gas seal tape is approved by relevant authorities and used by the gas industry world-wide. It's color-coded yellow so fitters and inspectors can

easily recognize it as an approved tape. Applications: Ideally suited for natural gas, propane and butane lines.

Use on pipe made from galvanized steel, iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS and fiberglass. Do not use Gas Thread Seal Tape on oxygen systems.

Certified to comply with the provisions of MilSpec T-27730A, UL-listed, CSA approved.

Reference Mill-Rose specification sheet for additional uses and applications.



Mill-Rose Full-Density Green Thread Seal Tape is over five times heavier than common sealing tapes so you can use it and never worry about contaminating systems. Because it is degreased; it has no residual lubricant, unlike common tapes made with petroleum as a lubricant. Specifically developed for oxygen installations, Green thread seal tape is both safe and reliable to use;

seal tape is both safe and reliable to use; it is chemically inert and won't support combustion.

Applications: Oxygen lines, systems and other flammable environments. Also may be used on most liquid, oil and chemical installations.

Oxygen sealant tape is a degreased version of Gas Seal Tape. Meets MilSpec T-27730A (A-A58092) and has the approval of most gas companies: AIRCO (USA), British Oxygen Co. (UK), CANOX (Canada), Commonwealth Ind. Gases (Aus.) and Air Liquid (France).

Reference Mill-Rose specification sheet for additional uses and applications.



### **PTFE Tapes & Thread Sealants**

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70820	1/2" x 260" Rolls	10	.4 lbs.
70830	3/4" x 260" Rolls	8	.3 lbs.
70840	1" x 260" Rolls	6	.3 lbs.

#### Display Packaging - 3-Wrap Yellow Gas Line Tape

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70821	1/2" x 260" Carded	10	.60 lbs.
70822	1/2" x 260" 40 Pk. Counter Disp.	1	2.1 lbs.
70823	3/4" x 260" 24 Pk. Counter Disp.	1	1.5 lbs.
70824	1" x 260" 24 Pk. Counter Disp.	1	2.0 lbs.
70825	1/2" x 260" 10 Pk. Dispenser	1	.60 lbs.
70835	3/4" x 260" 6 Pk. Dispenser	1	.71 lbs.
70845	1" x 260" 6 Pk. Display	1	.89 lbs.

### **Specifications:**

Composition:	99.0% PTFE <1.0% Pigment
Color:	Yellow
Thickness:	0.004" +/-10% (0.102mm +/-10%)
Density:	1.5g/cm <sup>3</sup> +/-10%
Elongation:	>100%
Duccessure wetting.	In tasta conducted by an independe

**Pressure rating:** In tests conducted by an independent laboratory Mill-Rose 3-Wrap Yellow Gas Seal Tape was found to seal fittings carrying natural gas at pressures up to 4,347 PSI or 30,000kPa when applied as per instructions. Note: Pressure ratings are relative to the quality and torque of the fittings and the amount of tape used.

**Temperature range:** -400°F to +500°F (-268°C to + 260°C) PTFE is completely stable up to +500°F or +260°C. Decomposition is slow up to 750°F or 400°C. Decomposition will occur on contact with naked flames. **Tensile strength:** 10-17 N/mm<sup>2</sup>

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70850	1/2" x 260" Rolls	10	.40 lbs.
70852	3/4" x 260" Rolls	8	.30 lbs.
70854	1" x 260" Rolls	6	.50 lbs.

### **Display Packaging - Green PTFE Thread Seal Tape**

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70861	1/2" x 260" 10 Pk. Dispenser	1	.60 lbs.
70862	3/4" x 260" 6 Pk. Dispenser	1	.71 lbs.
70863	1" x 260" 6 Pk. Dispenser	1	.89 lbs.
70865	Wire Rack Display	1	.25 lbs.
70805	wire Rack Display	I	.25 IDS.

### **Specifications:**

Composition:	99.6% PTFE <0.4% pigment
Color:	Green
Thickness:	0.0045" +/-10% (.0115mm +/-10%)
Density:	1.5g/cm <sup>3</sup> +/-10%
Elongation:	>100%

**Pressure rating:** Mill-Rose Green Oxygen Tape has been used regularly on oxygen fittings at pressures up to 2,173.9PSI or 15,000kPa. Note: Pressure ratings are relative to the quality and torque of the fittings and the amount of tape used.

**Temperature range:**  $-450^{\circ}$ F to  $+500^{\circ}$ F ( $-268^{\circ}$ C to  $+260^{\circ}$ C) PTFE is completely stable up to  $+500^{\circ}$ F or  $+260^{\circ}$ C. Decomposition is slow up to  $750^{\circ}$ F or  $+400^{\circ}$ C. Although decomposition will occur on contact with naked flames.

**Tensile strength:** 9-13N/mm<sup>2</sup>





Listed 31R0

# MR THE FLOSE

### **PTFE Tapes & Thread Sealants**

### **3-Wrap Red Waterline Tape**

Just 3 wraps is all you need for leak-proof joints.

Mill-Rose 3-Wrap Red Thread Sealing Tape is a PTFE tape designed specifically to seal lines carrying steam, water and other liquids. This is a full or maximum-density tape. Unlike most thread sealing tapes on the market, 3-Wrap tape has not been stretched during the



manufacturing process. Stretching lowers the apparent density of tape by increasing its porosity. As stretched tape is more porous, more tape is required to obtain an effective seal.

Applications: Use 3-Wrap Red Waterline Tape on pipe made from galvanized steel, iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS and fiberglass.



*3-Wrap* Red Waterline Tape is available in self-dispensing wall and counter displays, or carded for pegboard display.



(ŴĽ

### **Specifications:**

Composition: Color: Thickness: 99.0% PTFE <1.0% Pigment Listed 31R0 Pink 0.004" +/-10% (0.102mm +/-10%)

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70189	1/4" x 520" Rolls	10	.14 lbs.
70796	1/2" x 260" Rolls	10	.14 lbs.
70797	1/2" x 540" Rolls	10	.3 lbs.
70798	3/4" x 260" Rolls	8	.18 lbs.
70801	3/4" x 540" Rolls	8	.35 lbs.
70799	1" x 260" Rolls	6	.44 lbs.
70874	1" x 540" Rolls	6	.88 lbs.

### Display Packaging - 3-Wrap Red Waterline Tape

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70875	1/2" x 260" 40 Pk. Counter Disp.	1	2.0 lbs.
70876	3/4" x 260" 24 Pk. Counter Disp.	1	1.4 lbs.
70877	1" x 260" 24 Pk. Counter Disp.	1	1.4 lbs.
70878	1/2" x 260" 10 Pk. Dispenser	1	.5 lbs.
70879	3/4" x 260" 6 Pk. Dispenser	1	.6 lbs.
70881	1" x 260" 6 Pk. Dispenser	1	.6 lbs.

 Density:
 1.5g/cm<sup>3</sup> +/-10%

 Elongation:
 >100%

**Pressure rating:** In tests conducted by an independent laboratory Mill-Rose 3-Wrap Red Waterline Seal Tape was found to seal fittings carrying water at pressures up to 4,347 PSI or 30,000kPa when applied as per instructions. Note: Pressure ratings are relative to the quality and torque of the fittings and the amount of tape used.

### Blue Monster Silver-Seal PTFE Thread Seal Tape

Blends with high-end finishes including chrome, stainless steel and nickel for dependable, leak-proof joints..



Blue Monster® Silver-Seal Tape creates dependable,

leak-free joints on plumbing fixtures made with chrome, stainless steel and nickel finishes. The silver color of this professional-grade tape blends with high-end finishes minimizing any

exposure. Unsightly thread seal tape previously exposed on high-end fixtures, cheapening their appearance, is a thing of the past. Best of all, contractors can rely upon the sealing quality of Blue Monster Silver-Seal tape; it's thicker and creates a more effective seal with less tape.

### **Specifications:**

Composition:	99.6% PTFE < 0.4% Pigment
Color:	Silver
Thickness:	0.0035" +/-10% (0.0889 mm +/-10%)
Density:	0.8g/cm <sup>3</sup>
Elongation:	100%
PSI rating:	10,000 PSI (69,000 kPa) water and oil



**Temperature range:**  $-450^{\circ}$ F to  $+500^{\circ}$ F ( $-268^{\circ}$ C to  $+260^{\circ}$ C) PTFE is completely stable up to  $+500^{\circ}$ F or  $+260^{\circ}$ C. Decomposition is slow up to  $+750^{\circ}$ F or  $+400^{\circ}$ C. Decomposition will occur on contact with naked flames.

Tensile strength: 115N/mm<sup>2</sup>

Build sales at the pointof-purchase with this Blue Monster Silver-Seal PTFE Thread Seal Tape shelf/ counter display.





### Medium Density PTFE Thread Sealant Tape

Mill-Rose medium-density PTFE thread sealing tape designed for a broad range of applications.

Just 3 wraps is all you need for dependable, leak-proof joints on lines carrying steam, water and other liquids. This tape is also compatible with most gases, but for gas lines, Mill-Rose 3-Wrap Yellow Gas Seal Tape is recommended.



### **Specifications:**

Composition:	100% pure virgin PTFE
Color:	White
Thickness:	0.0025" +/-10% (0.0635mm +/-10%)
Density:	0.7g/cm <sup>3</sup> +/-10%

### **PTFE Tapes & Thread Sealants**

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70988	1/2" x 260"	144	5 lbs.
70989	1/2" x 520"	144	6 lbs.
70990	1/2" x 1296"	144	11 lbs.
70991	3/4" x 260"	144	7 lbs.
70992	3/4" x 520"	144	9 lbs.
70993	3/4" x 1296"	144	16 lbs.
70994	1" x 260"	144	10 lbs.
70995	1" x 520"	144	12 lbs.
70996	1" x 1296"	144	22 lbs.

Elongation: >50%

PSI rating: 10,000 PSI (69,000 kPa) water and oil

**Temperature range:** -450°F to +500°F (-268°C to +288°C) PTFE is completely stable up to +500°F or +288°C. Decomposition is slow up to 750°F or +400°C. Decomposition will occur on contact with naked flames. **Tensile strength:** 1000 PSI

### Standard Quality White Thread Sealant Tape

Just because it is white, do not confuse Mill-Rose Better Quality PTFE Sealant Tape with the cheaper, stretched white tape currently on the market as a commodity. Unlike those stringy, flimsy tapes, that are stretched razor thin before you get them, Mill-Rose Standard Quality Thread Seal Tape is sixteen percent (16%) thicker and certified to comply with the provisions of MilSpec MIL-T-27730A.

#### **Specifications:**

Composition:	100% virgin PTFE
Color:	White
Thickness:	.003 +/- 10%
Density:	0.6g/cm <sup>3</sup> +/- 10%
Elongation:	More than 50%
PSI rating:	3000 PSI (68.95 mPn)
Temperature range	:-450°F to +500°F (-268°C to +260°C)
Combustion:	Does not support combustion
Shelf Life:	Indefinite

Cat #	Description	Std. Pkg.	Master Pkg.	Wgt./Pkg.
70193	1/2" x 100"	10	1000	.07 lbs.
70190	1/2" x 260"	10	1000	.17 lbs.
70200	1/2" x 520"	10	1000	.34 lbs.
70202	1/2" x 1,296"	50	520	4.24 lbs.
70195	3/4" x 260"	8	800	.15 lbs.
70196	3/4" x 520"	8	800	.30 lbs.
70806	3/4" x 1296"	50	336	5.64 lbs.
70203	1" x 260"	6	600	.16 lbs.
70209	1" x 520"	6	600	.32 lbs.
70807	1" x 1296	50	336	6.75 lbs.

#### Display Packaging - White PTFE Thread Seal Tape

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70204	1/2" x 100" - 40 Pk.Counter Dspl	1	1.2 lbs.
70207	1/2" x 260" - 40 Pk.Counter Dspl	1	1.4 lbs.
70208	1/2" x 520" - 40 Pk.Counter Dspl	1	1.6 lbs.
70191	1/2" x 260" - Carded	10	.71 lbs.

### **PTFE Cord Packing**

This self-forming, self-lubricating, non-toxic cord packing is made of 100% pure PTFE. It is resistant to most liquids and gases. PH range from 0 to 14. Temperature range from -450°F to +450°F. PSI range is 1500 to 3000.

Typical applications include valve packing, rotating and reciprocating shafts, pump shafts and large-diameter thread sealing.



PTFE Cord Packing - Dispenser Pack					
Cat #	Size	Ft. per Pkg.	Std. Pkg.	Wgt./Pkg.	
70290	3/32"	40	1	1.00 lbs.	
70300	1/8"	30	1	1.00 lbs.	
70302	3/16"	16	1	1.00 lbs.	
70304	1/4"	10	1	1.00 lbs.	

### **PTFE Cord Packing - Display Handy Pack**

Cat #	Size	Ft. per Pkg.	Std. Pkg.	Wgt./Pkg.
70326	3/32"	4	5	.50
70306	1/8"	4	5	.50
70308	3/16"	4	5	.50
70310	1/4"	4	5	.50

# 

### **PTFE Tapes & Thread Sealants**

#### Blue Monster Industrial Grade Thread Sealant with PTFE

Formulated for extra lubrication on metal pipe threads, BLUE MONSTER Industrial Grade Thread Sealant with PTFE is a slow-drying, soft-setting, non-hardening pipe thread compound.

BLUE MONSTER has a high bulk density, which means there are more solids in the formulation. Recommended for on-site or assembly line

work. It is lead-free, non-toxic and will not harden or separate in the can.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76000	2 fl. oz. Squeeze Tube	24	4 lbs.
76001	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76003	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76005	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76017	1 quart / 32 fl. oz. / .95 liter	12	48 lbs.

#### Meets Mil. Spec. TT-S-1732

Temperature Range: -50°F (-45°C) to +400°F (204°C) Pressure ratings: Gases up to 3,000 PSI (211 kg/cm<sup>2</sup>)

ow/dwv/sv Standard 14 Standard 61 Liquids up to 10,000 PSI (703.1 kg/cm<sup>2</sup>)

Not recommended for use on oxygen systems. Use Clean-Fit 3-wrap Oxygen PTFE Tape.



NSE

#### Blue Monster Industrial Grade Thread Sealant

**BLUE MONSTER Industrial Grade Pipe** Thread Compound is a slow-drying, soft-setting, non-hardening pipe thread compound. Specially formulated with superb "sticking" characteristics, BLUE MONSTER applies evenly and quickly threads. Recommended for on-site or assembly line work, BLUE MONSTER is lead-free, non-toxic and will not harden or separate in the can.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76007	2 fl. oz. Squeeze Tube	24	4 lbs.
76009	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76011	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76015	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76019	1 quart / 32 fl. oz. / .95 liter	12	48 lbs.

### Meets Mil. Spec. TT-S-1732

Temperature Range: -50°F (-45°C) to +400°F (204°C) Pressure ratings: Gases up to 3.000 PSI (211 kg/cm<sup>2</sup>) Liquids up to 6,000 PSI (422 kg/cm<sup>2</sup>)

Not recommended for use on oxygen systems. Use Clean-Fit 3-wrap Oxygen PTFE Tape.



### Blue Monster Stay-Soft Thread Sealant with PTFE

Specially formulated for residential and commercial fire sprinkler systems

Blue Monster Stay-Soft PTFE enriched pipe thread compound does not harden and allows for pre-fab application to threads weeks before system assembly and pressurization. Stay-Soft is non-seizing and allows for easy disassembly of any threaded connection years after assembly. Easy clean-up and indefinite shelf life.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76023	1/4 pint / 4 fl. oz. / 118 ml	24	18 lbs (8.2 kg)
76025	1/2 pint / 8 fl. oz. / 237 ml	24	26 lbs (11.8 kg)
76027	1 pint / 16 fl. oz. / 473 ml	12	25 lbs (11.3 kg)
76029	1 quart / 32 fl. oz. / .95 liter	12	50 lbs (22.7 kg)

Approved for use on all metal threaded connections, FlowGuard Gold®, Blazemaster®, and Corzan® pipe and fittings.



Meets Mil. Spec. TT-S-1732 Temperature range: -15°F (-20°C) to +400°F (204°C) Gases up to 5,000 PSI (351.5 kg/cm<sup>2</sup>) Pressure ratings: Liquids up to 10,000 PSI (703.1 kg/cm<sup>2</sup>)



### Stainless Steel Pipe Thread Sealing Tape

Mill-Rose Stainless Steel Thread Sealing PTFE Tape is a unique thread sealing tape which prevents stainless steel fittings from galling or seizing during assembly and disassembly. The tape is thicker and denser than most tapes. The added thickness and density ensures an effective seal up to 12,000 PSI. Do not use on Oxygen systems - See Green Oxygen Tape in this section.





Applications: Stainless steel pipe systems, including joints and connections, bolts, nuts, valves, flanges, studs, threaded fittings, bushings, plugs and assemblies. Also used for protection from corrosion, seizing, galling, rust carbon fusion and galvanized pitting.

### Blue Monster® Nickel Guard® Anti-Seize Thread Seal Tape

### Easy assembly and disassembly of threaded components

- 10% Nickel Flake Content
- A clean and efficient alternative to anti-seize compounts
- A nickel impregnated PTFE thread sealing tape designed for stainless steel fittings
- Anti-seize assistance up to 2,651°F (1,455°C)

A unique thread sealing tape that prevents stainless steel fittings from galling or seizing during assembly and disassembly. This tape is impregnated with nickel powder which acts like bearing plates, keeping the surface of the male/female threads apart. Further protection is provided with this thicker and denser tape that ensures an effective seal. Blue Monster® Nickel Guard® Anti-Seize Thread Sealing Tape is recommended for stainless steel pipe and fittings but it is compatible with a wide range

### Copper-Filled PTFE Tape for Anti-Seize Thread Sealing

A clean copper based, high-temperature, anti-seize material for protection from corrosion, seizure, galling, rust carbon fusion, galvanic pitting. The copper acts like ball bearings. This tape maintains its elasticity where temperatures reach as high as 500°F-direct flame. Meets UL requirements for seal tests.

Applications: Bolts, studs, threaded fittings and couplings, valve shafts, cylinder heads, manifolds and any other connection in a hostile environment (boilers, ovens, exhaust manifolds, hot water storage tanks, pumps, burner assemblies, turbo charger fittings, etc.)

Do not use on oxygen systems.



### Anti-Seize Lubricants & Tapes

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70891	1/2" x 260" Rolls	10	.41 lbs.
70892	3/4" x 260" Rolls	8	.51 lbs.
70893	1" x 260" Rolls	6	.82 lbs.

### **Specifications:**

Composition:	90% PTFE/10% nickel
Color:	Silver
Thickness:	0.0045" +/-10% (0.115mm +/-10%)
Density:	1.6g/cm <sup>3</sup> +/-10%
Elongation:	50%

Temperature range:  $-450^{\circ}$ F to  $+500^{\circ}$ F ( $-268^{\circ}$ C to  $+260^{\circ}$ C) PTFE iscompletely stable up to  $+500^{\circ}$ F or  $+260^{\circ}$ C. Decomposition is slow up to $750^{\circ}$ F or  $+400^{\circ}$ C. Decomposition will occur on contact with naked flames.Tensile strength: $10-12N/mm^2$ 

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70894	1/2" x 600"	10	1.14 lbs.
70895	3/4" x 600"	8	1 lb.

of piping materials for use with a wide range of gases and liquids. Additional features include no curing time, effective across a broad range of temperatures, and it's non-toxic and non-flammable.

### **Specifications:**

90% PTFE / 10% nickel
Silver
0.0045" +/- 10% (0.115mm +/-10%)
1.6g/cm <sup>3</sup> +/- 10%
50%

**Temperature range:**  $-450^{\circ}$ F to  $+500^{\circ}$ F ( $-268^{\circ}$ C to  $+260^{\circ}$ C) PTFE is completely stable up to  $+500^{\circ}$  F or  $+260^{\circ}$  C. Decomposition will occur on contact with naked flames. Upon decomposiiton, the remaining copper powder will assist disassembly. Nickel flake will melt at 2,651°F or 1,455°C.

Tensile strength: 10-12N/mm<sup>2</sup>

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70800	1/2" x 120" Rolls	10	.22 lbs.
70811	1/2" x 600" Rolls	10	1.14 lbs.
70805	3/4" x 120" Rolls	8	.44 lbs.

### **Specifications:**

Composition:	90% PTFE/ 10% Copper
Color:	Copper
Thickness:	0.0045" +/-10% (0.115mm +/-10%)
Density:	1.5g/cm3 +/-10%
Elongation:	>100%

**Temperature range:** The tape is completely thermally stable at temperatures between -450°F to +500°F (-268°C to +260°C) PTFE in the tape will slowly decompose up to 750°F or 400°C. Decomposition will occur on contact with naked flames. Upon decomposition, the remaining copper powder will assist disassembly. The copper flake will melt at 1981°F or 1083°C

Tensile strength: 9-13N/mm<sup>2</sup>

Reference Mill-Rose specification sheet for additional uses & applications.

The Mill-Rose Co. | Clean-Fit Products | 800.321.3598 | info@cleanfit.com | cleanfit.com

# MR MILE SE

### Anti-Seize Lubricants & Tapes

### Blue Monster<sup>®</sup> Copper Guard<sup>®</sup> Anti-Seize Thread Seal Tape Easy assembly and disassembly of threaded components

- 10% Copper Flake Content
- A clean and efficient alternative to anti-seize compounts
- A copper impregnated PTFE thread sealing tape
- Anti-seize assistance up to 1,984°F (1,084°C)



Designed to permit the easy assembly and disassembly of threaded components. It takes the place of messy and potentially contaminating anti-seize compounds. Blue Monster® Copper Guard® Anti-Seize Tape is manufactured from a copper filled PTFE resin that provides excellent lubricity and helps prevent galling during assembly and disassembly of components. When wrapped around a thread, Mill-Rose Blue Monster® Copper Guard® Anti-Seize Tape seals it from corrosive substances or any dirt or grit likely to cause seizure. Apply to any threaded component made from galvanized steel, steel, iron, brass, copper, aluminum, titanium and magnesium. It is not recommended for stainless steel.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70811	1/2" x 600"	10	1.14 lbs.
70812	3/4" x 600"	8	1 lb.

### **Specifications:**

Composition:	90% PTFE / 10% copper
Color:	Copper
Thickness:	0.0045" +/- 10% (0.115mm +/-10%)
Density:	1.6g/cm <sup>3</sup> +/- 10%
Elongation:	50%

**Temperature range:**  $-450^{\circ}$ F to  $+500^{\circ}$ F ( $-268^{\circ}$ C to  $+260^{\circ}$ C) PTFE is completely stable up to  $+500^{\circ}$  F or  $+260^{\circ}$  C. Decomposition will occur on contact with naked flames. Upon decomposiiton, the remaining copper powder will assist disassembly. Copper flake will melt at 1,984°F or 1,084°C.

Tensile strength: 10-12N/mm<sup>2</sup>

### Blue Monster® Copper Anti-Seize Lubricant

Copper anti-seize lubricant for use on all metal pipe and fittings.

Mill-Rose Blue Monster Copper Anti-Seize is a specially formulated copper-based lubricant for high temperature up to 1800°F (982°C) and high pressure environments. Blue Monster Copper Anti-Seize lubricant will not bleed, separate, or settle. Prevents pressure leakage and seizing resulting from high

temperature, freezing, heavy loads, corrosion, and vibration.

### Blue Monster<sup>®</sup> Nickel Anti-Seize Lubricant

Pure nickel anti-seize compound for use on stainless steel pipe and fittings.

Blue Monster Nickel Anti-Seize is an extreme service anti-seize lubricant for use in a high temperature environment (up to 2600°F /1427°C). For use in applications where copper, lead, moly-disulfide, chlorides, and fluorides cannot be tolerated. Blue Monster Nickel Anti-Seize lubricant is chemically inert and can be

used with most chemicals that are unstable with copper-type compounds. Provides excellent resistance to chemical oxidation and/or corrosion. Prevents rusting, seizing, welding, or galling. Not for use on potable water systems.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
76024	10 oz. / .625 lb. / 283 g	12	9.5 lbs.
76026	16 oz. / 1 lb. / 454 g	12	15.2 lbs.

• Copper anti-seize lubricant for use on all metal pipe and fittings.

 Temperature Range Use: Gases: -0°F (-17°C) to 1800°F (982°C) Liquids: -0°F (-17°C) to 1800°F (982°C) Brushable to: 10°F (-12°C) Pour Point: 32°F (0°C)

Cat #	Description	Std. Pkg.	Wgt./Pkg.
76020	1/2 pint / 8 fl. oz. / 237 ml	12	10 lbs.
76022	1 pint / 16 fl. oz. / 473 ml	12	19 lbs.

• High teperature lubricant for use on stainless steel, PVC, CPVC, nylon, polypropylene, plastics and all metals.

 Temperature Range Use: Gases: -0°F (-17°C) to 2600°F (1427°C) Liquids: -0°F (-17°C) to 2600°F (1427°C) Brushable to: 10°F (-12°C) Pour Point: 32°F (0°C)





**NSF** 

pw/dwv/sw Standard 14

Standard 61

## **Solvent Weld Cements & Specialty Chemicals**

### Blue Monster 1-Step Weatherproof PVC Cement Blue and Clear Formulas

Self-priming PVC glue simplifies installations

Blue Monster 1-Step PVC cement is a self-priming PVC pipe glue that requires no additional primer. Blue Monster's STEP CONTRACTOR STEP 

1-step joining process simplifies installations by reducing labor and offers faster curing times before pressure testing. Ideal for under-the-sink jobs and home remodels. Use on all classes of rigid and flexible PVC pressure

pipe, including Sch. 80, up to 6" in diameter and 8" diameter on nonpressure rigid and flexible PVC pipe.



Cat #	Description	Std. Pkg.	Wgt./Pkg.	
Blue PVC	Cement			
76030	1/4 pint / 4 fl. oz. / 118 ml	24	10 lbs.	
76032	1/2 pint / 8 fl. oz. / 237 ml	24	16 lbs.	
76034	1 pint / 16 fl. oz. / 473 ml	12	15 lbs.	
76036	1 quart / 32 fl. oz. / .95 liter	12	28 lbs.	
<b>Clear PV</b>	Clear PVC Cement			
76031	1/4 pint / 4 fl. oz. / 118 ml	24	10 lbs.	
76033	1/2 pint / 8 fl. oz. / 237 ml	24	16 lbs.	
76035	1 pint / 16 fl. oz. / 473 ml	12	15 lbs.	
76037	1 quart / 32 fl. oz. / .95 liter	12	28 lbs.	
			$\frown$	

### Medium Body - Low VOC

Blue Monster 1-Step PVC cement emits less than 510 grams per liter VOC when tested according to SCAQMD method 316 A.

\*Use without primer where acceptable by local code.

### Blue Monster® Drain Banger

Professional strength, odorless drain opener

Blue Monster Drain Banger devours hair, grease, soap and oils that slow and plug drain lines in less than 60 seconds! Blue Monster Drain Banger is a hot water activated non-acid drain cleaner designed to be used by professional contractors only. It is odorless and will not harm plumbing fixtures, porcelain or septic systems.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76055	1 lb. (453 g)	24	26 lbs
76057	2 lbs. (907 g)	12	26 lbs
76059	6 lbs. (2722 g)	4	24 lbs

• Devours hair, grease, soap, oils and other organic materials that slow and plug drain lines in less than 60 seconds!

- For professional contractors only!
- Non-acid.

### Blue Monster<sup>®</sup> Microbubble Gas Leak Detector

Detects even the smallest of leaks

Blue Monster<sup>®</sup> Microbubble leak detector is a sensitive solution formulated to detect even the smallest of leaks in air and gas lines, tanks, cylinders, valves, fittings, pipelines, and other suspect areas. Blue Monster's dependable formula provides long lasting leak detection up to 10 minutes after application. Ideal for identifying leaks in refrigeration and air conditioning systems, this easy-touse leak detector is equally effective on natural gas, propane, butane, air, nitrogen, chlorine, CO2, and most other gases. Not for use on oxygen systems.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
71023	1/2 pint / 8 fl. oz. / 236 ml	24	16 lbs.
71025	1 pint / 16 fl. oz. / 473 ml	12	15 lbs.
71027	1 quart / 32 fl. oz. / 936 ml	12	31 lbs.
71029	1 gallon / 3.75 liters	4	37 lbs.

- Non-freezing formula usable from -10°F (-23°C) to 215 (101°C).
- Will not cause corrosion or deterioration of metal or plastic piping systems.
- Ideal for testing pressure less than 1psi.

# 

### Solvent Weld Cements & Specialty Chemicals

### Blue Monster Heavy-Duty Citrus Scrubbing Towels

Clean hands, tools, equipment, and hard surface areas with these convenient scrubbing towels.

BLUE MONSTER scrubbing towels are pre-moistened, heavy-duty cleaning towels dispensed from a handy, flip-top container. They are saturated with a safe, effective cleaning solution combined with a tough, dual-textured towel to loosen, dissolve and absorb dirt and grease leaving your hands clean. One side is rough for scrubbing and the other side is smooth. These towels require no water and leave hands feeling conditioned and clean with no left-over residue.



### Blue Monster<sup>®</sup> Compression Seal Tape

Stops problem leaks under pressure without turning off the water source!

Blue Monster® Compression Seal Tape features selffusing layers that form a waterproof compression seal. Seal leaks while under pressure - up to 150 PSI on any type of rigid piping material, from galvanized and cast iron to copper and all types of plastics and rubber.

Blue Monster Compression Seal Tape contains no adhesive and is ideal for crisis and long-term applications. This tape seals by compression, so pulling the tape as tight as possible forms a chemical reaction that fuses the layers of tape into a mass of silicone.





Cat #	Description	Std. Pkg.	Master Pkg.	Wgt./Pkg.
76084	1" x 12" Strip Pack (3 Strips	s) 20	40	3.5 lbs.
76085	1" x 12-foot Rolls	10	40	3.5 lbs.
76086	2" x 12-foot Rolls	6	24	4.0 lbs.

### Specifications:



-900°C to +260°C / -130° to 500°F continous

Standard requirement: "Tape shall not unwind more than 1.0 inch after 3 minutes with an attached load of 600g. Result: <1 inch

~ 1200 PSI throughout temperature range

Acid/Alkaline/Chlorine: No negative effect from brief exposure to acids, alkaline or chlorine and can withstand submersion

> ASTM D2240, D2240, A-A-59163, ASTM D-149, MIL-I-46852, ASTM D2148, ASTM D3767 Blue Monster Compression Seal Tape specifications meet other international standards not included in this list.

UL standard 94 rating V-0. Tested to IEEE 383 and IEEE 1202 for flammability, self-extinguishes and will not propagate a flame.

### All Purpose Lubricating Oil with Zoom Spout

The highest guality turbine lubricating oil! Ideal for use on industrial equipment, electric motors from 1/3HP to 5HP, shop tools, bearings, shafts and virtually all mechanical linkages. Available in a 4 ounce container with the patented Zoom Spout.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70704	Lubricating Oil with Zoom Spou	ıt 12	4.0 lbs.



## Blue Monster Heavy-Duty, Professional PLUMBING/REFRIGERATION Brushes

Blue Monster heavy-duty plumbing and refrigeration brushes set the industry's standard for quality. Features include heavy-gauge galvanized stem wire and double stem, doublespiral construction for long-lasting performance. The 6300 Heavy-Duty Plumbing brush features oil-tempered straight high-carbon fill wire. The 6400 Heavy-Duty Refrigeration brush features rust proof, spring-tempered straight stainless steel fill wire.



### Fitting & Tube Brushes

Carbon Steel		Stainless Steel			
Plumbing	(I.D.)	Refrig.	(O.D.)	Std. Pkg.	Wgt./Pkg.
63005	1/8"	64005	1/4"	1	13 lbs.
63015	1/4"	64020	3/8"	1	.13 lbs.
63025	3/8"	64030	1/2"	1	.13 lbs.
63035	1/2"	64040	5/8'	1	.18 lbs.
63050	5/8"	64050	3/4"	1	.18 lbs.
63060	3/4"	64060	7/8"	1	.18 lbs.
63075	7/8"	64070	1"	1	.18 lbs.
63085	1"	64080	1-1/8"	1	.18 lbs.
63095	1-1/4	" 64090	1-1/4"	1	.25 lbs.
63105	1-1/2	" 64100	1-3/8"	1	.25 lbs.
63115	2"	64115	1-1/2"	1	.25 lbs.
		64125	1-5/8"	1	.25 lbs.
		64135	2-1/8"	1	.25 lbs.
		64145	2-1/2"	1	.25 lbs.

### #6700 Heavy-Duty, Professional Fitting Brush, PLUMBING/REFRIGERATION

# 3/4 MILL-ROSE

- The 6700 Heavy-Duty (Professional).
- Next best brush available to the 6300 and 6400 series.
- Heavy gauge galvanized stem wire.
- Double stem, single spiral construction.
- Rust proof, spring-tempered crimped stainless steel fill wire.
- Brushes clearly marked with actual (0.D.) and nominal (I.D.) sizes.
- Standard packages include UPC.

Cat #	(I.D.)	(0.D.)	Std. Pkg.	Wgt./Pkg.
67005	1/8"	1/4"	12	1.5 lbs.
67010	1/4"	3/8"	12	1.5 lbs.
67015	3/8"	1/2"	12	1.5 lbs.
67020	1/2"	5/8"	12	2.2 lbs.
67025	5/8"	3/4"	12	2.2 lbs.
67030	3/4"	7/8"	10	1.8 lbs.
67035	7/8"	1"	10	1.8 lbs.
67040	1"	1-1/8"	8	1.4 lbs.
67045	1-1/4"	1-3/8"	6	1.5 lbs.
67050	1-1/2"	1-5/8"	6	1.5 lbs.
67055	2"	2-1/8"	6	1.5 lbs.

### Standard PLUMBING and REFRIGERATION Fitting Brush



Mill-Rose standard plumbing and refrigeration brushes are the first choice in price and quality. Features include heavy-gauge galvanized stem wire and single stem, single-spiral construction. Brushes are clearly marked with actual (0.D.) and nominal (I.D.) sizes.

The 6100 plumbing brush features crimped high-carbon fill wire.

The 9400 refrigeration brush features rust proof, crimped stainless steel fill wire.

Carbon		Stainless			
Steel	<b>(1 D</b> )	Steel	(0 D)		
Plumbing	(I.D.)	Refrig.	(0.D.)	Std. Pkg.	Wgt./Pkg.
61000	1/8"	94000	1/4"	12	1.2 lbs.
61070	1/4"	94010	3/8"	12	1.2 lbs.
61150	3/8"	94020	1/2"	12	1.2 lbs.
61210	1/2"	94030	5/8"	12	1.2 lbs.
61270	5/8"	94040	3/4"	12	1.2 lbs.
61330	3/4"	94050	7/8"	12	1.2 lbs.
61390	7/8"	94060	1"	12	1.2 lbs.
61450	1"	94070	1-1/8"	12	1.2 lbs.
61500	1-1/4"	94080	1-3/8"	8	1.0 lbs.
61560	1-1/2"	94085	1-1/2"	6	.8 lbs.
61620	2"	94090	1-5/8"	6	.8 lbs.
		94100	2-1/8"	6	.8 lbs.
		94105	2-1/2"	6	.8 lbs.
61211	1/2"			10 carded	1.3 lbs.
61321	3/4"			10 carded	1.3 lbs.
61451	1"			10 carded	1.3 lbs.

### #6100 Hard-Head Fitting Brush, PLUMBING



#### The 6100 Hard-Head fitting brush.

- Same as 6100 series brush with a protective galvanized end plate.
- Prevents damage to valve seats and seals.
- Extends brush life.
- Prevents misuse in undersized fittings.

Cat #	(I.D.)	Std. Pkg.	Wgt./Pkg.
61102	3/8"	12	1.3 lbs.
61212	1/2"	12	1.3 lbs.
61332	3/4"	12	1.3 lbs.
61453	1"	10	1.1 lbs.
61502	1-1/4"	10	1.1 lbs.
61562	1-1/2"	6	1.0 lbs.
61622	2"	4	1.7 lbs.

# R Eiting & Tubo Brushos

## Fitting & Tube Brushes

### All Stainless Steel "Quick Twist" & "Quick Twist Plus" Brush, PLUMBING/REFRIGERATION



#### Quick Twist Brush.

- Only all stainless steel brush on the market.
- Spark proof brush.Meets Mil and/or ASTM specs.
- Each brush individually labeled with UPC.
- Available up to 4" diameter.

#### Quick Twist Plus<sup>®</sup>.

• Same as 6800 series brush with non-slip plastisol comfort grip.

Quick	(	Quick Twis	t		
Twist	(I.D.)	Plus	(0.D.)	Std. Pkg.	Wgt./Pkg
68005	1/8"	68001	1/4"	12	.35 lbs.
68015	1/4"	68011	3/8"	12	.40 lbs.
68025	3/8"	68021	1/2"	12	.55 lbs.
68035	1/2"	68031	5/8"	12	.70 lbs.
68045	5/8"	68041	3/4"	12	.80 lbs.
68055	3/4"	68051	7/8"	12	.85 lbs.
68065	7/8"	68061	1"	12	.90 lbs.
68075	1"	68071	1-1/8"	12	1.10 lbs.
68085	1-1/4"	68081	1-3/8"	8	.80 lbs.
68095	1-1/2"	68091	1-5/8"	6	.75 lbs.
68105	2"	68101	2-1/8"	6	1.15 lbs.
68120	2-1/2"	68121	2-5/8"	1	.25 lbs.
68130*	3"		3-1/8"	1	.30 lbs.
68140*	4"		4-3/16"	1	.30 lbs.

\*T-handle construction for easy use.

### Standard & Soft Twist Fitting, PLUMBING/REFRIGERATION



#### The 9600 standard fitting brush

- Best choice for economy and comfort.
- Single stem, single spiral construction.
- Rust proof crimped stainless steel fill wire.

#### Soft Twist fitting brushes.

 Same as 9600 series brush with brightly colored non-slip plastisol comfort grip.

Standard	(I.D.)	Soft Twist	(0.D.)	Std. Pkg	.Wgt./Pkg.
96000	1/8"	96001	1/4"	12	.35 lbs.
96010	1/4"	96011	3/8"	12	.40 lbs.
96020	3/8"	96021	1/2"	12	.60 lbs.
96030	1/2"	96031	5/8"	12	.75 lbs.
96040	5/8"	96041	3/4"	12	.80 lbs.
96050	3/4"	96051	7/8"	12	.80 lbs.
96060	7/8"	96061	1"	12	.80 lbs.
96070	1"	96071	1-1/8'	' 12	.85 lbs.
96080	1-1/4	" <b>96081</b>	1-3/8'	' 8	.60 lbs.
96090	1-1/2	" <b>96091</b>	1-5/8'	' 6	.60 lbs.
96100	2"	96101	2-1/8'	' 6	.70 lbs.
96105	2-1/8	"   96106	2-1/4'	' 6	.70 lbs.
96110	2-3/8	" <b>96111</b>	2-1/2'	' 6	.75 lbs.

### Blue Monster Power Deuce Brushing Tool Two Brushes in One!

Multi-function brush cleans fittings and tubing for stronger joints.

The Power-Deuce is a multifunction brushing tool that prepares the inside of copper fittings and outside of copper tubing without having to change tools. The Power-Deuce is a selfcleaning brush with rust-proof, stainless steel bristles for plumbing and HVAC projects. A heavy-duty ABS housing is impact resistant and protects bristles so they retain their shape and prolongs brush life.



Cat #	Description	Std. Pkg.	Wgt./Pkg.		
12-Pack	12-Pack Counter/Shelf Display				
62820	1/2 I.D. (5/8" O.D.)	12	2.0 lbs.		
62830	3/4" I.D. (7/8" O.D.)	12	2.4 lbs.		
62840	1" I.D. (1-1/8" O.D.)	12	3.0 lbs.		
Power Pa	ick with Quik Change C	huck Adapter			
62850	1/2 I.D. (5/8" O.D.) 3/4" I.D. (7/8" O.D.)	6	1.2 lbs.		
	1" I.D. (1-1/8" O.D.)				
Individua	Illy Packaged on Blister	Card			
62821	1/2 I.D. (5/8" O.D.)	12	2.0 lbs.		
62831	3/4" I.D. (7/8" O.D.)	12	2.4 lbs.		
62841	1" I.D. (1-1/8" O.D.)	12	3.0 lbs.		





### #6600 Series Hex Shank Power Fitting Brushes



Contact Customer Service for additional sizes. Call: 1-800-321-3598, Fax: (440) 255-1072 or e-mail: info@cleanfit.com.

### Pop Display - 1/4" Hex Shank Power Fitting Brush Carbon Steel - 1/2" and 3/4" Carded



Cat #	(I.D.)	Desc. St	d. Pkg.	Wgt./Pkg.
66510	1/2"	Power	10	.80 lbs.
	&	Fitting		
	3/4"	Brushes		

Mill-Rose 1/4" hex-shank power fitting brushes feature high carbon or stainless steel bristles that provide long brush life. These brushes are ideal for quick cleaning of fittings, tubing, drill holes, as well as deburring soft steel, stainless steel, brass, copper, aluminum, plastic

and other materials. These brushes

strength and longer wear under the rigors of power drills and presses.

have been beefed up to provide greater

Single Stem Single Spiral

\*Note: Power brushes must be rotated in clockwise direction only.

Fitting	&	Tube	<b>Brushes</b>
---------	---	------	----------------

Carbon Steel	Stainless Steel				
Plumbing	Refrig.	(I.D.)	(O.D.)	Std. Pkg.	Wgt./Pkg.
Bulk					
66410	66435	1/4"	3/8"	12	.40 lbs.
66420	66455	3/8"	1/2"	12	.40 lbs.
66430	66475	1/2"	5/8"	12	.50 lbs.
66440	66480	5/8"	3/4"	12	.50 lbs.
66450	66490	3/4"	7/8"	12	.60 lbs.
66460	66495	7/8"	1"	12	.60 lbs.
66470	66500	1"	1 1/8"	12	.64 lbs.
66472	66512	1 1/4"	1 3/8"	6	.30 lbs.
66473	66515	1 3/8"	1 1/2"	6	.30 lbs.
66474	66520	1 1/2"	1 5/8"	6	.40 lbs.
66482	66525	2"	2 1/8"	6	.80 lbs.
66483	66530	2 1/2"	2 5/8"	1	.13 lbs.
66484	66535	3"	3 1/4"	1	.15 lbs.
66487	66540	4"	4 1/4"	1	.18 lbs.
POP Di	splay - 2	Per Bag			
66411	66436	1/4"	3/8"	5	.80 lbs.
66421	66456	3/8"	1/2"	5	.80 lbs.
66431	66476	1/2"	5/8"	5	.90 lbs.
66441	66481	5/8"	3/4"	5	.90 lbs.
66451	66491	3/4"	7/8"	5	.90 lbs.
66461	66496	7/8"	1"	5	1.00 lbs.
66471	66501	1"	1-1/8"	5	1.00 lbs.



#### Power Brush, Nutdriver and Screwdriver Kits

Two convenient kits contain everything needed to accessorize power drills to clean fittings and tubing fast! Each kit contains 1/4" hex shank power fitting and tube cleaning brushes in a range of sizes, plus magnetic power nut drivers and screwdriver bits. Mill-Rose power brushes are ideal for quick cleaning of fittings, tubing, drill holes, as well as deburring metal, plastic and other materials. These brushes are beefed up to withstand the rigors of power drills.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
72155	Plumbing K	it 6	9.0 lbs.
	1 - 62340	1 - 62350	1 - 62370
	1 - 62390	1 - 66420	1 - 66430
	2 - 66450	1 - 66470	1 - 72136
	1 - 72138	1 - 72100	1 - 72098
	1 - 72104	1 - 72106	
72156	Refrigeratio	on Kit 6	9.0 lbs.
	1 - 66455	1 - 66475	1 - 66480
	1 - 66490	1 - 66495	1 - 62340
	1 - 62350	1 - 62370	1 - 62390
	1 - 72138	1 - 72136	1 - 72098
	1 - 72100	1 - 72104	1 - 72106



#### #6200 Series Hand & Power Tube Cleaning Brushes

6200 Series Tube Cleaning Brush is the first high impact (ABS) plastic tube cleaning brush ever made. High carbon plated steel cleans and scores the outside diameter of tubing with minimal effort and makes for a better soldered joint. Available in plastic bags or carded for point-of-purchase display.

Cat #	(I.D.)	(O.D.)	Std. Pkg.	Wgt./Pkg.
62005	1/8"	1/4"	12	.80 lbs.
62020	1/4"	3/8"	12	.80 lbs.
62035	3/8"	1/2"	12	.80 lbs.
62050	1/2"	5/8"	12	.80 lbs.
62065	5/8"	3/4"	12	.80 lbs.
62080	3/4"	7/8"	12	.80 lbs.
62095	7/8"	1"	12	.40 lbs.
62110	1"	1-1/8'	' 12	.45 lbs.

# MR MERODE

### Fitting & Tube Brushes

### **O.D. Tube Cleaning Brush**



### #6200 Tube Cleaning Brush - Carded

Cat #	(I.D.)	(0.D.) Std	l. Pkg. V	/gt./Pkg.
62501	1/2"	5/8"	10	1.4 lbs.
62502	3/4"	7/8"	10	1.4 lbs.
62510	1	1-1/8"	10	1.4 lbs.

Mill-Rose power tube cleaning brushes make fast work of projects requiring a number of solder or brazed fittings. Tube cleaning brushes are available with 1/4" hex shanks for use with a Quik-Change Chuck Adapter or standard drill chucks. Power tube cleaning brushes are not available in sizes larger than 1" I.D. (1-1/8" 0.D.).

Four-in-One Brush
-------------------



Four-in-One Brush (PLUMBING) - Bag						
Cat #	Description Std. Pkg. Wgt./Pkg.					
70264	1/2" x 3/4" (ID)					
	4-in-1 Brush 12 3.50 lbs.					
70269	1/2" x 3/4" (ID)					
	Replacement Kit 6 .60 lbs.					
Four-in-	One Brush (PLUMBING) - Carded					
Cat #	Description Std. Pkg. Wgt./Pkg.					
70260	1/2" x 3/4" (ID)					
	4-in-1 Brush 10 2.90 lbs.					

The only contractor-grade tube cleaning and fitting brush on the market. It's made of high impact engineered plastic and designed for easy parts replacement. Ideal for every tool box. Available in high carbon steel for plumbing and stainless steel for refrigeration. Brushes are individually packaged in poly-bags or carded for point-of-purchase display. Replacement kits include I.D. and O.D. brushes and rubber backings. Screws not included.

#### Six-in-One Brush (PLUMBING) - Bag

Cat #	Description Std. Pkg. Wgt./Pkg.
70255	1/2" x 3/4" ID Brush/Deburrer 10 3.50 lbs.
70269	1/2" x 3/4" Replacement Kit 6  .60 lbs.
70271	Adapter Kit (Deburring plate) 6 .50 lbs.

Blue Monster Six-in-One Brush cleans the inside diameter of 1/2" and 3/4" fittings and outside diameter of 1/2" and 3/4" tubing. The deburing plate reams and deburs the I.D. of tubing, has a b-tank gas key (square opening on plate), and also serves as a bottle opener.

#### #6200 Tube Cleaning Brush - Bag

				9
Cat #	(I.D.)	(0.D.) Sta	l. Pkg.	Wgt./Pkg.
62500	3/8"	1/2"	6	.50 lbs.
62505	1/2"	5/8"	6	.50 lbs.
62506	3/4"	7/8"	6	.50 lbs.
62503	1"	1-1/8"	6	.55 lbs.

### #6200 Power Tube Cleaning Brush - Bag

Cat #	(I.D.)	(0.D.)	Std. Pkg.	Wgt./Pkg.
62330	1/4"	3/8"	5	1.2 lbs.
62340	3/8"	1/2"	5	1.3 lbs.
62350	1/2"	5/8"	5	1.3 lbs.
62360	5/8"	3/4"	5	1.3 lbs.
62370	3/4"	7/8"	5	1.3 lbs.
62380	7/8"	1"	5	1.3 lbs.
62390	1"	1-1/8"	5	1.3 lbs.

#### Four-in-One Brush (REFRIGERATION) - Bag

Cat #	Description	Std. Pkg.	Wgt./Pkg.	
70258	3/8" x 1/2" 0 4-in-1 Brush	-	3.50 lbs.	
70259	3/8" x 1/2" Replacement	t Kit 6	.60 lbs.	
70284	3/8" x 3/4" C 4-in-1 Brush	-	3.50 lbs.	
70285	3/8" x 3/4" Replacemen	t Kit 6	.60 lbs.	
70265	3/4" x 1/2" 0 4-in-1 Brush	-	3.50 lbs.	
70262	3/4" x 1/2" Replacemen	t Kit 6	.60 lbs.	
70268	5/8" x 7/8" C 4-in-1 Brush	-	3.50 lbs.	
70263	5/8" x 7/8" Replacemen	t Kit 6	.60 lbs.	

### Six-in-One Brush (REFRIGERATION) - Bag

Cat #	Description S	td. F	'kg.	Wgt./Pkg.
70270	5/8" x 7/8" ID Brush/Deburi		8	3.50 lbs.
70263	5/8" x 7/8" Replacement	Kit	6	.60 lbs.
70271	Adapter Kit (Deburring pl	ate)	6	.50 lbs.

Available in high carbon steel for plumbing and stainless steel for refrigeration.

The Six-in-One brushing/deburring tool is available in poly-bags with attractive, three-color display packaging for point-ofpurchase display.



### **Abrasive Products**

### Nylon Abrasive Grit Hand Pads

Clean-Fit Hand Pads are offered with different grit sizes for a broad range of applications including heavy-duty cleaning, finishing and light polishing. These pads are very durable and waterproof, so they can be used wet or dry. They will not rust and are an excellent alternative to steel wool.

**Maroon Hand Pad, Aluminum Oxide Fine -** Commercial-quality hand pad for aggressive cleaning and deburring. Ideal for general cleaning where a fast initial cut is desired. Made from non-woven nylon webbing impregnated with a very fine grit abrasive. This pad is stronger, more resilient and resists tearing or snagging. Easily washed or rinsed, can be used wet or dry. These pads are "solvent resistant." Ideal for cleaning copper tubing before brazing. Catalog #70198.

**Black Hand Pad, Silicon Carbide Fine** - Extremely resilient and conformable to irregular surfaces. Ideal for general purpose applications, including removing rust and oxidation from metals, blending around solder joints, cleaning molds and satin-finish aluminum. Completely waterproof. Catalog #70186..



#### Maroon General-Purpose Pad, -Aluminum Oxide Very Fine

A heavy backing provides aggressive cutting action and long life. Coated surface is an economical alternative to our fine-quality pad. Ideal for satin finishing, stainless steel finishes, scuffing surfaces prior to applying adhesives, and removing rust, corrosion and oxides. Completely waterproof. Catalog #70199..

Cat #	Description	Color	Grit	Std. Pkg.	Wgt./Pkg.
70198	4" x 6" Nylon Abrasive Pads - 10/Display Carton	Maroon	Fine	6	.43 lbs.
70199	4" x 6" Nylon Abrasive Pads - 10/Display Carton	Maroon	Very Fine	6	.43 lbs.
70186	2" x 6" Nylon Abrasive Pads - 2/Card - Carded	Black	Fine	10	.10 lbs.

### **Blue Monster Contractor Grade Abrasives**

## 2" Width – 33% wider than traditional plumbers' rolls and 100% waterproof.

Blue Monster premium open mesh and Ultra-Flex<sup>®</sup> abrasive cloth are revolutionary, high-performance abrasives that are tough! Blue Monster outlasts all others in the most demanding conditions, wet or dry. Blue Monster's wide design provides more surface-to-surface coverage making it easier and faster to prep large-diameter tube and fittings.



- 21 x 21 Mesh Has larger holes than other open mesh products. This feature prevents "loading" and allows contractors to rinse the mesh clean. Resists clogging even when used on softer materials.
- Premium blended 165 grit white Aluminum Oxide cuts and scores surfaces faster for more effective cleaning and deburring.

Cat #	Description	Std. Pkg.	Wgt./Pkg.						
Blue Mo	Blue Monster Open Mesh								
70151	2" x 8" mini strips (10)	12	1.70 lbs.						
70152	2" x 5 yard roll	12	7.00 lbs.						
70154	2" x 10 yard roll	12	11.00 lbs.						
70156	2" x 25 yard roll	12	22.00 lbs.						
Blue Mo	onster Ultra-Flex								
70171	2" x 8" mini strips (10)	12	1.85 lbs						
70172	2" x 5 yard roll	12	5.00 lbs.						
70174	2" x 10 yard roll	12	9.00 lbs.						
70176	2" x 25 yard roll	12	20.00 lbs.						



- Super flexible Ultra-Flex<sup>®</sup> backing conforms to tight work areas and Blue Monster will not crack or tear during use.
- Premium 150 grit cuts and scores surfaces faster for more effective cleaning and deburring.

# MR MEROSE

Cat #

70092

70102

70113

Description

1-1/2" x 5 Yards

1-1/2" x 10 Yards

1-1/2" x 25 Yards

plastic pipe prior to adhesion, etc. 100% waterproof.

### **Abrasive Products**

### Aluminum Oxide Open Mesh - 180 Grit



Cat #	Description	Grit Size	Std. Pkg.	Wgt./Pkg.
70090 70100	1-1/2" x 5 Yds. 1-1/2" x 10 Yds.	180 A0 / 24 180 A0 / 24	24 24	8.0 lbs. 14.0 lbs.
70110	1-1/2" x 25 Yds.	180 A0 / 24	20	30.0 lbs.

Mill-Rose original Aluminum Oxide mesh for copper tube cleaning. A fully waterproof product made with open nylon fabric, Phenolic resin adhesive, which makes it waterproof, and rugged aluminum oxide. Coated on both sides of the nylon fabric to produce a long-lasting sharp cutting product. If this material becomes coated (loaded) with copper, brass or other non-ferrous or plastic residue, simply rinse in water or tap against a hard surface to clean.

Grit Size

180 SC / 18

180 SC / 18

180 SC / 18

Designed to provide an alternative to Aluminum Oxide Open Nylon Mesh. We have opened up the mesh to reduce loading and replaced Aluminum Oxide

with Silicon Carbide. Silicon carbide mesh is sharper and tends to cut faster

and produce finer scratch patterns on most surfaces. Black Open Mesh can be used on a wide variety of surfaces and materials. These include ferrous and nonferrous metals, ceramics, plastics, fiberglass, plywood and others. Applications include deburring, cleaning, scouring, blending, polishing, deflashing plaster, dulling laminates, removing oxides and rust, scuffing

Std. Pka.

24

24

20

Wgt./Pkg.

8.0 lbs.

14.0 lbs.

30.0 lbs.

### Silicon Carbide Open Nylon Mesh - 180 Grit



#### Aluminum Oxide "Wet One" - 120 Grit



#### Cat # Grit Size Std. Pkg. Wgt./Pkg. Description 70161 1-1/2" x 2 Yds. Carded 120-J 10 .6 lbs. 1-1/2" x 5 Yds. 1-1/2" x 2 Yds. <u>Boxed</u> 70162 8.0 lbs. 120-J 24 70163 120-J 20 2.6 lbs. 70164 1-1/2" x 10 Yds. 120-J 14.0 lbs. 24 1-1/2" x 25 Yds. 20 70166 120-J 30.0 lbs.

The **"Wet One"** is an Aluminum Oxide 100% waterproof sand cloth - ideal for tough deburring, cleaning and polishing plumbing tubing, fittings and parts exposed to water. Our bonding system provides exceptional grain retention and durability under the most severe conditions.

### Aluminum Oxide "Red Stuff" - 120 Grit



Cat #	Description	Grit Size	Std. Pkg.	Wgt./Pkg.
70045	1-1/2" x 5 Yards	120-J	24	8.0 lbs.
70050	1-1/2" x 10 Yards	120-J	24	14.0 lbs.
70060	1-1/2" x 25 Yards	120-J	20	30.0 lbs.

**Red Stuff** is our best quality Closed Coat abrasive cloth with a "J" weight cotton backing. Features a full Aluminum Oxide coating for increased cutting power, water and weather-resistant bond for consistently strong solder joints. The original copper tubing cleaner.



### **Abrasive Products**

Aluminum Oxide "Yellow Stuff" - 120 Grit



Cat #	Description	Grit Size	Std. Pkg.	Wgt./Pkg.
70068	1-1/2" x 5 Yards	120-J	24	8.0 lbs.
70070	1-1/2" x 10 Yards	120-J	24	14.0 lbs.
70080	1-1/2" x 25 Yards	120-J	20	30.0 lbs.

Yellow Stuff is our best quality Open Coat abrasive cloth with a "J" weight cotton backing. This premium water-resistant abrasive cloth is designed to clean soft metals. The open coat scores better than closed coat cloth as there is no glaze coating over the aluminum oxide. Widely used by the air conditioning/refrigeration trade.

### Aluminum Oxide "Brown Stuff" - 120 Grit



Cat #	Description	Grit Size	Std. Pkg.	Wgt./Pkg.
70125	1-1/2" x 5 Yards	120-J	24	8.0 lbs.
70130	1-1/2" x 10 Yards	120-J	24	14.0 lbs.
70140	1-1/2" x 25 Yards	120-J	20	30.0 lbs.
70150	1-1/2" x 50 Yards	120-J	10	30.0 lbs.

**Brown Stuff** is a good quality Closed Coat abrasive cloth on a "J" weight cotton backing. Brown in color, water-resistant bonding and flexible backing provides a durable, efficient abrasive for long life. Almost as good as the "Red Stuff".

### Aluminum Oxide - 120 Grit Economy



Cat #	Description	Grit Size	Std. Pkg.	Wgt./Pkg.
70175	1-1/2" x 5 Yards	120-J	24	8.0 lbs.
70170 70180	1-1/2" x 10 Yards 1-1/2" x 25 Yards	120-J 120-J	24 20	14.0 lbs. 30.0 lbs.

Good, economy-grade Closed Coat abrasive cloth, "J" weight cotton cloth. Our resin bonding of the grit still gives you a water resistant cloth when price may be your principal factor.

# MR MILEROSE

### **Condenser Tube & Heat Exchanger Brushes**



Mill-Rose offers a complete line of condenser tube and heat exchanger brushes. Available in four bristle materials: High Carbon Steel, Stainless Steel, Brass and Nylon. Bristle sizes are graduated from .008" on small diameter brushes, to .010" on larger sizes to provide consistent cleaning power.

The 1/4" diameter brushes are mounted on a 3/16" diameter coupling with a 8-32 external thread. The #75110 extension rod kit has 30" of 3/16" diameter self-connecting rods with an 8-32 internal thread.

All brushes from 3/8" diameter to 3" have a 11/32" diameter coupling with a 5/16-18 internal thread and 1/8" NPT outside. There is no 0.D. thread on 3/8" brushes. Shank length is 2". Adapters are also available to accommodate other standard thread sizes.



Individually boxed with UPC and sizes clearly indicated.

#### 1/4" Condenser Tube Brushes with 8/32 Threaded Female Coupling and Extension Rod Kit

	Catalog N	umber		Brush	Brush	Overall	Wire	Standard	Weight/
H/C Steel	Stainless	Bronze	Nylon	Diameter	Length	Length	Size	Pack	Package
65500	65502	65504	65506	1/4"	2-1/4"	3-1/4"	.006	6	.06 lbs.
75110	Extension	Rod Kit for 1/4	" Condenser Bru	shes - 30" in lenat	th - includes han	dle and fitting to	couple 3/16"	rod 1	.32 lbs.

#### 3/8" to 3" Condenser Tube Brushes - 1/8 NPT Outside - 5/16-18 Internal Thread

H/C Steel	Catalog N Stainless	umber Bronze	Brush Nylon	Brush Diameter	Overall Length	Wire Length	Standard Size	Weight/ Pack	Package
65020	65135	65250	65365	+3/8"	4-1/2"	7-1/2"	.008	1	.14 lbs.
65025	65140	65255	65370	7/16"	4-1/2"	7-1/2"	.008	1	.14 lbs.
65030	65145	65260	65375	1/2"	4-1/2"	7-1/2"	.008	1	.14 lbs.
65035	65150	65265	65380	9/16"	4-1/2"	7-1/2"	.008	1	.15 lbs.
65040	65155	65270	65385	5/8"	4-1/2"	7-1/2"	.008	1	.15 lbs.
65045	65160	65275	65390	11/16"	4-1/2"	7-1/2"	.008	1	.16 lbs.
65050	65165	65280	65395	3/4"	4-1/2"	7-1/2"	.008	1	.16 lbs.
65055	65170	65285	65400	13/16"	4-1/2"	7-1/2"	.008	1	.17 lbs.
65060	65175	65290	65405	7/8"	4-1/2"	7-1/2"	.010	1	.17 lbs.
65065	65180	65295	65410	15/16"	4-1/2"	7-1/2"	.010	1	.18 lbs.
65070	65185	65300	65415	1"	4-1/2"	7-1/2"	.010	1	.20 lbs.
65075	65190	65305	65420	1-1/8"	4-1/2"	7-1/2"	.010	1	.20 lbs.
65080	65195	65310	65425	1-1/4"	4-1/2"	7-1/2"	.010	1	.22 lbs.
65085	65200	65315	65430	1-3/8"	4-1/2"	7-1/2"	.010	1	.23 lbs.
65090	65205	65320	65435	1-1/2"	4-1/2"	7-1/2"	.010	1	.24 lbs.
65095	65210	65325	65440	1-5/8"	4-1/2"	7-1/2"	.010	1	.25 lbs.
65100	65215	65330	65445	1-3/4"	4-1/2"	7-1/2"	.010	i	.28 lbs.
65105	65220	65335	65450	1-7/8"	4-1/2"	7-1/2"	.010	i	.28 lbs.
65110	65225	65340	65455	2"	4-1/2"	7-1/2"	.010	i	.30 lbs.
65115	65230	65345	65460	2-1/4"	4-1/2"	7-1/2"	.010	1	.32 lbs.
	CEODE	65050	CE ACE	0 1/0"	4 1/0"	7 1/0"	010	4	
65120	65235	65350 65255	65465 65470	2-1/2"	4-1/2"	7-1/2"	.010	1	.34 lbs.
65125	65240 65245	65355	65470 65475	2-3/4"	4-1/2"	7-1/2"	.010	1	.36 lbs.
65130	65245	65360	65475	3"	4-1/2"	7-1/2"	.010	I	.40 lbs.

\*No 0.D. Thread on 3/8" brushes.

18

A-5227 adapter converts brush threads to 1/4" NPT

### **Condenser Tube & Heat Exchanger Brushes**





Cat #	Description	Std. Pkg.	Wgt./Pkg.					
Extension	Extension Rods							
65000	3' Fiberglass extension rod 5/16-18 1/8 NPT with "T" handle	6	1.6 lbs.					
65002	3' Steel extension rod, 5/16" dia.	6	6.0 lbs.					
65010	2' Fiberglass ext. rod 5/16-18 1/8" N	PT 6	1.0 lbs.					
65015	3' Fiberglass ext. rod 5/16-18 1/8" N	PT 6	1.25 lbs.					
65018	3' Fiberglass ext. rod w/T-handle (6/F	°k 1	1.71 lbs.					
65016	4' Fiberglass ext. rod 5/16-18 1/8" N	PT 6	1.5 lbs.					
65017	6' Fiberglass ext. rod 5/16-18 1/8" N	PT 6	1.9 lbs.					
Accessor	ies							
65001	"T" handle for fiberglass extension re	od 6	.4 lbs.					
65006	"T" handle for steel extension rod	6	.4 lbs.					
Tube Cro	ssover Adapters							
65003	M/R brush adapter to comp. rod (5/16-18 male brush to 12-24 female	6 rod)	.3 lbs.					
65004	M/R rod adapter to comp. brush (12-24 male brush to 5/16-18 female	6 rod)	.3 lbs.					
65007	M/R brush adapter to power condenser cleaning machine	6	1.0 lbs.					

\*65003 and 65004 - adapt to Schaefer brush (12-24)



Cat #	Description	Std. Pkg.	Wgt./Pkg.
73610	6-3/4" Fin & Coil Whisk	12	.8 lbs.
73620	Fin Comb Scraping Tool (Adjustable	) 12	1.5 lbs.

Fin comb cleans air conditioner fins and restores bent fins to normal position. Small whisk type brush features stiff polypropylene bristles firmly imbedded in plastic handle. Ideal for cleaning in between small fins and coils. Display packaged with UPC clearly indicated.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
01390	5/8" - 1-5/8" Tapered Diameter, Horsehair, 32" OAL, Wood Handle, Display Package	12	3.60 lbs.
01392	5/8" - 1-5/8" Tapered Diameter, Horsehair, 29" OAL, Plastic Handle, Coated Stem, Display Package	12	3.24 lbs.
01394	3/4" - 1-5/8" Double Stepped Diamete Synthetic 26" OAL, Wood Handle, Display Package	er, 12	4.80 lbs.
84377	3/4" - 1-3/4" Tapered Diameter, Synthetic 30" OAL, Plastic Handle, Display Package	12	3.30 lbs.

# 

### Flue & Boiler Tube Brushes

8300 / 8400 Series Flue & Boiler Tube Brushes Black Oil Tempered Wire - 1/4" NPT



Quality flue and boiler tube brushes designed and engineered from durable black oil-tempered wire. Available in two standard constructions: single spiral #8300 Series and double-spiral #8400 Series. Brushes have an overall length of 8" and brush length of 4-1/2". Individually packaged with unit size and UPC.

\*\* 1/8" NPT

8400 Series Flue & Boiler Tube Brushes Fiber Fill - 1/4" NPT



Single Spiral	Double Spiral	Brush Dia.	Flue Dia.	Brush Length	Overall Length	Std. Pack	Wgt./ Pkg.
**83002	84002	1/2"	3/4"	4-1/2"	8"	1	1.2 lbs.
**83003	84003	5/8"	7/8"	4-1/2"	8"	1	1.3 lbs.
83005	84005	3/4"	1"	4-1/2"	8"	1	1.5 lbs.
83010	84010	1"	1-1/4"	4-1/2"	8"	1	1.5 lbs.
83015	84015	1-1/4"	1-1/2"	4-1/2"	8"	1	1.5 lbs.
83020	84020	1-1/2"	1-3/4"	4-1/2"	8"	1	1.5 lbs.
83025	84025	1-3/4"	2"	4-1/2"	8"	1	1.5 lbs.
83030	84030	2"	2-1/4"	4-1/2"	8"	1	2.0 lbs.
83035	84035	2-1/4"	2-1/2"	4-1/2"	8"	1	2.0 lbs.
83040	84040	2-1/2"	2-3/4"	4-1/2"	8"	1	2.0 lbs.
83045	84045	2-3/4"	3"	4-1/2"	8"	1	2.5 lbs.
83050	84050	3"	3-1/4"	4-1/2"	8"	1	2.5 lbs.
83055	84055	3-1/4"	3-1/2"	4-1/2"	8"	1	3.0 lbs.
83060	84060	3-1/2"	3-3/4"	4-1/2"	8"	1	3.0 lbs.
83065	84065	3-3/4"	4"	4-1/2"	8"	1	3.2 lbs.
83070	84070	4"	4-1/4"	4-1/2"	8"	1	3.2 lbs.
83085	84090	5"	5-1/4"	4-1/2"	8"	1	3.2 lbs.
83100	84105	6"	6-1/4"	4-1/2"	8"	1	3.4 lbs.

Single	Brush	Flue	Brush	Overall	Std.	Wgt./
Spiral	Dia.	Dia.	Length	Length	Pack	Pkg.
84810	1"	1-1/4"	4-1/2"	8"	1	1.5 lbs.
84815	1-1/4"	1-1/2"	4-1/2"	8"	1	1.5 lbs.
84820	1-1/2"	1-3/4"	4-1/2"	8"	1	1.5 lbs.
84830	2"	2-1/4"	4-1/2"	8"	1	1.5 lbs.
84835	2-1/4"	2-1/2"	4-1/2"	8"	1	1.5 lbs.
84840	2-1/2"	2-3/4"	4-1/2"	8"	1	1.5 lbs.
84845	2-3/4"	3"	4-1/2"	8"	1	1.7 lbs.
84850	3"	3-1/4"	4-1/2"	8"	1	2.0 lbs.
84860	3-1/2"	3-3/4"	4-1/2"	8"	1	2.0 lbs.
84870	4"	4-1/4"	4-1/2"	8"	1	2.0 lbs.
84880	5"	5-1/4"	4-1/2"	8"	1	2.4 lbs.
84890	6"	6-1/4"	4-1/2"	8"	1	2.6 lbs.
84900	7"	7-1/4"	4 1/2"	8"	1	3.0 lbs.
84910	8"	8-1/4"	4 1/2"	8"	1	3.6 lbs.
84920	9"	9-1/4"	4 1/2"	8"	1	4.1 lbs.
84930	10"	10-1/4"	4 1/2"	8"	1	4.4 lbs.

8400 Series Heavy-Duty Cleaning Brushes	Cat #	Description	Std. Pkg.	Wgt./Pkg.
For Furnace Flues	84106	1-1/2" x 4" x 5" Dbl. Stem U-Shape Wire Flue Brush	6	2.9 lbs.
	84108	1-3/4" x 4" x 5-1/2" Dbl. Stem U-Shape Wire Flue Brush	6	3.8 lbs.
	84110	2" x 4-1/2" x 5" Dbl. Stem U-Shape Wire Flue Brush	6	5.0 lbs.
and the second s	84112	3-1/2" x 6" x 6-1/2" Dbl. Stem U-Shape Wire Flue Brush	6	6.0 lbs.
A AND	84032	2" x 4" x 4-1/2" Oval Shape Wire Flue Brush	6	5.0 lbs.
The second second	84034	2-1/2" x 4-1/2" x 4-1/2" Oval Shape Wire Flue Brush	6	6.0 lbs.
	84052	3" x 5" x 4-1/2" Oval Shape Wire Flue Brush	6	6.0 lbs.
#84106 #84026	84054	3" x 4" x 4-1/2" Dbl. Stem, Dbl. Spiral Oval Shape Wire Flue Brush	6	6.0 lbs.
U-Shaped	84008	3/8" x 1" Flat Fine Wire Baffle Brush 5/16-18 internal thread 1/8"N	PT 6	0.9 lbs.
Cleaning Brush	84026	1/2" x 2" Flat Fine Wire Baffle Brush	6	1.9 lbs.
-	84033	3/4" x 3" Flat Fine Wire Baffle Brush	6	2.3 lbs.
Multi-purpose brushes with 1/4" NPT Connectors.	84066	7/8" x 4" Flat Fine Wire Baffle Brush	6	2.7 lbs.

Multi-purpose brushes with 1/4" NPT Connectors.



Flexible, self-connecting twisted-in-wire or fiberglass extension rods with self-connecting 1/4" NPT nipples are available in three convenient lengths (3', 4', 6').

Cat #	Description	Length	Std. Pkg.	Wgt./Pkg.
30002	Fiberglass	3'	6	2.50 lbs.
30021	Fiberglass	4'	6	2.16 lbs.
30023	Fiberglass (24/Pack)	4'	1	10.40 lbs.
30061	Fiberglass	6'	6	3.00 lbs.
30007	Twisted Steel Rod	3'	6	4.60 lbs.
30031	Twisted Steel Rod	4'	6	4.90 lbs.
30064	Twisted Steel Rod	6'	4	7.90 lbs.
30003	Twisted Steel Rod	3'	6	4.30 lbs.
70766	with loop-end handle T-handle (4" x 2-1/2")		6	2.30 lbs.



### Flue & Boiler Tube Brushes



The Mill-Rose Company offers the most comprehensive line of boiler and flue brushes in the industry. These brushes are made in the U.S.A. with the highest quality materials and workmanship. Brushes presented here address cleaning all major boilers and other service needs.

For your convenience, these brushes are organized with

you in mind. First, determine the type of brush fill you need (fine wire, nylon, horsehair, etc.). Go to the appropriate listing and select the desired brush size (diameter and overall length). If you require a special brush not shown on the following pages, please contact Customer Service.

### Fine-Wire Single Spiral Brushes for Small Boilers, Burners, Nozzles & Fans

Brushes in the following categories have 3" brush part lengths and loop handles for easy hanging. All brushes have labels on handles with individual UPC identification.

Cat #	Description	Std. Pkg.	Wgt./Pkg.	Cat #	Description	Std. Pkg.	Wgt./Pkg.
01015	3/16" Dia., 7" OAL, Carbon Steel	12	.12 lbs.	01060	1/2" Dia., 8" OAL, Stainless Steel	12	.25 lbs.
01025 01190 01208 01256	1/4" Dia., 7" OAL, Carbon Steel 1/4" Dia., 16" OAL, Stainless Steel 1/4" Dia., 24" OAL, Stainless Steel 1/4" Dia., 36" OAL, Stainless Steel	12 12 12 12	.15 lbs. .50 lbs. .70 lbs. 1.00 lbs.	01065 01194 01212 01260 01286	1/2" Dia., 8" OAL, Carbon Steel 1/2" Dia., 18" OAL, Stainless Steel 1/2" Dia., 24" OAL, Stainless Steel 1/2" Dia., 36" OAL, Stainless Steel 1/2" Dia., 42" OAL Carbon Steel	12 12 12 12 6	.25 lbs 1.00 lbs. 1.40 lbs. 2.10 lbs. 2.40 lbs.
01045 01192 01210 01258	3/8" Dia., 8" OAL, Carbon Steel 3/8" Dia., 18" OAL, Stainless Steel 3/8" Dia., 24" OAL, Stainless Steel 3/8" Dia., 36" OAL, Stainless Steel	12 12 12 12	.25 lbs. .80 lbs. 1.10 lbs. 1.60 lbs.	01080 01157 01214 01262	5/8" Dia., 9" OAL, Carbon Steel 5/8" Dia., 16" OAL, Carbon Steel 5/8" Dia., 24" OAL, Stainless Steel 5/8" Dia., 36" OAL, Stainless Steel	12 12 12 12	.50 lbs. .90 lbs. 1.50 lbs. 2.20 lbs.

Dia. = Diameter OAL = Overall length

# M E C SE

### Flue & Boiler Tube Brushes

### Fine-Wire Single Spiral Brushes for Small Boilers, Burners, Nozzles & Fans (continued)

These brushes have 3" brush lengths and 1/2" or 3/4" loop handles for easy hanging. All brushes have labels on handles with individual UPC identification.

Cat #	Description	Std. Pkg.	Wgt./Pkg.		Cat #	Description	Std. Pkg.	Wgt./Pkg.
01100	3/4" Dia., 9" OAL, Carbon Steel	12	.55 lbs.		01204	1-1/4" Dia., 18" OAL, Stainless, Steel	12	1.50 lbs.
01198	3/4" Dia., 18" OAL, Stainless Steel	12	1.10 lbs.		01222	1-1/4" Dia., 24" OAL, Stainless Steel	12	2.10 lbs.
01216	3/4" Dia., 24" OAL, Stainless Steel	12	1.50 lbs.		01272	1-1/4" Dia., 36" OAL, Stainless Steel	12	2.90 lbs.
01264	3/4" Dia., 36" OAL, Stainless Steel	12	2.20 lbs.		01224	1-1/2" Dia., 24" OAL, Stainless Steel	6	1.00 lbs.
01399	3/4" Dia., 42" OAL, Carbon Steel	6	2.50 lbs.		01274	1-1/2" Dia., 36" OAL, Stainless Steel	6	1.50 lbs.
01110	13/16" Dia., 10" OAL, Carbon Steel	12	.80 lbs.		01398	1-1/2" Dia., 42" OAL, Carbon Steel	6	2.60 lbs.
				1	01226	2" Dia., 24" OAL, Stainless Steel	6	1.00 lbs.
01120	7/8" Dia., 10" OAL, Carbon Steel	12	.80 lbs.		01276	2" Dia., 36" OAL, Stainess Steel	6	1.50 lbs.
01200	7/8" Dia., 18" OAL, Stainless Steel	12	1.20 lbs.		01400	2" Dia., 42" OAL, Carbon Steel	6	2.70 lbs.
01218	7/8" Dia., 24" OAL, Stainless Steel	12	2.00 lbs.		01324	2" Dia., 48" OAL, Stainless Steel	6	2.90 lbs.
01268	7/8" Dia., 36" OAL, Stainless Steel	12	2.80 lbs.		01278	2-1/2" Dia., 36" OAL, Stainless Steel	6	1.50 lbs.
01140	1" Dia., 10" OAL, Carbon Steel	12	.80 lbs.		01405	2-1/2" Dia., 42" OAL, Staintess Steel	6	2.80 lbs.
01202	1" Dia., 18" OAL, Stainless Steel	12	1.50 lbs.		01326	2-1/2" Dia., 48" OAL, Stainless Steel	6	3.00 lbs.
01220	1" Dia., 24" OAL, Stainless Steel	12	2.00 lbs.			, ,	-	
01270	1" Dia., 36" OAL, Stainless Steel	12	2.80 lbs.		01280	3" Dia., 36" OAL, Stainless Steel	6	1.60 lbs.
	.,,				01410	3" Dia., 42" OAL, Carbon Steel	6	3.00 lbs.
01294	1" Dia., 42" OAL, Carbon Steel	6	2.50 lbs.		01328	3" Dia., 48" OAL, Stainless Steel	6	3.50 lbs.

### **Nylon Tube Brushes**

For Boilers, Burners, Radiators, Flues, Vents and Nozzles

### Horsehair/Fiber Tube Brushes for Boilers Burners, Radiators, Flues, Vents and Nozzles

	1		
Cat #	Description	Std. Pkg.	Wgt./Pkg.
04882	1/4" Dia., 6-1/4" OAL, Nylon Tube Brush	6	.05 lbs.
04883	3/8" Dia., 6-1/4" OAL, Nylon Tube Brush	6	.05 lbs.
04884	1/2" Dia., 8-1/2" OAL, Nylon Tube Brush	6	.15 lbs.
01445	1/2" Dia., 30" OAL, Nylon Tube Brush	6	.80 lbs.
04867	3/4" Dia., 9" OAL, Nylon Tube Brush	6	.15 lbs.
04887	3/4" Dia., 30" OAL, Nylon Tube Brush	6	.60 lbs.
01450	3/4" Dia., 30" OAL, Nylon Tube Brush	6	1.20 lbs.
01470	3/4" Dia., 36" OAL, Nylon Tube Brush	6	1.30 lbs.
04888	1" Dia., 12-1/4" OAL, Nylon Tube Brush	6	.40 lbs.
01455	1" Dia., 30" OAL, Nylon Tube Brush	6	1.20 lbs.
01475	1" Dia., 36" OAL, Nylon Tube Brush	6	1.40 lbs.
04890	1-1/4" Dia., 13" OAL, Nylon Tube Brush	6	.40 lbs.
04891	1-1/2" Dia., 13" OAL, Nylon Tube Brush	6	.50 lbs.
01460	1-1/2" Dia., 30" OAL, Nylon Tube Brush	6	1.30 lbs.
01478	1-1/2" Dia., 36" OAL, Nylon Tube Brush	6	1.40 lbs.
04892	2" Dia., 16" OAL, Nylon Tube Brush	6	.75 lbs.
01520	2" Dia., 24" OAL, Nylon Tube Brush	6	1.50 lbs.
39963	2" Dia., 27" OAL, Nylon Tube Brush	6	1.70 lbs.
01481	2" Dia., 42" OAL, Nylon Tube Brush	6	2.30 lbs.
01500	2-1/4" Dia., 36" OAL, Nylon Tube Brush	6	2.20 lbs.
01538	2-1/2" Dia., 36" OAL, Nylon Tube Brush	6	2.20 lbs.
39964	3" Dia., 27" OAL, Nylon Tube Brush	6	1.80 lbs.
01491	3" Dia., 42" OAL, Nylon Tube Brush	6	2.50 lbs.

		1	
Cat #	Description	Std. Pkg.	Wgt./Pkg.
04850	1/4" Dia., 6-1/4" OAL, Horsehair	6	.05 lbs.
04856	3/8" Dia., 9" OAL, Horsehair	6	.15 lbs.
04860	1/2" Dia., 9" OAL, Horsehair	6	.15 lbs.
04964	1/2" Dia., 12" OAL, Horsehair	6	.10 lbs.
04962	1/2" Dia., 18" OAL, Horsehair	6	.30 lbs.
04970	1/2" Dia., 24" OAL, Horsehair	6	.50 lbs.
01836	1/2" Dia., 36" OAL, Horsehair	6	.70 lbs.
01837	1/2" Dia., 42" OAL, Horsehair	6	1.20 lbs.
04865	3/4" Dia., 9" OAL, Horsehair	6	.15 lbs.
04965	3/4" Dia., 12" OAL, Horsehair	6	.25 lbs.
04960	3/4" x 1-1/4" Tapered, 12" OAL, Horseh	air 6	.30 lbs.
04961	3/4" x 1-1/4" Tapered, 17" OAL, Horseh	air 6	.40 lbs.
17415	7/8" Dia., 27" OAL, Horsehair	6	1.00 lbs.
17419	7/8" Dia., 40" OAL, Horsehair	6	1.50 lbs.
04870	1" Dia., 12-1/2" OAL, Horsehair	6	.30 lbs.
04900	1" Dia., 16" OAL, Horsehair	6	.50 lbs.
04875	1-1/4" Dia., 13" OAL, Horsehair	6	.50 lbs.
04905	1-1/4" Dia., 16" OAL, Horsehair	6	.60 lbs.
39924	1-1/4" Dia., 30" OAL, Horsehair	6	1.50 lbs.
04878	1-1/2" Dia., 12" OAL, Horsehair	6	.50 lbs.
04910	1-1/2" Dia., 16" OAL, Horsehair	6	.60 lbs.
01388	1-1/2" Dia., 42" OAL, Tampico	6	2.50 lbs.
04880	2" Dia., 16" OAL, Horsehair	6	1.2 lbs.
39961	2" Dia., 27" OAL, Tampico	12	4.30 lbs.
01480	2" Dia., 42" OAL, Tampico	24	13.00 lbs.
39920	2-1/4" Dia., 30" OAL, Horsehair	6	2.50 lbs.
39960	2-1/2" Dia., 27" OAL, Tampico	12	4.50 lbs.
39962	3" Dia., 27" OAL, Tampico	12	2.40 lbs.
39921	3" Dia., 30" OAL, Horsehair	6	1.60 lbs.
01490	3" Dia., 42" OAL, Tampico	12	7.00 lbs.
01492	4" Dia., 42" OAL, Tampico	12	4.50 lbs.



### Soot Saw

#### ------

Ideal for heavy-duty soot and creosote removal from commercial and residential boilers. The perfect tool when brushes just don't do the job.

#### **Polished Tampico Boiler & Flue Brushes**

Select Grade of Polished Tampico (slightly stiffer and more durable).

		- 400904	
Cat #	Description	Std. Pkg.	Wgt./Pkg.
39971	2" Diameter, 27" OAL	6	1.8 lbs.
39973	2" Diameter, 42" OAL	6	2.7 lbs.
39975	3" Diameter, 27" OAL	6	2.0 lbs.
39977	3" Diameter, 42" OAL	6	3.0 lbs.







### Flue & Boiler Tube Brushes

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70707	Soot Saw	10	10.0 lbs.

Features plastic handle and heavy-gauge galvanized steel with serrated edge that cuts through soot and creosote fast. 32" overall length.



#### Specialty Boiler Brushes - TAPERED

	84023			
- 0	84215	-	Here and the second	
Cat #	Description	Std. Pkg.	Wgt./Pkg.	
84219	3/8" - 7/8" Taper, 24" OAL, Tampico	6	2.5 lbs.	L
84023	1-7/8" - 1-1/8" Taper, 30" OAL, Tampico	6	1.2 lbs.	L
84027	1-7/8" - 1-1/8" Taper, 42" OAL, Horsehai	ir 12	4.0 lbs.	L
84028	1-7/8" - 1-1/8" Taper, 30" OAL Horsehai	r 6	1.2 lbs.	L
84029	1/2" - 1" Taper, 42" OAL, Horsehair	6	1.2 lbs.	L
84212	1/2" -1" Taper, 36" OAL, Horsehair	6	1.3 lbs.	L
84214	1/2" - 1" Taper, 30" OAL, Horsehair	6	1.2 lbs.	L
84215	1/2" - 1" Taper, 30" OAL, Tampico	6	1.2 lbs.	
84216	1/2" - 1" Taper, 21" OAL, Horsehair	6	1.0 lbs.	

Horsehair Brush for Radiators					
Cat #	Description	Std. Pkg.	Wgt./Pkg.		
39919	1-Row, 24"OAL, Wood Handle Brush	12	4.0 lbs.		

The Mill-Rose Co. | Clean-Fit Products | 800.321.3598 | info@cleanfit.com | cleanfit.com

# MR THE FOSE

Cat #

## **Target Chimney Flue Cleaning Products**

1/4" Target Consumer-Grade Chimney Flue Cleaning Products



Target chimney/flue cleaning brushes are available in oil-tempered wire for cleaning ceramic flues and chimneys, and polypropylene (synthetic nylon) for cleaning metal flues and chimneys. Choose from a complete range of standard sizes and shapes with 1/4" NPT connectors, and made with #10 galvanized material.

#### Extension Rods for Flue, Boiler, and Chimney Cleaning Brushes with 1/4" Couplings



300334' Standard Twisted Wire Rod, Bulk-Pack, 24 119.6 lbs.300646' Standard Twisted Wire Rod47.9 lbs.300736' Standard Twisted Wire Rod, Bulk-Pack, 24 147.4 lbs.

Note: Exercise caution when working near electrical outlets and wires as metal brushes and steel extension rods conduct electricity.



Consume	r Grade Wire Chimney / Flue Br	ushes with	1/4" NPT
30450	4-3/4" Round	1	.5 lbs.
30500	5" Round	1	.6 lbs.
30600	6" Round	1	.75 lbs.
30700	7" Round	1	.8 lbs.
30800	8" Round	1	.9 lbs.
30900	9" Round	1	1 lbs.
31000	10" Round	1	1.2 lbs.
31100	11" Round	1	1.3 lbs.
31200	12" Round	1	1.4 lbs.
31428	14" Round	1	1.75 lbs.
30404	4"x4" Square	1	.75 lbs.
30606	6"x6" Square	1	.85 lbs.
30707	7"x7" Square	1	.95 lbs.
30808	8"x8" Square	1	1.2 lbs.
31010	10"x10" Square	1	1.0 lbs.
31111	11"x11" Square	1	1.8 lbs.
31212	12"x12" Square	1	2 lbs.
31416	14"x14" Square	1	2.5 lbs.
31006	10"x6" Rectangular	1	1.2 lbs.
31008	10"x8" Rectangular	1	1.5 lbs.
31107	11"x7" Rectangular	1	1.6 lbs.
31208	12"x8" Rectangular	1	1.8 lbs.
31612	16"x12" Rectangular	1	2.5 lbs.
Consume	r Grade Poly Chimney / Flue Br	ushes with	1/4" NPT
33105	4" Round Poly	1	.4 lbs.
33110	5" Round Poly	1	.5 lbs.
33140	6" Round Poly	1	.6 lbs.
33170	7" Round Poly	1	.7 lbs.
33190	8" Round Poly	1	.8 lbs.
33205	9" Round Poly	1	.9 lbs.
33208	10" Round Poly	1	1 lbs.
33210	12" Round Poly	1	1.2 lbs.
33150	6"x6" Square Poly	1	.75 lbs.
33180	7"x7" Square Poly	1	.8 lbs.
33200	8"x8" Square Poly	1	1 lbs.
33211	10"x10" Square Poly	1	1.4 lbs.
33212	12"x12" Square Poly	1	1.6 lbs.
33213	11x7" Rectangular Poly	1	1.2 lbs.
33222	12"x8" Rectangular Poly	1	1.4 lbs.
33226	16"x12" Rectangular Poly	1	2 lbs.



## **Target Chimney Flue Cleaning Products**



### Standard Accessory Kits - 1/4" NPT (without Brushes)

These space saving SKU's offer a complete cleaning kit with any selected brush. Contains: 6 each 4' FG Rods, 1 each Eye Socket Nipple, 1 each Bent Handle Scratch Brush, 1 each "T" handle, 1 each Flue Creosote Scraper and 1 each DIY Illustration Booklet. (Accessory Kit does not include a chimney brush).

### 3/8" Target Contractor-Grade Chimney Flue Cleaning Products



Target contractor-grade chimney/flue cleaning brushes are available in oil-tempered wire for cleaning ceramic flues and chimneys. These heavy-duty brushes are offered with 3/8" NPT connectors and are made with #8 galvanized stem material for reduced flex. Our brushes are oversized by 1/16" and have 2-1/2" brush parts. Contact customer service for oval-shaped chimney brushes or other sizes that are not listed.

are oversized by 1/16" and have 2-1/2" brush parts. Contact customer service for oval-shaped chimney brushes or other sizes that are not listed.	
Extension Rods for	
Flue, Boiler, and Chimney Cleaning Brushes with 3/8" Couplings	C

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70010	Eye Socket Nipple 1/4" NPT Bulk 1/4" NPT fitting, 3/4" eye - for rope weigh or two person chimney flue cleaning.	12 nt	.5 lbs.
70040	25' Poly Rope Bulk packed. Use with standard or heavy-duty chimney brushes and eye socket nipple or brush ri to clean chimneys.		1.2 lbs.
70722	Flex Connector 13" Flex connector for standard rods - 1/-	4" NPT 6	0.45 lbs.
70766	<b>"T" Handle For Extension Rods</b> Steel - use with 1/4" NPT extension rods. #70020 coupling included for female thre Display package.		2.3 lbs.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
39690	Fiberglass Accessory Kit	1	3.0 lbs.
The second		- In Column	Bellen and

Bras Net 110 Bras Net 120

AND ACTING TO

Standard Roun Wire Brush	d Standard Square Wire Brush		d Rectangular re Brush
Cat #	Description	Std. Pkg.	Wgt./Pkg.
30501	5" H.D. Round Wire	1	2.0 lbs.
30601	6" H.D. Round Wire	1	2.1 lbs.
30701	7" H.D. Round Wire	1	2.1 lbs.
30801	8" H.D. Round Wire	1	2.2 lbs.
30901	9" H.D. Round Wire	1	3.2 lbs.
31001	10" H.D. Round Wire	1	3.4 lbs.
31101	11" H.D. Round Wire	1	3.5 lbs.
31201	12" H.D. Round Wire	1	3.6 lbs.
31401	14" H.D. Round Wire	1	3.6 lbs.
30607	6"x6" H.D. Sqr. Wire	1	2.1 lbs.
30708	7"x7" H.D. Sqr. Wire	1	2.4 lbs.
30809	8"x8" H.D. Sqr. Wire	1	2.8 lbs.
30910	9"x9" H.D. Sqr. Wire	1	3.4 lbs.
31011	10"x10" H.D. Sqr. Wire	1	3.6 lbs.
31112	11"x11" H.D. Sqr. Wire	1	3.8 lbs.
31213	12"x12" H.D. Sqr. Wire	1	3.9 lbs.
31415	14"x14" H.D. Sqr. Wire	1	4.0 lbs.
31007	10"x6" H.D. Rect. Wire	1	2.6 lbs.
31009	10"x8" H.D. Rect. Wire	1	2.7 lbs.
31108	11"x7" H.D. Rect. Wire	1	2.8 lbs.
31205	12"x8" H.D. Rect. Wire	1	2.9 lbs.
31613	16"x12" H.D. Rect Wire	1	4.0 lbs.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
Contract	or-Grade Rods with 3/8" NPT		
30015	3' Heavy-Duty Fiberglass Rod	6	3.0 lbs.
30035	4' Heavy-Duty Fiberglass Rod	6	2.4 lbs.
30065	6' Heavy-Duty Fiberglass Rod	4	4.0 lbs.

# MR MILEROSE

## **Target Chimney Flue Cleaning Products**

### 3/8" Chimney Brush Accessories



Purchase 70030 and 70766 when coupling handle to 3/8" rod.

<ul> <li>70016 Heavy Duty Eye Socket Nipple 3/8" NPT Bulk 3/8" NPT, 3/4" eye - heavy duty.</li> <li>70030 Reducer Coupling 3/8" to 1/4" NPT 1/4" - 3/8" Reducer for conversion from 3/8" NPT extension rod/brush to standard 1/4" NPT or vice versa.</li> <li>70040 25' Poly Rope Bulk packed. Use with standard or heavy-duty chimney brushes and eye socket nipple or brush ring to clean chimneys.</li> <li>70766 "T" Handle For Extension Rods Steel - use with 1/4" NPT extension rods. #70020 coupling included for female thread.</li> <li>12 1.2 lbs.</li> </ul>	Cat #	Description Std.	Pkg.	Wgt./Pkg.
1/4" - 3/8" Reducer for conversion from 3/8" NPT extension rod/brush to standard 1/4" NPT or vice versa.121.2 lbs.7004025' Poly Rope Bulk packed. Use with standard or heavy-duty chimney brushes and eye socket nipple or brush ring to clean chimneys.121.2 lbs.70766"T" Handle For Extension Rods Steel - use with 1/4" NPT extension rods.62.3 lbs.	70016	, , , , , ,,	k 12	.9 lbs.
<ul> <li>Use with standard or heavy-duty chimney brushes and eye socket nipple or brush ring to clean chimneys.</li> <li>70766 "T" Handle For Extension Rods Steel - use with 1/4" NPT extension rods.</li> </ul>	70030	1/4" - 3/8" Reducer for conversion from 3/8" NPT extension rod/brush to standard 1/4"	12	1.2 lbs.
Steel - use with 1/4" NPT extension rods.	70040	Use with standard or heavy-duty chimney brushes and eye socket nipple or brush ring	12	1.2 lbs.
Display package.	70766	Steel - use with 1/4" NPT extension rods. #70020 coupling included for female thread.	6	2.3 lbs.

Chimney Brush Accessori	es	
-	39925	
C	39950	
		Munness.
70035		
	70038	
	•	70606
70650		70610
1000000	73834	2

26

Cat #	Description Std. P	kg. \	Ngt./Pkg.
39925	Chimney Smoke Shelf Cleaning Brush 2-1/2"x25" long/handle - drilled hole for display. Can be bent for desired length. Horsehair/tampico fiber.	6	4 lbs.
39950	Professional Smoke Shelf Cleaning Brush 3-1/2"x28" long/handle-drilled hole for display. Heavier duty-horseshoe shape. Horsehair/ tampico blend fiber.	6	8 lbs.
70035	Deluxe Utility Dusting/Cleaning Brush Horsehair/tampico filament - drilled handle/ display. Wood Handle.	12	4 lbs.
70038	Utility Dusting Brush Economy with synthetic filament - drilled handle/display.	12	4 lbs.
70606	Bent Handle Scratch Brush Drilled handle for display - quality hardwood handle, carbon steel wire for corrosion, paint and dirt removal.	12	4.6 lbs.
70610	Bent Handle Scratch Brush/Scraper Same as #70606/Metal End Scraper.	12	5.3 lbs.
70650	Chimney Duster Wire Brush Wood handle, fine wire fill. For smoke shelf and fireplace corners.		5.0 lbs.
73834	Stainless Steel Stove Appliance Brush 8 1/4" plastic handle. For cleaning decorative areas of wood stoves and fireplace screens. (Also Available in brass/nylon).	36	5.0 lbs.



## **Target Chimney Flue Cleaning Products**

### Brushes & Accessories for Clothes Dryer Vents / Pellet Stove Flues



Cleaning brushes and accessories for clothes dryer vents and pellet stove flues improve heating efficiency, reduce fire hazard and save money! Soft synthetic fiber brushes are designed to remove lint buildup (#84373). For heavy lint build-up in commercial dryer vents, fiber brushes may be more aggressive (#84333). Fiber brushes work best for soot removal in pellet stove flues, while stainless steel wire works best for creosote removal.

Target cleaning brushes and flexible extension rods with 1/4"-20 couplings are designed to negotiate 90° joints in most vents and flues. In many cases, vents and flues can be cleaned without disassembly. Attractive point-of-sale packaging includes complete cleaning instructions.

**Fiberglass Extension Rods** 

Steel Extension Rods

Cat #	Description	Std. Pkg.	Wgt./Pkg.	
Pellet B	rushes (1/4-20 male/female thread)			
84332	3" dia. Fiber Pellet Stove Brush	6	1.1 lbs.	
	Point-of-Purchase			
84333	4" dia. Fiber Pellet Stove Brush	6	1.2 lbs.	
	Point-of-Purchase			
84334	4" dia. Fiber Pellet Stove Brush with 12' Flexible Extension Bod	1	1.0 lbs.	
84352	3" dia. St.St. Wire Pellet Stove	6	1.6 lbs.	
04332	Brush Point-of-Purchase	0	1.0 103.	
84372	4" dia. St.St. Wire Pellet Stove	6	1.8 lbs.	
0.012	Brush Point-of-Purchase	•		
84380	6" dia. Fiber Pellet Stove Brush	6	2.2 lbs.	
84385	8" dia. Fiber Pellet Stove Brush	6	2.5 lbs.	
Dryer Ve	ent Brushes (1/4-20 male/female thr	ead)		
84373	4" dia. Synthetic Fiber Dryer Vent	6	1.0 lbs.	
	Brush - Point-of-Purchase			
84374	4" dia. Synthetic Fiber Dryer Vent	1	.8 lbs.	
	Brush with 8' Flexible Ext. Rod			
84375	4" dia. Synthetic Fiber Dryer Vent 1		1.0 lbs.	
	Brush with 12' Flexible Ext. Rod			
Pellet &	Dryer Vent Accessories (1/4-20 male	e/female	thread)	
65011	4' Flexible extension Rod	6	.6 lbs.	
	1/4"-20 thread			
65012				
65013	8' Flexible Ext. Rod-POP-1/4-20 threa		1.2 lbs.	
65008	"T" Handle only - 1/4-20 thread	6	.4 lbs.	
65009	Rod/Brush Adapter	0	0.11-2	
70723	(5/16-18 to 1/4-20 thread) 6" OAL for Dryer Vent Brush	6	.3 lbs.	
10123	1/4"-20 Flex Connector	6	.45 lbs.	
		U	.40 105.	

Description	Std. Pkg.	Wgt./Pkg.
ve / Vent Cleaning Brushes (5/16" -	18 interr	nal thread)
2" dia. Fiber Pellet Stove / Vent Brus	h 6	1.0 lbs.
3" dia. Fiber Pellet Stove / Vent Brus	h 6	1.1 lbs.
4" dia. Fiber Pellet Stove / Vent Brus	h 6	1.2 lbs.
3' Fiberglass Ext. Rod with "T" Hand	le 6.	90 lbs.
"T" Handle with	6	.40 lbs.
5/16" - 18 male/female thread		
Rod/Brush Adapter with		
5/16"-18 to 1/4-20 thread	6	.30 lbs.
2' Fiberglass Ext. Rod 5/16"-18 thread	6	1.00 lbs.
3' Fiberglass Ext. Rod 5/16"-18 thread	6	1.25 lbs.
4' Fiberglass Ext. Rod 5/16"-18 thread	6	1.90 lbs.
6' Fiberglass Ext. Rod 5/16"-18 thread	6	1.90 lbs.
5/16-18 Flex Connector	6	1.10 lbs.
	ve / Vent Cleaning Brushes (5/16" - 2" dia. Fiber Pellet Stove / Vent Brusl 3" dia. Fiber Pellet Stove / Vent Brusl 4" dia. Fiber Pellet Stove / Vent Brusl 3' Fiberglass Ext. Rod with "T" Handl "T" Handle with 5/16" - 18 male/female thread Rod/Brush Adapter with 5/16"-18 to 1/4-20 thread 2' Fiberglass Ext. Rod 5/16"-18 thread 4' Fiberglass Ext. Rod 5/16"-18 thread 6' Fiberglass Ext. Rod 5/16"-18 thread	ve / Vent Cleaning Brushes (5/16" - 18 interr2" dia. Fiber Pellet Stove / Vent Brush63" dia. Fiber Pellet Stove / Vent Brush64" dia. Fiber Pellet Stove / Vent Brush63' Fiberglass Ext. Rod with "T" Handle63' Fiberglass Ext. Rod with "T" Handle65/16" - 18 male/female thread6Rod/Brush Adapter with5/16"-18 to 1/4-20 thread5/16"-18 to 1/4-20 thread62' Fiberglass Ext. Rod 5/16"-18 thread63' Fiberglass Ext. Rod 5/16"-18 thread64' Fiberglass Ext. Rod 5/16"-18 thread66' Fiberglass Ext. Rod 5/16"-18 thread6

### Maintenance & Applicator Brushes

### **Platers Brushes**



These brushes are made with selected hard woods and designed for fine cleaning in metal finishing solder joints, grills, wire mesh, etc. Platers brushes differ from hand scratch brushes in that they are made with finer wire resulting in a softer brush. Available with shoe handle or longer curved handle, trim length 1".

Cat #	Fill Material	Block Type	No. of Rows	Wgt./Pkg.
73800	Fine Brass Wire	Shoe Handle	3 x 16	5 lbs.
73802	Fine Brass Wire	Shoe Handle	4 x 16	6 lbs.
73804	Fine St. Steel	Shoe Handle	3 x 16	4 lbs.
73806	Fine St. Steel	Shoe Handle	4 x 16	5 lbs.
73808	White Tampico	Shoe Handle	4 x 16	5 lbs.
73810	Fine Brass Wire	Curved Handle	3 x 19	5 lbs.
73812	Fine Brass Wire	Curved Handle	4 x 19	6 lbs.
73814	Fine St. Steel	Curved Handle	3 x 19	4 lbs.
73816	Fine St. Steel	Curved Handle	4 x 19	5 lbs.
73820	White Tampico	Curved Handle	4 x 19	5 lbs.
73822	White Tampico	Curved Handle	6 x 19	5 lbs.

Standard package for above is 12.

### Scratch Brushes

These brushes are high quality solid Appalachian hardwood handles and backs - tough, quality, oil tempered, carbon steel fill wire available with or without scrapers and have an extradeep wire staple securing the wire for agressive cleaning jobs.



Cat # **Block Type** Block Size Trim Size Wgt./Pkg. Rows 70540 Straight Back 7-1/4" x 2-1/2" 6 x 19 1-3/4" 9.4 lbs. 70630 7" x 3" 1-3/16" Curved Back 9 x 21 8.0 lbs. 70550 **Curved Handle** 14" x 1-1/8" 4 x 18 1-3/16" 4.6 lbs. 70560 Curved Handle/Scraper 14" x 1-1/8" 4 x 18 1-3/16" 5.3 lbs. 1-3/16" 70606 **Curved Handle** 14" x 1" 3 x 19 4.6 lbs. 1-3/16" 70620 **Curved Handle STST** 14" x 1" 3 x 19 5.3 lbs. 70610 **Curved Handle/Scraper** 14" x 1" 3 x 19 1-3/16" 5.3 lbs. 10" x 1-1/8" 70570 4 x 16 1-3/16" Shoe Handle 5.3 lbs. 70640 Shoe Handle 10" x 9/16" 1-3/16" 4.6 lbs. 2 x 16 Wood Hndl. Duster 2-3/4" x 1-1/8" 4 x 8 2-3/8" 70650 5.0 lbs.

Standard package for above is 12.

70491

70493

Description	Std. Pkg.	Wgt./Pkg.
Deluxe BBQ Brush 20" OAL	12	6.9 lbs.
Short Handle BBQ Brush	12	2.8 lbs.
	Deluxe BBQ Brush 20" OAL	Deluxe BBQ Brush 20" OAL 12

### **Barbeque Grill Brushes**

The design of these brushes places all crimped brass bristles flush on the grill for faster, easier clean up. Our brushes feature more bristles per tuft and more tufts per inch than inexpensive import brushes.

and and all				
	Cat #	Description	Std. Pkg.	Wgt./Pkg.
th a natural bristle.	70490	6" Plastic Applicator Brush - Pint	12	1.9 lbs.

7" Plastic Applicator Brush - Quart

8" Plastic Applicator Brush - 1/2 Gal.

# Plastic Applicator Brush with Cap

This brush is made with a natural bristle, solvent resistant adhesive. Ideal for applying solvents, cleaners and adhesives. Fits pint, guart or 1/2-gallon containers.

### Acid, Solder Paste and Flux, Adhesive Applicator Brushes

Tin handles are stamped firmly to the bristles to eliminate bristle fall-out.



They are offered in three convenient sizes with pure, stiff black-graded natural horsehair. Our #70240 brush has a hardwood handle with seamless aluminum ferrule.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70210	#1 Acid Br 1/4" (gross lot)	1	5.8 lbs.
70211	#1 Acid Br 1/4" (48 per box)	1	2.0 lbs.
70220	#2 Acid Br 3/8" (gross lot)	1	6.0 lbs.
70221	#2 Acid Br 3/8" (48 per box)	1	2.1 lbs.
70230	#3 Acid Br 1/2" (gross lot)	1	6.2 lbs.
70231	#3 Acid Br 1/2" (48 per box)	1	2.2 lbs.
70240	#7 Acid Br. (Wood Handle) - 3/4"	1	5.8 lbs.
71020	#2 Acid Br. 3/8" - 3 each Carded	10	1.3 lbs.
71021	#2 Acid Br. 3/8" - 6 each Disp Bag	10	2.4 lbs.
71022	#1 Acid Br. 1/4" - 10 each Disp Bag	10	2.3 lbs.

12

12

2.2 lbs.

2.5 lbs.



### **Cotton Swabs**

These twisted-wire swabs are available in cotton for gasketed pipe lube, solder flux, adhesive, solvents, etc. Ideal for cleaning and many other applications.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
05060	Cotton Swab 1-1/2" x 11" Overall	12	1.5 lbs.
05065	Cotton Swab 2" x 11" Overall	12	1.7 lbs.
05070	Cotton Swab 2" x 15" Overall	12	2.0 lbs.



## Maintenance & Applicator Brushes



These wood-handle brushes have nickel-steel ferrules making them rugged and rust proof. The bristles are fitted using chemical and solvent resistant adhesives and come in stiff, medium and soft bristles. They are useful for cleaning parts, tools, machine components, etc., using solvents or degreasers.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70510	#10 Medium Black Crimped Polypropylene - Dome trim, wood har cracks and crevices for quick, efficier 1-1/16" Dia.; Trim Length is 3-1/4"; 1	nt parts washin	g.
70520	#10 Three-Color Gray Tampico Dome Trim, Wood Handle. Excellent fi and small parts. Tough tampico bristle 1-1/16" Diameter; Trim Length is 3";	es withstand m	ost solvents.
70500	#8 Soft Natural Bristle Fill Plastic Handle - Straight Trim, Round, and for applying solutions to clean sn 15/16" Dia.; Trim Length is 2"; 10-1/8	nall parts and e	lectronics.

### **Economy Paint Chip and Applicator Brushes**



These wood handle brushes contain natural bristles fitted with a chemically-resistant adhesive. They are disposable and offer a variety of uses such as applying solvents, cements and pipe lube. They can also be used for clean-up or staining and painting.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70430	Econo. Applicator Brush - 1/2"	36	1.4 lbs.
70440	Econo. Applicator Brush - 1"	36	1.8 lbs.
70450	Econo. Applicator Brush - 1-1/2"	36	2.3 lbs.
70460	Econo. Applicator Brush - 2"	24	2.9 lbs.
70470	Econo. Applicator Brush - 2-1/2"	24	3.0 lbs.
70480	Econo. Applicator Brush - 3"	24	3.3 lbs.
70485	Econo. Applicator Brush - 4"	12	3.5 lbs.
70483*	Econo. Applicator Brush - 3"	12	3.5 lbs.
70486*	Econo. Applicator Brush - 4"	12	4.0 lbs.
70489	Sample Kit-Display (One Each of Above	e) 1	1.8 lbs.

Cat #	Wire Type	Rows	Trim/ Inches	Block Type	Std. Pkg.	Wgt./ Pkg.
73830	Stainless Steel	3 x 7	1/2	Wood	36	5 lbs.
73832	Brass	3 x 7	1/2	Curved wood	36	5 lbs.
73834	Stainless Steel	3 x 7	1/2	Plastic	36	5 lbs.
73836	Brass	3 x 7	1/2	Plastic	36	5 lbs.
73838	Nylon	3 x 7	1/2	Plastic	36	5 lbs.
71040	2 Brushes - Car (1 Stainless S				10	1.4 lbs.
71041	3 Brushes - Ba (1 Stainless S		Brass, 1	Plastic Nylon)	5	1.8 lbs.

### Welders / Utility Brushes



in wood or plastic handles, are offered with different types of fine wire bristles, including stainless steel, brass, bronze, aluminum and nylon. They are perfect for cleaning in tight spots. Other uses include clean-up after soldering, brazing and

These brushes, available

### **Appliance Type Brushes**

These are small scouring brushes with smooth hardwood handles. Ideal for cleaning and scouring appliances, stoves, burner units, oil burners, for assemblies of small parts. Fine wire stainless steel and brass.



Cat #	Wire Type	Rows	Trim/ Inches	Block Type	Std. Pkg.	Wgt./ Pkg.
73842	Stainless Stee	el 2 x 9	11/16"	Curved wood	36	7 lbs.
73844	Brass	2 x 9	11/16"	Curved wood	36	7 lbs.





welding.

These brushes are staple-set constructed in a shaped, hardwood, beaver-tail style handle with a lacquer coating and hole for hanging. They are designed specifically for light brushing or dusting.

Cat #	Description	Length	Width	Trim St	d. Pkg.	Wgt./Pkg.
70035	Horsehair/Tampico	13"	3"	2-1/2"	12	4 lbs.
70038	Polypropylene	13"	3"	2-1/2"	12	4 lbs.

\*Double-Thick Bristles

# R M - ROSE

### **Maintenance & Applicator Brushes**

### Handy Wire Chip Brush

This tool, offered in carbon or stainless steel bristles, is designed for the removal of machine chips, cuttings and dust in those narrow, hard to reach places. Resistant to heat.



Cat #	Description	Width	Length	Std. Pkg.	Wgt./Pkg.
75200	Carbon Steel Wire	1-1/2"	5-1/2"	12	1.3 lbs.
75210	St. Steel Wire	1-1/2"	5-1/2"	12	1.3 lbs.

### Deluxe Mill-Rose Hand & Nail Brush

These brushes are constructed of high-impact plastic and durable nylon bristles. They have an ergonomic grip and are great for removing embedded dirt and grime from hands and fingernails. The bristles are unaffected by hand cleansers and common household chemicals.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
73864	Deluxe Hand & Nail Brush (Box of 12)	1	3.4 lbs.



**Toilet Bowl Brushes** 

Cat #	Fill Material	Length	Handle St	d. Pkg.	Wgt./Pkg.
05010	Tampico	19-1/2"	3/4" x 14"	12	6.5 lbs.
05015	Black polypropylene	19-1/2"	3/4" x 14"	12	6.5 lbs.
05020	Black nylon	19-1/2"	3/4" x 14"	12	6.5 lbs.

Clean-Fit Toilet Bowl Brushes all come with a lacquered hardwood handle and are built to withstand the daily concentrated abuse of commercial, industrial and institutional service. Not to be confused with the average light duty household toilet brush for limited duty. #05015 heavy-duty version made with 2-1/4" diameter. #05010 and #05020 made with 2" diameter.

### Long Handle Utility Scrub Brush

Applications include scrubbing vehicles, rigs, cans, tubs, pots, pipe, refuse containers, fenders, wheels, tires, and boats. The Tampico and Nylon fill materials are designed specifically for trade applications for combustion chambers, pots, and ducts.

Cat #	Base Type	Fill Material	Trim Length	Length	Std. Pkg	Wgt./Pkg.
75100	Plastic	Tampico	2-1/4"	20"	12	10 lbs.
75108	Plastic	Nylon	2-1/4"	20"	12	9 lbs.

#### Whisk Broom

This broom is constructed of fine grade broom corn with a emral hanging. It is tough and yet maintains a "light touch" for detail cleaning of trucks and vehicles as well as many other uses.

	Cat #	Broom Length	Std. Pkg.	Wgt./Pkg.
all.	70795	12"	12	4 lbs.
20				-



## **Maintenance & Applicator Brushes**

Palmyra - Heavy Floor Sweep



Heavy floor sweeps are used for heavier dirt and debris. Superior construction makes these sweeps ideal for use on unfinished concrete or rough floors.

Cat #	Wood Block Size	Trim	Std. Pkg.	Wgt./Pkg.
75054	3" x 18"	4" 4"	12 12	20.50 lbs. 27.30 lbs.
75056	3" x 24"	4	12	27.30 IDS.

### Horsehair and Plastic Mix - Fine Floor Sweep



Cat #	Wood Block Size	Trim	Std. Pkg.	Wgt./Pkg.
75040	3" x 18"	3"	12	20.50 lbs.
75041	3" x 24"	3"	12	27.30 lbs.

Fine floor sweeps are used for sweeping dust and dirt on smooth waxed or polished surfaces.

Looguarad Waad and Eibergloop Handloo	Cat #	<b>Overall Length</b>	Handle	Diameter	Std. Pkg.	Wgt./Pkg.
Lacquered Wood and Fiberglass Handles	75071	60"	Lacquered	15/16"	12	22.1 lbs.
Lacquered wood handle or fiberglass handle with hang hole.	75080	60"	Fiberglass	1"	12	16.5 lbs.





# M THE SE

### Screwdrivers/Hand Tools & Storage Boxes

### **Superior Quality Screwdrivers**

These professional screwdrivers are produced to Mill-Rose specifications using high-carbon, fine-grained, open-hearth tool steel which insures long-lasting steel durability. Bits are salt-bath hardened and tempered to provide optimum hardness, maximum torque transfer and high wear resistance.

- Versatile
- Finest Grade Tool Steel!
- Precision Ground
- Professional Quality
- Deep-Tempered ... exclusive with Mill-Rose
- The ultimate in professional-quality forged hand tools

### 6-in-1 Ratcheting Screwdriver Slot/Phillips/Nut Drivers







This screwdriver features three-way ratcheting (forward, fixed and reverse) with a large, ergonomic cushion-grip handle. Six drivers include two nut drivers (1/4" and 5/16"), interchangeable magnetized flat bits (1/4" and 3/16") and phillips bits (#1 and #2). Not available for private labeling at this time.

### Personalized or "Private Labeled" 4-in-1 Screwdrivers / 6-in-1 Screwdrivers

Your name, company logo, message, phone number, website, or whatever, will be printed on each screwdriver. One line of type in one flute on the handle:

> 26 letters - 4-in-1 / 6-in-1 Screwdriver 17 letters - Mini 4-in-1 Screwdriver

### FONT SIZE SAME AS THESE LETTERS

(26 total characters including spaces)

Cat #	Description	Stock Size	Overall Length	Std. Pkg	<b>J</b>
72148	6-in-1 Ratchet Screwdriver (1 each) Flat/Phillips/Nut Drive	1/4"-5/16" r	7-1/2"	12	7.5 lbs.
72143	6-in-1 Screwdriver repl. tube	4-1/2"	4-1/2"	10	1.0 lbs.
72144	Flat 3/16" and Phillips PB1	1/4"	3"	10	.5 lbs.
72145	Flat 1/4" and Phillips PB2	5/16"	3"	10	.5 lbs.
	Chandowd waalkawa in 10 aanh e	4 C in 1 Car		DOL	Diamlass

Standard package is 12 each of 6-in-1 Screwdrivers - POP Display

### 6-in-1 Screwdriver Slot/Phillips/Nut Drivers







This screwdriver is six drivers in one with an interchangeable slot and Phillips bits, plus two different size nut drivers. Contains flat 3/16" and 1/4" bits, #1 and #2 Phillips bits and 1/4" and 5/16" nut drivers.

Cat #	Description	Stock Size	Overall Length	Std. Pkg.	<b>J</b>
72151	6-in-1 Screwdriver (1 each) Flat/Phillips/Nut Drive	1/4"-5/16 r	7-1/2"	12	5.2lbs.
70410 70412	Flat 3/16" and 5/16" Bits each Phillips PB1 and PB2 Bits each	5/16" 5/16"	3" 3"	10 10	.5 lbs. .5 lbs.
72086 72089	Flat 1/8" and 3/16" Bits each Phillips PB1 and PB2 Bits each	1/4" 1/4"	2-1/2" 2-1/2"	10 10	.3 lbs. .3 lbs.
	Standard package is 12 each of	6-in-1 Sc	rewdrivers	s - POF	P Display

### 4-in-1 Screwdriver Slot/Phillips





This screwdriver is four screwdrivers in one with an interchangeable slot and Phillips bits. Applications for this versatile screwdriver are limitless. Contains flat 3/16" and 1/4" bits with #1 and #2 Phillips bit.

Cat #	Description	Stock Size	Overall Length	Std Pkg	<b>J</b>
70400	4-in-1 Screwdriver (1 each) Flat/Phillips Bits	5/16"	7-1/2"	12	5.2 lbs.
70410 70412	Flat 3/16" and 5/16" Bit each Phillips PB1 and PB2 Bits each	5/16" 5/16"	3" 3"	10 10	.5 lbs. .5 lbs.

Standard package is 12 each of 4-in-1 screwdrivers - POP Display



### Screwdrivers/Hand Tools & Storage Boxes



Perfect for recreational vehicles, utility drawers, automobiles, boats, and as gifts. Contains flat 1/8" and 3/16" bit with #0 and #1 Phillips bits. See previous page for our Private Label Program. We can personalize with your company name or message. Contains flat 1/8" and 3/16" bits with #0 and #1 Phillips bits.

Cat #	Description	Stock Size	Overall Length	Std. Pkg	3
72083	4-in-1 Mini Screwdriver (1 each) Flat/Phillips Bits	1/4"	5"	12	3.0 lbs.
72086	Flat 1/8" & 3/16" Bit	1/4"	1-1/2"	10	.3 lbs.
72088	Phillips PB0 & PB1 Bit	1/4"	1-1/2"	10	.3 lbs.

Standard package is 12 for 4-in-1 mini screwdrivers - POP Display

# 2-in-1 Stubby Screwdriver

A stubby version. Only one bit with a No. 1 Phillips on one end, and a 3/16" flat on the other. 3-3/8" overall length.

Cat #	Description	Stock Size			. Wgt./ . Pkg.
72090	2-in-1 Stubby Screwdriver	5/16"	3-3/8"	6	1.2 lbs.
72092	Flat 3/16" & PB1 Bit	5/16"	3"	6	.3 lbs.
72093	Fishbowl Display (10 per di	isplay)		10	5 lbs.



### **Magnetic Power Nut Drivers**



The "Fishbowl" Display Point-of-Sale Merchandiser is great way to display small items on the Countertop.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
Magnet	ic Power Nut Drivers - Bagged		
72136 72138	1/4" Power Nut Driver - 1 per bag 5/16" Power Nut Driver - 1 per bag	10 10	1.5 lbs. 1.5 lbs.
Bulk - F	ishbowl Display - 150 Drivers Per Dis	splay	
72140 72142	1/4" Power Nut Driver 5/16" Power Nut Driver	1 1	5.0 lbs. 5.0 lbs.

For fast work when driving 1/4" and 5/16" hex-head washer screws, including speed screws, sheet metal screws and no-hub couplings. Inserts into 1/4" and 3/8" drill chucks.

# 

## Screwdrivers/Hand Tools & Storage Boxes

"Fit All" Power Bits 1-7/8" Overall Length 1/4" Hex Shank



Transparent "Fishbowl"Display is an ideal Point-of-Sale Merchandiser for Countertops.

A tougher, longer lasting power bit! Precision tip geometry transmits higher torque into the screw, resulting in a decrease in the screw or

Cat #	Description	Overall Length	Std. Pkg.	Wgt./Pkg.
"Fit-All	" Power Bits - 1/4" Hex	Shank 2 Per	Display Pac	:kage
72098	#6-#8 Flat Tip	1-7/8"	10	1.0 lbs.
72100	#8-#10 Flat Tip	1-7/8"	10	1.0 lbs.
72102	#10-#12 Flat Tip	1-7/8"	10	1.0 lbs.
72104	No. 1 Phillips	1-7/8"	10	1.0 lbs.
72106	No. 2 Phillips	1-7/8"	10	1.0 lbs.
72110	No. 3 Phillips	1-7/8"	10	1.0 lbs.
Bulk -	Fishbowl Display - 200	Bits		
72112	5 lbs. Bulk #6-#8 Flat	1-7/8"	1	5.0 lbs.
72114	5 lbs. Bulk #8-#10 Fla	t 1-7/8"	1	5.0 lbs.
72116	5 lbs. Bulk #10-#12 Fl	at 1-7/8"	1	5.0 lbs.
72118	5 lbs. Bulk PB1	1-7/8"	1	5.0 lbs.
72120	5 lbs. Bulk PB2	1-7/8"	1	5.0 lbs.
72122	5 lbs. Bulk PB3	1-7/8"	1	5.0 lbs.

screwdriver slippage... a reduction in the ejection forces...thus giving low wear, and longer tip life. Outlasts most power bits 5 to 1! Domestic high carbon, open hearth tool steel. Individually heat-treated. Industrial quality. Each bit 1-7/8" overall length.

### "Fit All" Power Bits 6" - 1/4" Hex Shank (2 Per Display Pk.)

Cat #	Description	Overall Length	Std. Pkg.	Wgt./Pkg.
72124	#6-#8 Flat Tip	6"	10	3.0 lbs.
72126	#8-#10 Flat Tip	6"	10	3.0 lbs.
72128	#10-#12 Flat Tip	6"	10	3.0 lbs.
72130	No. 1 Phillips	6"	10	3.0 lbs.
72132	No. 2 Phillips	6"	10	3.0 lbs.
72134	No. 3 Phillips	6"	10	3.0 lbs.

### **Quik-Change Chuck Adapter**

Change Power Bits and other 1/4" hex-shank tools fast with the Quik-Change chuck adapter. Inserts into 1/4" and 3/8" drill chucks.



	Cat #	Description	Std. Pkg.	Wgt./Pkg.
Carlos and	70420	Display Bag	5	1.00 lbs.
)	70421	Carded	10	1.40 lbs.

### **Blue Monster Advantage Closet Bolts**

Our bolt's patented broach-tip design gives the installer the direction of the foot underneath the flange. Each kit includes 2 solid brass bolts, 2 solid brass hex nuts, 2 solid brass open-ended acorn hex nuts, 4 stainless steel washers and 2 nylon tinnerman nuts. Not only does our bolt provide foot direction but also provides a true hold-back and breakoff eliminating the need for a hacksaw.





x 3-1/2"	100	16
Indicates foot direction		
finite creeses	00000	BLUE MONE

True (clean) break-off feature

The Mill-Rose Co. | Clean-Fit Products | 800.321.3598 | info@cleanfit.com | cleanfit.com



### Screwdrivers/Hand Tools & Storage Boxes

### **Deburring Tool**

The fast and easy way to smooth edges of pipe and tubing.

Remove rough or irregular I.D. edges on plastic, ferrous and nonferrous metals with Mill-Rose deburring tools. Fixed-blade "pencil" deburring tool clips on shirt pockets and fits anywhere. Standard deburring tool features hand-contoured handle and snap-on cap for convenient storage of replacement blades. Blades on pencil style tool can not be replaced.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70413	Pencil Deburring Tool - Carded	10	1.0 lbs.
70414	Pencil Deburring Tool - Bulk	24	1.5 lbs.
70415	Deburring Tool - Carded (3 Blades Included)	10	0.9 lbs.
70416	Deburring Tool-Bulk (3 Blades Included)	10	0.9 lbs.
70418	Deburring Tool - Carded (10 Blades Included)	10	2.7 lbs.
70417	Replacement Blades - 5/Bag	5	0.3 lbs.

### **Slip-Joint Pliers**

These slip joint pliers are made of chrome vanadium steel and have textured plastisol handles. Features include seven locking positions, a 2-1/8" capacity and pipe wrench style milled teeth.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
73060	10" Slip-Joint Pliers	12	14 lbs.

#### **Scissor-Action Cutter**



Cut soft plastic tubing and hose quick and easy. Features cast aluminum construction and easy-change, reversible blade for long-lasting performance. Cuts tubing and hose from 1/8" to 1-1/4" (3-31mm) 0.D.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
73003	Scissor-action Tube Cutter	5	3.0 lbs.
73010	Replacement Blades for #73003	10	1.0 lbs.

### S-25 Ratchet-Action Tube Cutter

The contractor's choice when cutting Schedule 40 materials (PVC, CPVC, ABS, vinyl, poly pipe and tubing). Features Molybdenum vanadium stainless steel blades.

	0 6		1
-	97	0	
	2		

Cat #	Description	Std. Pkg.	Wgt./Pkg.
73002	1" Ratchet-action Tube Cutter	5	7.0 lbs
73006	Replacement Blades for #73002	10	1.0 lbs.
73004	1-1/2" Rachet-action Tube Cutter	5	7.5 lbs.
73008	Replacement Blades for #73004	10	1.0 lbs.

#### **RINGCRUSHER®** Decrimping Tool

RINGCRUSHER<sup>®</sup> takes the work out of removing copper crimp rings and PEX tube from 1/2", 3/4" and 1" fittings. Stop wasting time using a hacksaw or torch, and stop throwing away expensive PEX fittings.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
73015	RINGCRUSHER bagged	5	3.79 lbs.

**RINGCRUSHER** Decrimping Tool...

- Removes copper crimp rings and PEX tubing from fittings in seconds!
- Cushion-grip handle.
- · Heavy-duty head with rounded anvil cuts fast.
- · Prevents damage to inside fittings.
- No more hacksaw, torch or frustration.
- Will not damage PEX fittings when used properly
- · Lets you recycle brass & poly alloy/plastic fittings.



# MR MILE 105E

### Screwdrivers/Hand Tools & Storage Boxes

Razorback™ Wrench - versatile wrench fits popular basket strainers and shower drains!







Mill-Rose designed this indispensible wrench to accommodate popular basket strainers and shower drains. The Razorback Wrench addresses these common problems:

- Many fiberglass shower bases have wood or material "glassed in" to provide support. This material often extends past the drain, preventing access to the ring nut. No problem for the Razorback Wrench!
- Showers installed on wood floors usually have 3" to 4" of space between the wood floor and the shower drain preventing access to the ring nut. No problem for the Razorback Wrench!
- Many shower installations place drains too close to support studs preventing access to the ring nut. No problem for the Razorback Wrench!
- The Razorback Wrench can also be used on some types of basket strainers.

A STATE OF STATE OF

Cat # Description
73055 Razorback

Razorback Wrench - boxed

6

Wgt./Pkg. 6.0 lbs.





Attractive point-of-sale packaging promotes use of the Razorback drain wrench.

### Water-Gate Water Shut Off Tools



Solder without draining the entire system! Change out a valve, solder or glue on fittings, make line repairs and test lines while under pressure with the Water-Gate. There's no need to shut off water to the rest of the building, drain lines, use bread clogs or freeze lines. Ideal for refrigeration and boiler applications, the Water-Gate's seals withstand temperatures from -20°F to 225°F. The Water-Gate water shut-off tool works on copper, steel or C/PVC lines and is pressure rated to 65 psi.



Attractive point-of-sale packaging and displays attract attention and promote use of the Water-Gate Tool. Impact-resistant case includes a complete range of tool sizes for virtually every application. Water-Gate



Cat #	Description	Std. Pkg.	Wgt./Pkg.	
Water-Ga		ota. i ky.	ingt./T kg.	
			0.0.11.5	
77000	1/2" Water-Gate Tool	1	0.9 lbs.	
77005	3/4" Water-Gate Tool	1	0.9 lbs.	
77010	1" Water-Gate Tool	1	1.0 lbs.	
77015	1-1/4" Water-Gate Tool	1	1.1 lbs.	
77020	1-1/2" Water-Gate Tool	1	1.2 lbs.	
77025	2" Water-Gate Tool	1	1.8 lbs.	
77030	2-1/2" Water-Gate Tool	1	2.5 lbs.	
77035	3" Water-Gate Tool	1	3.0 lbs.	
77040	4" Water-Gate Tool	1	3.5 lbs.	
Water-Gate Kits				
77070	1/2"-1" Water-Gate Kit	1	3.8 lbs.	
77080	1/2"-2" Water-Gate Kit	1	7.9 lbs.	
Water-Ga	te Replacement Seals			
77001	1/2" Replacement Seal	1	0.03 lbs.	
77006	3/4" Replacement Seal	1	0.07 lbs.	
77011	1" Replacement Seal	1	0.13 lbs.	
77016	1-1/4" Replacement Seal	1	0.21 lbs.	
77021	1-1/2" Replacement Seal	1	0.32 lbs.	
77026	2" Replacement Seal	1	0.56 lbs.	
77031	2-1/2" Replacement Seal	1	0.65 lbs.	
77036	3" Replacement Seal	1	0.75 lbs.	
77041	4" Replacement Seal	1	0.96 lbs.	
	• • • • • • • • • • • • • • • • • • • •			



## Screwdrivers/Hand Tools & Storage Boxes

Description

Standard 26" Cable Saw

Extended 44" Cable Saw

POP Display - 24 Std. Cable Saws

POP Display - 24 Ext. Cable Saws

### 6" Mini Hacksaw with Rubber Grip

This nickel plated Mini-Hacksaw has a 6" blade and a comfortable plastisol-dipped handle. Ideal for cutting metal in tight places, this Mini-Hacksaw cuts copper, brass, steel and other metals in places most hacksaws can't fit. A set of 10 replacement blades (carded) is also offered.



Cat #

70390

70391

70392

70393

# Cat #DescriptionStd. Pkg.Wgt./Pkg.703836" Mini-Hacksaw, Rubber Grip63.0 lbs.70384Replacement Blades for #7038360.5 lbs.(10 Blades)00.5 lbs.0.5 lbs.

0	
	2
A DESCRIPTION OF TAXABLE	

### **PVC Cable Saw**

This PVC cable saw cuts plumbing or electrical PVC and is faster than a hacksaw! Ideal for tight spots and inground repairs - the perfect tool for everyday cutting jobs. Display packaged - available in two lengths.

~	1.1	~		
()ı	uick		litte	٦r
G.	aion			~

This tool quickly cuts through plastic PVC and ABS pipe from the inside. It will cut wood for sink rims, closet flanges, shower drains, bath waste and overflow. It is great for hard to reach applications. The zinc plated dichromate dipped shank has a 1/4" hex shank for a secure grip. The strong steel blade is heat treated for longer wear.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
73025	Quik Cutter Tool	12	3.5 lbs.
73026	Replacement Blades 5/bag	6	0.5 lbs.

Std. Pkg.

20

20

1

1

Wgt./Pkg.

.06 lbs.

.07 lbs.

2.0 lbs.

2.0 lbs.



Cat #	Description	Std. Pkg.	Wgt./Pkg.				
Lock 'N Load Drybox							
75605	Carton	4	13.0 lbs.				
75610	Floor Display (10 cases)	1	34.0 lbs.				
Load 'N Go Tuff Box							
75630	Carton	4	17.0 lbs.				

The Lock 'N Load Heavy-Duty Drybox locks out moisture as well as dirt and grime. Three compartments store and organize tools and accessories. An easy access top compartment is ideal for small tools and parts. Lock 'N Load dimensions are 15" x 8" x 10".

The Load 'N Go Heavy-Duty Tuff Box is a "Contractor Grade" carrying case for storing, transporting and protecting tools, parts and fittings. Four compartments store and organize tools and accessories. Two easy-access compartments on top are ideal for small parts and fittings, plus a removable tray. Large capacity base (20" x 9.75" x 9.75").

# MR MILE SE

## Hand Tools, Heat Shields & Flame Blankets

### **Quick-Release Pliers for All Types of Push-Lock Fittings**

Remove all types of 3/8", 1/2" and 3/4" push-on fittings used with copper, PEX and CPVC materials with Mill-Rose Quick-Release Pliers. The plier's spring action makes for a quick and secure grip on tubing, even in hard to work areas where space is limited. These pliers feature a comfortable cushion-grip handle and heavy-duty design for years of service. Mill-Rose Quick-Release Pliers will save you time, aggravation and money removing push-on fittings.



### Arctic Armor Thermal Shield Gel

Blue Monster Arctic Armor creates a thermal barrier that protects surfaces from heat damage during soldering, welding and brazing operations. Spray on hard-to-reach surfaces or apply to any surface to shield studs, walls, floors and other surfaces from flames, sparks and molten splash. Arctic Armor's unique, no-drip gelled formula evaporates within 48 hours, eliminating cleanup.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
71028	Arctic Armor Thermal Shield Gel	12	48.0 lbs.
	valve seals and seats from heat dama soldered joints from loosening when s	0 0	0

- Protects wood, metal, plastic, rubber, wire, insulation, drywall, painted surfaces and more.
- Unique gelled formula sticks to surfaces without dripping or running
- Safe, non-toxic, harmless to skin, and odorless

### The Insurance Pad®



The Insurance Pad is the ultimate heat shield. Use wet or dry, where higher temperature protection and prolonged use is required. Great for use with acetylene air torches. The Insurance Pad delivers protection in excess of 2500°F, an incredible improvement over ceramic and fiberglass heat shields on the market. The Insurance Pad<sup>®</sup> is a fibrous-felt heat shield with the safest specs in the industry. Repeated use actually

Cat #	Description	Std. Pkg.	Wgt./Pkg.
71036	6" x 9" Display Pkg.	10	1.0 lbs
71038	9" x 12" Display Pkg.	10	1.8 lbs.

increases its heat resistance. Fibers in this heat shield take on graphite qualities when exposed to flame, increasing its heat resistance. Attractive point-of-sale packaging builds sales, plus the zip-lock bag provides added protection when not in use!

Custom sizes are available. Contact our Customer Service Department for information.



### Blue Monster Torch Guard Heat Shield

Shield studs, walls, floors and surfaces from flames, sparks and molten splash during soldering and brazing operations

Professional contractors appreciate the flame resistance and liability protection provided by Blue Monster Torch-Guard. It's asbestosfree (OSHA's Material Safety Data Sheet on Torch-Guard is available) and features highstrength needle-punched carbon fiber that stands up to heat while other materials peel, flake and break down. Ideal for confined working areas, Blue Monster Torch-Guard is

very flexible, easy to work with and provides heat resistance up to, but not exceeding  $2500^{\circ}$ F. This heat shield has two grommets for hanging, is flexible and will not peel, flake or break down.







## Numerical Index

		0-1 # D				a . # a	
Cat # Page	Cat # Page	Cat # Page	Cat # Page	Cat # Page	Cat # Page	Cat # Page	Cat # Page
0101521	0149122	3070024	3997123	6400511	6519518	6643013	6807512
0102521 0104521	0149222 0150022	3070125 3070724	3997323 3997523	6402011 6403011	6520018 6520518	6643113 6643513	6808112 6808512
0106021	0152022	3070825	3997723	6404011	6521018	6643613	6809112
0106521	0153822	3080024	6100011	6405011	6521518	6644013	6809512
0108021	0183622	3080125	6107011	6406011	6522018	6644113	6810112
0110022	0183722	3080824	6110211	6407011	6522518	6645013	6810512
0111022 0112022	0485022 0485622	3080925 3090024	6115011 6121011	6408011 6409011	6523018 6523518	6645113 6645513	6812012 6812112
0114022	0486022	3090125	6121111	6410011	6524018	6645613	6813012
0115721	0486522	3091025	6121211	6411511	6524518	6646013	6814012
0119021	0486722	3100024	6127011	6412511	6525018	6646113	7001025
0119221	0487022	3100125 3100624	6132111	6413511	6525518 6526018	6647013	7001626
0119421 0119822	0487522 0487822	3100824	6133011 6133211	6414511 6500019	6526518	6647113 6647213	7003026 7003526, 29
0120022	0488022	3100824	6139011	6500119	6527018	6647313	7003826, 29
0120222	0488222	3100925	6145011	6500219	6527518	6647413	7004025, 26
0120422	0488322	3101024	6145111	6500319	6528018	6647513	7004516
0120821 0121021	0488422 0488722	3101125 3110024	6145311 6150011	6500419 6500619	6528518 6529018	6647613 6648013	7005016 7006016
0121221	0488822	3110125	6150211	6500719	6529518	6648113	7006817
0121421	0489022	3110724	6156011	6500827	6530018	6648213	7007017
0121622	0489122	3110825	6156211	6500927	6530518	6648313	7008017
0121822 0122022	0489222 0490022	3111124 3111225	6162011 6162211	6501027 6501127	6531018 6531518	6648413 6648713	7009016 7009216
0122222	0490522	3120024	6200513	6501227	6532018	6649013	7010016
0122422	0491022	3120125	6202013	6501327	6532518	6649113	7010216
0122622	0496022	3120525	6203513	6501527	6533018	6649513	7011016
0125621	0496122	3120824	6205013	6501627	6533518	6649613	7011316
0125821 0126021	0496222 0496422	3121224 3121325	6206513 6208013	6501727 6502018	6534018 6534518	6650013 6650113	7012517 7013017
0126221	0496522	3140125	6209513	6502518	6535018	6651013	7014017
0126422	0497022	3141525	6211013	6503018	6535518	6651213	7015017
0126822	0501030	3141624	6233014	6503518	6536018	6651513	7015115
0127022 0127123	0501530 0502030	3142824 3161224	6234014 6235014	6504018 6504518	6536518 6537018	6652013 6652513	7015215 7015415
0127222	0506028	3161325	6236014	6505018	6537518	6653013	7015615
0127422	0506528	3310524	6237014	6505518	6538018	6653513	7016116
0127622	0507028	3311024	6238014	6506018	6538518	6654013	7016216
0127822 0128022	1741922 3000220, 24	3314024 3315024	6239014 6250014	6506518 6507018	6539018 6539518	6700511 6701011	7016316 7016416
0128621	3000320, 24	3317024	6250114	6507518	6540018	6701511	7016616
0129422	3000424	3318024	6250214	6508018	6540518	6702011	7016817
0132422	3000720, 24	3319024	6250314	6508518	6541018	6702511	7017017
0132622 0132822	3000924 3001525	3320024 3320524	6250514 6250614	6509018 6509518	6541518 6542018	6703011 6703511	7017115 7017215
0138822	3002120, 24	3320824	6251014	6510018	6542518	6704011	7017415
0139019	3002224	3321024	6282112	6510518	6543018	6704511	7017517
0139219	3002320, 24	3321124	6283112	6511018	6543518	6705011	7017615
0139419 0139822	3003120, 24 3003324	3321224 3321324	6284112 628259	6511518 6512018	6544018 6544518	6705511 6800112	7018017 7018615
0139922	3003525	3322224	628359	6512518	6545018	6800512	701894
0140022	3006120, 24	3322624	628459	6513018	6545518	6801112	701905
0140522	3006420, 24	3969025	6285012	6513518	6546018	6801512	701915
0141022 0144522	3006525	3991923 3992022	6300511	6514018 65145 19	6546518 6547018	6802112 6802512	701935 701955
0144522	3007124 3007324	3992022	6301511 6302511	6514518 6515018	6547518	6803112	701955
0145522	3040424	3992422	6303511	6515518	6550018	6803512	7019815
0146022	3045024	3992526	6305011	6516018	6550218	6804112	7019915
0147022	3050024	3995026	6306011 63075 11	6516518 65170 18	6550418 65506 18	6804512 68051 12	702005
0147522 0147822	3050125 3060024	3996022 3996122	6307511 6308511	6517018 6517518	6550618 6641013	6805112 6805512	702025 702035
0148022	3060125	3996222	6309511	6518018	6641113	6806112	702045
0148122	3060624	3996322	6310511	6518518	6642013	6806512	702075
0149022	3060725	3996422	6311511	6519018	6642113	6807112	702085

# Numerical Index

Cat # Pag	ge Cat #	Page Cat #	Page Cat #	Page Cat	# Page	Cat #	Page Ca	t # Page	Cat # Pag	ge
702095	70460				4229	77025		405220	8492020	
7021028					4429	77026		405420	8493020	
7021128					6430	77030		405520	9400011	
7022028					4031	77031		406020	9401011	
7022128					4131	77035		406520	9402011	
7023028					5431	77036		406620	9403011	
7023128					5631	77040		407020	9404011	
7024028					7131	77041		409020	9405011	
7025514					8031	77070 77080		410520	9406011 9407011	
7025814 7025914					8131 8331	77080		410620	9407011	
7025914					8531	83002		410820 411020	9408511	
7026014					0030	83002		411220	9409011	
7026314					0830	83005		420023	9410011	
7026414					1018	83010		420123	9410511	
7026514					0030	83015		420223	9600012	
7026814					1030	83020		420323	9600112	
7026914					0537	83025		420423	9601012	
7027014					1037	83030		420523	9601112	
7027114			2 72145.		3037	83035		420723	9602012	
7028414					006	83040		420823	9602112	
7028514		28 70887			016	83045		421023	9603012	2
702905	70650				036	83050		421123	9603112	2
703005	70658	4 70891	7 72156.	13 7600	056	83055	20 84	421223	9604012	2
703025	70659	2 70892	7 73002.	35 7600	076	83060		421423	9604112	2
703045	70660	2 70893	7 73003.	35 7600	096	83065	20 84	421523	9605012	2
703065	70661				116	83070		421623	9605112	
703085	70662				156	83085		433127	9606012	
703105	70663				176	83100		433227	9606112	
703265	70664		28 73010.		196	84002		433327	9607012	
7038337					236	84003		433427	9607112	
7038437					208	84005		435127	9608012	
7038530					228	84006		435227	9608112	
7038630					248	84007		437127	9609012	
7038730					268	84008		437227	9609112	
7038830					256	84009		437327	9610012 9610112	
7039037 7039137					276 296	84010 84011		437427 437527	9610512	
7039137					290 559	84011		437719	9610612	
7039237					559 579	84015		438027	9611012	
70395					599	84023		438527	9611112	
7040032					8410	84025		481020		
7041232		4 72016			8510	84026	20 84	481520		
7041335					8610	84027		482020		
7041435					0036	84028		483020		
7041535					0136	84029		484020		
7041635					0536	84030		484520		
7041735	70807			28 7700	0636	84032		485020		
7041835	70811	7 72093	33 73822.		1036	84033	20 84	486020		
7042034	70820	3 72098			1136	84034	20 84	487020		
7042134					1536	84035		488020		
7043029					1636	84040		489020		
7044029					2036	84045		490020		
7045029	70824	3 72106	34 73838.	29 7702	2136	84050	20 84	491020		

40



## **Display Products**

### **Build Sales with Customized Point-of-Purchase Merchandising Displays**

In addition to a comprehensive assortment of bagged and carded products, Mill-Rose offers *customized point-of-purchase merchandising displays.* Build sales at the point-of-purchase with these attractive displays.

- Increase sales of most profitable items.
- Assists inventory control.
- Displays and products are interchangeable.

Designed for areas with limited space, these visual merchandisers offer maximum product visibility for planned and impulse buying, and provide faster product turnover. Mill-Rose merchandising displays are flexible and allow you to promote and display products best-suited for your customer base.

Sample displays are shown here. Contact customer service for a complete list of displays and planograms.

Blue Monster® 24" Gondola Display

onal Grade Products

BLUE MONSTER

### Water-Gate Plan-O-Gram #3 24" x 36" Display



### Blue Monster® 48" Gondola Display



# HVAC Brushes Befriceration Elizabeth TECENFERENCEUSES Mair Ander Wire Bruter Chin Brushes Products For Plumbing 7310 Corporate Blvd. Oil & Gas Industry Mentor, OH 44060 Pipes, Valves & Fittings Phone 440.974.6730 Refrigeration 800.321.3598 Fax 440.255.1072 Insulation Sheet Metal Fabrication Bar-B-Que www.CleanFit.com Industry Ventilation Appliance Parts & Service Mechanical Service Residential DIY Market Oil & Hydraulic Heating Government Commercial Pliers Six in (