



DESIGN FEATURES

Perfect for water heaters

Quick-Fill for Roman tub faucets

- Chloramine resistant washers
- Exclusive POWR-TIGHT 12-point crimp-many times industry standard
- Chloramine resistant tubing
- Withstands dramatic changes in water pressure
- Easy installation, no special tools or soldering required.

MATERIAL SPECIFICATIONS

- Working Pressure: 160 psi
- Operating Temperature: 33° F - 140° F
- Tubing: Reinforced PVC, NSF 61 Compliant
- Nuts & End Fittings: Brass
- Washers: NSF 61 Compliant

COMPLIANCES/LISTINGS

- IAPMO Certified
- NSF Compliant
- ASME A112.18.6



3689 Arrowhead Drive, Carson City, NV 89706

Phone (800) 854-3215 Fax (800) 243-1777

E-mail sales@lspproducts.com Website www.lspproducts.com

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained.

AF/S-2008 (04-08) Rev 3

ULTRACORE WATER HEATER CONNECTORS Specification Sheet

Part Number	Description	Length
WHC-112-PP	3/4" MIP X 3/4" ID Comp Coupling	12"
WHC-118-PP		18"
WHC-124-PP		24"
WHC-512-PP	3/4" MIP X 1/2" ID Comp Coupling	12"
WHC-518-PP		18"
WHC-524-PP		24"
WHF-112-PP	3/4" MIP x 3/4" FIP	12"
WHF-118-PP		18"
WHF-124-PP		24"
WHL-2118-PP	3/4" MIP x 3/4" CPVC Socket	18"
WHL-2124-PP		24"
WHJ-2118-PP	3/4" MIP x 3/4" PEX Barb*	18"
WFC-112-PP	3/4" FIP x 3/4" ID Comp Coupling	12"
WFC-118-PP		18"
WFC-124-PP		24"
WFC-512-PP	3/4" FIP x 1/2" ID Comp Coupling	12"
WFC-518-PP		18"
WFC-524-PP		24"
WFF-112-PP	3/4" FIP x 3/4" FIP	12"
WFF-118-PP		18"
WFF-124-PP		24"
WFL-2112-PP	3/4" FIP x 3/4" CPVC Socket	12"
WFL-2118-PP		18"
WFJ-2118-PP	3/4" FIP x 3/4" PEX Barb*	18"

*PEX Connectors are not IAPMO certified.

Product Submittal		
Job Name		
Date		
Part Number	Quantity	
Architect		
Contractor		