

SAMMYS SWIVEL HEAD™ FOR CONCRETE - Swivel Application



MADE WITH Tapcon



#14 SH Orange Nut Driver
Part # 8273910

Application



Product Features

- Installs vertically and swivels up to 89° in wood & concrete structures.
- Eliminates distortion of threaded rod.
- 1/4" pre-drilled pilot hole required.
- Concrete installation tool available for a one piece installation process.
- Assembled in the U.S.A.

Approvals	Rod Size	Part Number	Model	Screw Descriptions	Ultimate Shear (lbs)*	Box Qty	Case Qty
SWIVEL MOUNT							
	3/8"	8269957	SH-GST/CST 20	5/16 x 1-3/4"	2537 in 3000 psi concrete 1459 @ 45° off vertical in 3000 psi concrete 2852 in 6000 psi concrete 1636 @ 45° off vertical in 6000 psi concrete	25	125
	3/8"	8308957	SH-CCST 516	5/16-14 x 2-1/2"	857**	25	125

Note: UL Listed for wood - see page 5


* Tested in 3000 PSI concrete ** Pullout strength for cracked concrete and Seismic Zones A-F

CONCRETE / WOOD INSTALLATION KIT




Application

Rotary Hammer Drill into concrete



Hammer Drill into concrete



Part Number	Description	Each Qty
8122910	Concrete Installation Kit (a)	1

Kit includes the following items:

8113910	#14 Black Nut Driver (b)	1
8114910	#14 SW Red Nut Driver (c)	1
8116910c	#250 Bit (1/4") (d)	1
8117910	SDS Bit (1/4") (e)	1
8118910	7/32 Wood Bit (f)	1
8120910	HEX 250 Bit Receiver (1/4") (g)	1
8098910	SL 250 Sleeve (h)	1