

FILTER systems

DW-600 Deluxe Drinking Water



DW-600

600-R

- Point-of-Use filter system
- Features a single, compact quick-change cartridge
- Includes all installation hardware

- Works with copper, plastic or flexible tubing
- 500-gallon capacity



Tested and Certified by NSF International.

COMPONENT

Model Number	Part Number	Reduces	I/O	Overall Dimensions	Rating (nominal)	Operating Pressure	Operating Temperature
DW-600	158573	Lead, Cysts, Lindane, Atrazine, Chlorine Taste & Odor, Sediment	1/4"	3" x 3" x 13 1/2"	0.5 micron	30-125 psi	40-100°F
Replacement Cartridge							
600R	155785-51	Lead, Cysts, Lindane, Atrazine, Chlorine Taste & Odor, Sediment	—	2 1/2" x 2 1/2" x 12 1/2"	0.5 micron	30-125 psi	40-100°F

WLCS-1000 Chemical/Lead



WLCS-1000

- Point-of-Use filter system
- Effectively reduces a wide range of chemicals and other contaminants
- System includes an electronic monitor for filter replacement
- 1,000 gallon capacity

- No storage tank or recovery time is required
- Provides great-tasting water on demand
- Completely assembled and ready to install conveniently under the sink



Tested and Certified by NSF International.

COMPONENT

Model Number	Part Number	Reduces	I/O	Overall Dimensions	Rating (nominal)	Operating Pressure	Operating Temperature
WLCS-1000	152077	99% of Dissolved Lead, > 99.5% of <i>Giardia</i> & <i>Cryptosporidium</i> Cysts, Mercury, Asbestos, Bad Taste & Odor, Chlorine Taste & Odor, Sediment	1/4" tube	11" x 6 1/2" x 15"	0.5 micron	30-125 psi	40-100°F
Replacement Cartridge Kit							
W-250	155584-51	99% of Dissolved Lead, 99.5% of <i>Giardia</i> & <i>Cryptosporidium</i> Cysts, Mercury, Asbestos, Chlorine Taste & Odor, Sediment	—	—	0.5 micron	30-125 psi	40-100°F